

SaRonix

Voltage Controlled Crystal Oscillator

3.3V, LVCMOS

Technical Data

S1300 / S1309 / ST1300 / ST1309 Series




Description

A 3.3V, voltage controlled crystal oscillator with output logic levels compatible with LVCMOS and LVTTTL logic families. The series is designed with excellent Jitter characteristics which makes it ideal for use in Telecom and Datacom applications. True SMD DIL versions for IR reflow are available, select option "S" in part number builder. See separate data sheet for SMD package dimensions.

Applications & Features

- Phase-Locked Loop (PLL) Clock and Data Recovery, Frequency Transaltion, Frequency Synthesis apps in Video, Video Compression, Telephony, and LAN/WAN Data Communication
- 3.3 Volt operations
- LVCMOS / LVTTTL compatible
- 3.5ps max RMS period jitter
- Wide range of performance options:
 - ±50 to ±100 ppm APR*
 - ±20 to ±50 ppm Frequency Stability
- Tri-State option
- True SMD for IR reflow available

Output Waveform



Frequency Range:	1.5 MHz to 28.6363 MHz
Frequency Stability:	±20, ±25 or ±50ppm over all conditions: operating temperature, voltage change, load change, calibration tolerance, shock and vibration, with $V_C = 1.65V$
Aging @ 25°C:	± 3ppm max per year, ±10ppm max for 10 years

Temperature Range:	
Operating:	0 to +70°C or -40 to +85°C
Storage:	-55 to +125°C

Supply Voltage:	
Recommended Operating:	3.3V ±10%

Supply Current:	10mA typ, 15mA max
------------------------	--------------------

Output Drive:	
Symmetry:	45/55% max @ 50% VDD
Rise & Fall Times:	9ns max 20% to 80% VDD
Logic 0:	10% VDD max
Logic 1:	90% VDD min
Load:	30pF
Jitter:	3.5ps max RMS period jitter

Pull Characteristics:	
Input Impedance (pin 1):	50KΩ min
Frequency Response (-3dB):	10 kHz min
Pullability:	±50, ±70, ±100ppm APR* min
Control Voltage:	0.3 to 3.0V
Transfer Function:	Frequency Increases when Control Voltage Increases
Linearity:	5 or 10% max
Center Control Voltage:	1.65V

Mechanical:	
Shock:	MIL-STD-883, Method 2002, Condition B
Solderability:	MIL-STD-883, Method 2003
Terminal Strength:	MIL-STD-883, Method 2004, Condition B2
Vibration:	MIL-STD-883, Method 2007, Condition A
Solvent Resistance:	MIL-STD-202, Method 215
Resistance to Soldering Heat:	MIL-STD-202, Method 210, Conditions A, B or C (I or J for Gull Wing)

Environmental:	
Gross Leak Test:	MIL-STD-883C, Method 1014, Condition C
Fine Leak Test:	MIL-STD-883C, Method 1014, Condition A2
Thermal Shock:	MIL-STD-883C, Method 1011, Condition A
Moisture Resistance:	MIL-STD-883C, Method 1004

* APR = (VCXO Pull relative to specified Output Frequency) – (VCXO Frequency Stability)
NOTE: APR is inclusive of 10 Years Aging

SaRonix


Voltage Controlled Crystal Oscillator

3.3V, LVCMOS

Technical Data

S1300 / S1309 / ST1300 / ST1309 Series

Package Details




Pin Function:

- Pin 1: Control Voltage
- Pin 3: Tri-State control (optional)
- Pin 7: GND/Case (VSS)
- Pin 8: OUTPUT
- Pin 12: N/C (optional)
- Pin 14: +3.3VDC (VDD)


Marking Format**

Includes Date Code, Frequency & Part Number



Denotes Pin 1

HALF SIZE PACKAGE



Marking Format**


Includes Date Code, Frequency & Part Number



Denotes Pin 1

**Exact location of items may vary
Scale: None (Dimensions in $\frac{mm}{inches}$)

Part Numbering Guide




** APR = (VCXO Pull relative to specified Output Frequency) - (VCXO Frequency Stability)
NOTE: APR is inclusive of 10 Years Aging

Tri-State Logic Table

Pin 3(2) Input	Pin 8(5) Output
Logic 1 or NC	Oscillation
Logic 0 or GND	High Impedance

Required Input Levels on Pin 3(2):
Logic 1 = 0.7 V_{DD} min
Logic 0 = 0.3 V_{DD} max

Test Circuit







NOTE A: C_L includes probe and fixture capacitance
* Items in brackets () represent Half Size model

All specifications are subject to change without notice.

SaRonix

True SMD Adaptor

Technical Data



RECOMMENDED LAND PATTERN

