


TQM676021

Advance Data Sheet

WCDMA / HSUPA Band I Tritium III PA-Duplexer Module™

Functional Block Diagram



Product Description

The Tritium III PAD Module [™] is an integrated 3V Linear Power Amplifier, Duplexer and Transmit Filter Module including a highly accurate Output Power Detector designed for mobile UMTS handset applications, supporting HSUPA operation with transmission datarates up to 10Mb/s.

It features 2 output power modes, additional continuous bias in low power mode, low off and standby currents, and a separate pin for module enable. RF input and output matching is included within the module; therefore, minimal external circuitry is required. Tritium III gives excellent RF performance with low current consumption resulting in longer talk times in portable applications. The tiny 7x4x1.1 mm³ surface mount package is ideal for new generation slim, small and light phones.

Electrical Specifications

Parameter	Min	Тур	Max	Units
Frequency	1922.4		1977.6	MHz
Linear P _{OUT} (HSUPA) high power mode	The Table	25.2	COM	dBm
Maximum current high power mode	THE WAY	450		mA
Linear P _{OUT} (HSUPA) low power mode	MAL.	16.2		dBm
Idle current low power mode		15		mA
ACPR (HS <mark>UPA) 5 MH</mark> z		-45		dBc
ALPR (HSUPA) 10 MHz		-60		dBc
Ant-to-RX Insertion Loss		2		dB

Test Conditions: $V_{CC1} = V_{CC2} = 3.4 \text{ V}, T = 25^{\circ}\text{C}$

dvance Data Sheet: Subject to change without notice

Features

- Handset Tritium III™ (PA-Duplexer)
 Module for UMTS Band I (IMT2100
 band)
- Specified for HSUPA Modulation (Transmission Data-Rates up to 10Mb/s)
- Integrates Power Amplifier, Highly Accurate Output Power Detector, Transmit Filter and Duplexer
- No Regulated Voltage Required
- Separate 'Module Enable' Pin
- All RF Ports Matched to 50 Ω
- Low Current Consumption:
 - 2 Power Modes
 - Continuous Bias in Low Power Mode
 - Extremely Low Idle Current
 (15mA typ.) in Low Power Mode
- Compatible for Low Collector Voltage Operation with DC-DC-Converters

Applications

3G UMTS Handsets and Data-Cards

Package Style

 Compact 7 x 4 x 1.1 mm³ 16-Pin LGA Package

