



ZXTP23015CFH

15V, SOT23, PNP medium power transistor

Summary

$V_{(BR)CES} > -15V, V_{(BR)CEO} > -15V$


$V_{(BR)ECO} > -6V$

$I_{C(CONT)} = -6A$

$R_{CE(SAT)} = 20m\Omega$ typical

$V_{CE(SAT)} < -36mV @ -1A$


$P_D = 1.25W$



Complementary part number ZXTN23015CFH

Description

Advanced process capability and package design have been used to maximize the power handling and performance of this small outline transistor. The compact size and ratings of this device make it ideally suited to applications where space is at a premium.




Feature

- Higher power dissipation SOT23 package
- High peak current
- Low saturation voltage
- 15V forward blocking voltage
- 6V reverse blocking voltage

Applications

- High side disconnect switches
- DC - DC converters
- MOSFET and IGBT gate driving
- Motor drive
- Relay, lamp, and solenoid drive



Pinout - top view

Ordering information

Device	Reel size (inches)	Tape width	Quantity per reel
ZXTP23015CFHTA	7	8mm	3000

Device marking

317

ZXTP23015CFH

Absolute maximum ratings

Parameter	Symbol	Limit	Unit
Collector-base voltage	V_{CBO}	-15	V
Collector-emitter voltage	$V_{(BR)CES}$	-15	V
Collector-emitter voltage	V_{CEO}	-15	V
Emitter-base voltage	V_{EBO}	-7.0	V
Emitter-collector voltage	V_{ECO}	-6.0	V
Peak pulse current	I_{CM}	-10	A
Continuous collector current ^(c)	I_C	-5	A
Continuous collector current ^(d)	I_C	-6	A
Base current	I_B	-1.2	A
Power dissipation @ $T_A=25^{\circ}C^{(a)}$ Linear derating factor ^(a)	P_D	0.73 5.84	W mW/°C
Power dissipation @ $T_A=25^{\circ}C^{(b)}$ Linear derating factor ^(b)	P_D	1.05 8.4	W mW/°C
Power dissipation @ $T_A=25^{\circ}C^{(c)}$ Linear derating factor ^(c)	P_D	1.25 9.6	W mW/°C
Power dissipation @ $T_A=25^{\circ}C^{(d)}$ Linear derating factor ^(d)	P_D	1.81 14.5	W mW/°C
Operating and storage temperature	$T_j; T_{stg}$	-55 to +150	°C

Thermal resistance

Parameter	Symbol	Value	Unit
Junction to ambient ^(a)	$R\theta_{JA}$	171	°C/W
Junction to ambient ^(b)	$R\theta_{JA}$	119	°C/W
Junction to ambient ^(c)	$R\theta_{JA}$	100	°C/W
Junction to ambient ^(d)	$R\theta_{JA}$	69	°C/W

NOTES:

(a) For a device surface mounted on 15mm x 15mm x 1.6mm FR4 PCB with high coverage of single sided 1oz copper, in still air conditions.





(b) Mounted on 25mm x 25mm x 1.6mm FR4 PCB with a high coverage of single sided 2 oz copper in still air conditions.

(c) Mounted on 50mm x 50mm x 1.6mm FR4 PCB with a high coverage of single sided 2 oz copper in still air conditions.

(d) As (c) above measured at $t < 5$ secs.

ZXTP23015CFH

Characteristics



ZXTP23015CFH

ELECTRICAL CHARACTERISTICS (at $T_{AMB} = 25^{\circ}\text{C}$ unless otherwise stated)






Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions
Collector-base breakdown voltage	$V_{(BR)CBO}$	-15	-40		V	$I_C = -100\mu\text{A}$
Collector-emitter breakdown voltage	$V_{(BR)CES}$	-15	-40		V	$I_C = -100\mu\text{A}$
Collector-emitter breakdown voltage	$V_{(BR)CEO}$	-15	-25		V	$I_C = -10\text{mA}^{(*)}$
Emitter-base breakdown voltage	$V_{(BR)EBO}$	-7.0	-8.2		V	$I_E = -100\mu\text{A}$
Emitter-collector breakdown voltage	$V_{(BR)ECO}$	-6.0	-8.5		V	$I_E = -100\mu\text{A}$
Collector-emitter cut-off current	I_{CES}			-20	nA	$V_{CE} = -12\text{V}$
Collector-base cut-off current	I_{CBO}			-20	nA	$V_{CB} = -12\text{V}$
Emitter-base cut-off current	I_{EBO}			-10	nA	$V_{EB} = -6\text{V}$
Static forward current transfer ratio	H_{FE}	200 200 140	380 350 220	560		$I_C = -10\text{mA}, V_{CE} = -2\text{V}^{(*)}$ $I_C = -500\text{mA}, V_{CE} = -2\text{V}$ $I_C = -6\text{A}, V_{CE} = -2\text{V}$
Collector-emitter saturation voltage	$V_{CE(sat)}$		-6 -27 -90 -140	-10 -36 -120 -190	mV mV mV mV	$I_C = -100\text{mA}, I_B = -10\text{mA}^{(*)}$ $I_C = -1\text{A}, I_B = -100\text{mA}^{(*)}$ $I_C = -3\text{A}, I_B = -60\text{mA}^{(*)}$ $I_C = -6\text{A}, I_B = -240\text{mA}^{(*)}$
Base-emitter saturation voltage	$V_{BE(sat)}$		-0.83 -0.93	-0.93 -1.03	V V	$I_C = -3\text{A}, I_B = -60\text{mA}^{(*)}$ $I_C = -6\text{A}, I_B = -240\text{mA}^{(*)}$
Base-emitter turn-on voltage	$V_{BE(on)}$		-0.83	-0.93	V	$I_C = -6\text{A}, V_{CE} = -2\text{V}^{(*)}$
Transition frequency	f_T		270		MHz	$I_C = -500\text{mA}, V_{CE} = -2\text{V}, f = 50\text{MHz}$
Output capacitance	C_{obo}		78.4		pF	$V_{CB} = -10\text{V}, f = 1\text{MHz}$
Delay time	$t_{(d)}$		14		ns	$V_{CC} = -5\text{V}, I_C = -3\text{A}, I_{B1} = I_{B2} = -150\text{mA}$
Rise time	$t_{(r)}$		35		ns	
Storage time	$t_{(stg)}$		138		ns	
Fall time	$t_{(f)}$		17.4		ns	

NOTES:

(*) Measured under pulsed conditions. Pulse width = $300\mu\text{s}$. Duty cycle $\leq 2\%$.


ZXTP23015CFH

Typical characteristics



ZXTP23015CFH

Package outline - SOT23



Dim.	Millimeters		Inches		Dim.	Millimeters		Inches	
	Min.	Max.	Min.	Max.		Min.	Max.	Max.	Max.
A	2.67	3.05	0.105	0.120	H	0.33	0.51	0.013	0.020
B	1.20	1.40	0.047	0.055	K	0.01	0.10	0.0004	0.004
C	-	1.10	-	0.043	L	2.10	2.50	0.083	0.0985
D	0.37	0.53	0.015	0.021	M	0.45	0.64	0.018	0.025
F	0.085	0.15	0.0034	0.0059	N	0.95 NOM		0.0375 NOM	
G	1.90 NOM		0.075 NOM		-	-	-	-	-

Note: Controlling dimensions are in millimeters. Approximate dimensions are provided in inches

Europe

Zetex GmbH
Streitfeldstraße 19
D-81673 München
Germany

Telefon: (49) 89 45 49 49 0
Fax: (49) 89 45 49 49 49
europe.sales@zetex.com

Americas

Zetex Inc
700 Veterans Memorial Highway
Hauppauge, NY 11788
USA

Telephone: (1) 631 360 2222
Fax: (1) 631 360 8222
usa.sales@zetex.com

Asia Pacific

Zetex (Asia Ltd)
3701-04 Metroplaza Tower 1
Hing Fong Road, Kwai Fong
Hong Kong

Telephone: (852) 26100 611
Fax: (852) 24250 494
asia.sales@zetex.com

Corporate Headquarters

Zetex Semiconductors plc
Zetex Technology Park, Chadderton
Oldham, OL9 9LL
United Kingdom

Telephone: (44) 161 622 4444
Fax: (44) 161 622 4446
hq@zetex.com

For international sales offices visit www.zetex.com/offices

Zetex products are distributed worldwide. For details, see www.zetex.com/salesnetwork

This publication is issued to provide outline information only which (unless agreed by the company in writing) may not be used, applied or reproduced for any purpose or form part of any order or contact or be regarded as a representation relating to the products or services concerned. The company reserves the right to alter without notice the specification, design, price or conditions of supply of any product or service.