


[查询CM15MD-24H供应商](#)

MITSUBISHI IGBT MODULES
捷多邦, 专业PCB打样工厂, 24小时加急出货

CM15MD-24H

MEDIUM POWER SWITCHING USE
INSULATED TYPE

CM15MD-24H



- IC 15A
- VCES 1200V
- Insulated Type
- CIB Module
- 3φ Inverter+3φ Converter+Brake
- UL Recognized

Yellow Card No. E80276 (N)


File No. E80271

APPLICATION

AC & DC motor controls, General purpose inverters, Servo controls, NC, Robotics

OUTLINE DRAWING & CIRCUIT DIAGRAM

Dimensions in mm



CM15MD-24H

MEDIUM POWER SWITCHING USE
INSULATED TYPE**MAXIMUM RATINGS** ($T_j = 25^\circ\text{C}$)**INVERTER PART**

Symbol	Parameter	Condition	Rating	Unit
VCES	Collector-emitter voltage	G – E Short	1200	V
VGES	Gate-emitter voltage	C – E Short	± 20	V
Ic	Collector Current	$T_c = 25^\circ\text{C}$	15	A
ICM		PULSE (Note. 2)	30	A
IE (Note. 1)	Emitter Current	$T_c = 25^\circ\text{C}$	15	A
IEM (Note. 1)		PULSE (Note. 2)	30	A
PC (Note. 3)	Maximum collector dissipation	$T_f = 25^\circ\text{C}$	66	W

BRAKE PART

Symbol	Parameter	Condition	Rating	Unit
VCES	Collector-emitter voltage	G – E Short	1200	V
VGES	Gate-emitter voltage	C – E Short	± 20	V
Ic	Collector Current	$T_c = 25^\circ\text{C}$	15	A
ICM		PULSE (Note. 2)	30	A
PC (Note. 3)	Maximum Collector dissipation	$T_f = 25^\circ\text{C}$	66	W
VRRM	Repetitive peak reverse voltage	Clamp diode part	1200	V
IFM (Note. 3)	Forward current	Clamp diode part	15	A

CONVERTER PART

Symbol	Parameter	Condition	Rating	Unit
VRRM	Repetitive peak reverse voltage		1600	V
Ea	Recommended AC input voltage		440	V
Io	DC output current	3 ϕ rectifying circuit	15	A
IFSM	Surge (non-repetitive) forward current	1 cycle at 60Hz, peak value Non-repetitive	150	A
I ² t	I ² t for fusing	Value for one cycle of surge current	93	A ² s

COMMON RATING

Symbol	Parameter	Condition	Rating	Unit
Tj	Junction temperature		-40 ~ +150	$^\circ\text{C}$
Tstg	Storage temperature		-40 ~ +125	$^\circ\text{C}$
Viso	Isolation voltage	AC 1 min.	2500	V
—	Mounting torque	Mounting M4 screw	0.98 ~ 1.47	N·m
—	Weight	Typical value	100	g

CM15MD-24H

MEDIUM POWER SWITCHING USE
INSULATED TYPEELECTRICAL CHARACTERISTICS (T_j = 25°C)

INVERTER PART

Symbol	Parameter	Test conditions	Limits			Unit
			Min.	Typ.	Max.	
ICES	Collector cutoff current	VCE = VCES, VGE = 0V	—	—	1	mA
VGE(th)	Gate-emitter threshold voltage	IC = 1.5mA, VCE = 10V	4.5	6	7.5	V
IGES	Gate-emitter cutoff current	VGE = VGES, VCE = 0V	—	—	0.5	μA
VCE(sat)	Collector-emitter saturation voltage	T _j = 25°C	—	2.7	3.4	V
		T _j = 150°C	—	2.45	—	
Cies	Input capacitance	VCE = 10V VGE = 0V	—	—	3.0	nF
Coes	Output capacitance		—	—	2.4	nF
Cres	Reverse transfer capacitance		—	—	0.6	nF
QG	Total gate charge	VCC = 600V, IC = 15A, VGE = 15V	—	75	—	nC
td (on)	Turn-on delay time	VCC = 600V, IC = 15A	—	—	100	ns
tr	Turn-on rise time	VGE1 = VGE2 = 15V	—	—	200	ns
td (off)	Turn-off delay time	RG = 21Ω	—	—	150	ns
tf	Turn-off fall time	Resistive load	—	—	350	ns
VEC (Note. 1)	Emitter-collector voltage	IE = 15A, VGE = 0V	—	—	3.5	V
trr (Note. 1)	Reverse recovery time	IE = 15A, VGE = 0V	—	—	250	ns
Qrr (Note. 1)	Reverse recovery charge	die / dt = - 30A / μs	—	0.11	—	μC
R _{th(j-f)Q} (Note. 5)	Thermal resistance	IGBT part, Per 1/6 module	—	—	1.9	°C/W
R _{th(j-f)R} (Note. 5)		FWDi part, Per 1/6 module	—	—	2.4	°C/W

BRAKE PART

Symbol	Parameter	Condition	Limits			Unit
			Min.	Typ.	Max.	
ICES	Collector cutoff current	VCE = VCES, VGE = 0V	—	—	1	mA
VGE(th)	Gate-emitter threshold voltage	IC = 1.5mA, VCE = 10V	4.5	6	7.5	V
IGES	Gate-emitter cutoff current	VGE = VGES, VCE = 0V	—	—	0.5	μA
VCE(sat)	Collector-to-emitter saturation voltage	T _j = 25°C	—	2.7	3.4	V
		T _j = 150°C	—	2.45	—	
Cies	Input capacitance	VCE = 10V VGE = 0V	—	—	3.0	nF
Coes	Output capacitance		—	—	2.4	nF
Cres	Reverse transfer capacitance		—	—	0.6	nF
QG	Total gate charge	VCC = 600V, IC = 15A, VGE = 15V	—	75	—	nC
VFM	Forward voltage drop	IF = 15A, Clamp diode part	—	—	1.5	V
R _{th(j-f)Q} (Note. 5)	Thermal resistance	IGBT part	—	—	1.9	°C/W
R _{th(j-f)R} (Note. 5)		Clamp diode part	—	—	1.7	°C/W

CONVERTER PART

Symbol	Parameter	Condition	Limits			Unit
			Min.	Typ.	Max.	
IRRM	Repetitive reverse current	VR = VRRM, T _j = 150°C	—	—	8	mA
VFM	Forward voltage drop	IF = 15A	—	—	1.5	V
R _{th(j-f)} (Note. 5)	Thermal resistance	Per 1/6 module	—	—	1.7	°C/W

Note 1. IE, VEC, trr, Qrr & die/dt represent characteristics of the anti-parallel, emitter to collector free-wheel diode.

2. Pulse width and repetition rate should be such that the device junction temp. (T_j) does not exceed T_{jmax} rating.

3. Junction temperature (T_j) should not increase beyond 150°C.

4. Pulse width and repetition rate should be such as to cause negligible temperature rise.

5. Thermal resistance is specified under following conditions.


- The conductive grease applied, between module and fin.
- Al plate is used as fin.

CM15MD-24H


MEDIUM POWER SWITCHING USE
INSULATED TYPE

PERFORMANCE CURVES


OUTPUT CHARACTERISTICS
(TYPICAL)




TRANSFER CHARACTERISTICS
(TYPICAL)




COLLECTOR-EMITTER SATURATION
VOLTAGE CHARACTERISTICS
(TYPICAL)




COLLECTOR-EMITTER SATURATION
VOLTAGE CHARACTERISTICS
(TYPICAL)



FREE-WHEEL DIODE
FORWARD CHARACTERISTICS
(TYPICAL)




CAPACITANCE VS. Vce
(TYPICAL)




CM15MD-24H

MEDIUM POWER SWITCHING USE
INSULATED TYPE


HALF-BRIDGE SWITCHING CHARACTERISTICS (TYPICAL)




REVERSE RECOVERY CHARACTERISTICS OF FREE-WHEEL DIODE (TYPICAL)



TRANSIENT THERMAL IMPEDANCE CHARACTERISTICS (IGBT part)



TRANSIENT THERMAL IMPEDANCE CHARACTERISTICS (FWDi part)



VGE - GATE CHARGE (TYPICAL)

