

FEATURES

- Low forward voltage : $V_{F(3)}=0.9V$ (typ.)
- Fast reverse recovery time : $t_{rr}=1.6ns$ (typ.)

MARKING: F3

SOT-23



1. ANODE
2. N.C.
3. CATHODE

Maximum Ratings @ $T_A=25^\circ C$

Parameter	Symbol	Limits		Unit
Non-Repetitive Peak reverse voltage	V_{RM}	85		V
DC Blocking Voltage	V_R	80		V
Forward Continuous Current	I_{FM}	300		mA
Average Rectified Output Current	I_O	100		mA
Power Dissipation	P_D	150		mW
Junction temperature	T_J	125		°C
Storage temperature range	T_{STG}	-55-125		°C

Electrical Characteristics @ $T_A=25^\circ C$

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions
Reverse Breakdown Voltage	$V_{(BR)R}$	80			V	$I_R=100\mu A$
Forward voltage	V_{F1}		0.60		V	$I_F=1mA$
	V_{F2}		0.72		V	$I_F=10mA$
	V_{F3}		0.90	1.2	V	$I_F=100mA$
Reverse current	I_{R1}			0.1	uA	$V_R=30V$
	I_{R2}			0.5	uA	$V_R=80V$
Capacitance between terminals	C_T		0.9	3.0	pF	$V_R=0, f=1MHz$
Reverse recovery time	t_{rr}		1.6	4.0	ns	$I_F=I_R=10mA, I_n=0.1\times I_R$

