



Silicon Schottky Barrier Rectifiers



**ELECTRICAL RATINGS**

Peak Inverse Voltage	40 VOLTS
I <sub>o</sub> AMPS @ 95 °C Case	25 AMPS
Maximum Surge Current Single Cycle Amps	600 AMPS
Maximum Forward Drop @ 25°C Case	
I <sub>o</sub> Amps	25 AMPS
V <sub>f</sub> Volts	.82 VOLTS
Maximum Reverse Current @ 25°C @ PRV	1 m AMPS
Storage Temperature °C	-65 to 175
Operating Temperature °C Jedec Style	-65 to 150 DO4

(203) 467-2591 TEL  
(203) 469-5928 FAX  
Email: [Info@edal.com](mailto:Info@edal.com)  
Internet: <http://www.edal.com>

***EDAL*** industries, inc.

51 Commerce St. East Haven, CT 06512



**This datasheet has been downloaded from:**

**[www.EEworld.com.cn](http://www.EEworld.com.cn)**

**Free Download**

**Daily Updated Database**

**100% Free Datasheet Search Site**

**100% Free IC Replacement Search Site**

**Convenient Electronic Dictionary**

**Fast Search System**

**[www.EEworld.com.cn](http://www.EEworld.com.cn)**