

**8916 Hook-up/Lead - UL AWM Style 1015**

		<p>For more information please call <b>1-800-Belden1</b></p> <p><u>See Put-ups and Colors</u></p>
---	--	---

**Description:**

Tinned copper conductor, PVC insulation. Rated 105°C, 600V. Rated 2500V peak for electronic circuits, and internal wiring of electronic and electrical equipment.

**PHYSICAL CHARACTERISTICS:**

**CONDUCTOR:**

Number of Conductors	1
Total Number of Conductors	1
AWG	14
Stranding	41x30
Conductor Material	TC - Tinned Copper

**INSULATION:**

Insulation Material	PVC - Polyvinyl Chloride
Insulation Thickness	.030 in.

**OVERALL:**

Overall Nominal Diameter	.138 in.
--------------------------	----------

**APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:**

**APPLICABLE STANDARDS:**

UL AWM Style	1015
UL Rating	600 V, 105°C
CSA Type	TEW
CSA Rating	600 V, 105°C
EU CE Mark (Y/N)	Yes
EU RoHS Compliant (Y/N)	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	07/01/2005
Other Specification	JQA-F-

**FLAME TEST:**

UL Flame Test	VW-1
---------------	------

**PLENUM/NON-PLENUM:**

Plenum (Y/N)	N
--------------	---

**8916 Hook-up/Lead - UL AWM Style 1015**

**PUT-UPS AND COLORS:**

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
8916 001100	14 STR PVC BRN	100	2.8	BROWN	
8916 0014000	14 STR PVC BRN	4000	80	BROWN	C P
8916 001500	14 STR PVC BRN	500	10.5	BROWN	
8916 002100	14 STR PVC RED	100	2.8	RED	
8916 0024000	14 STR PVC RED	4000	80	RED	C P
8916 002500	14 STR PVC RED	500	10.5	RED	
8916 003100	14 STR PVC ORG	100	2.8	ORANGE	
8916 0034000	14 STR PVC ORG	4000	80	ORANGE	P
8916 003500	14 STR PVC ORG	500	10.5	ORANGE	
8916 004100	14 STR PVC YEL	100	2.8	YELLOW	
8916 0044000	14 STR PVC YEL	4000	80	YELLOW	P
8916 004500	14 STR PVC YEL	500	10.5	YELLOW	
8916 005100	14 STR PVC D GRN	100	2.8	GREEN, DARK	
8916 0054000	14 STR PVC DGRN	4000	80	GREEN, DARK	C P
8916 005500	14 STR PVC D GRN	500	10.5	GREEN, DARK	
8916 007100	#14 STR PVC VIO	100	2.8	VIOLET	P
8916 0074000	#14 STR PVC VIO	4000	80	VIOLET	P
8916 007500	#14 STR PVC VIO	500	10.5	VIOLET	P
8916 008100	#14 STR PVC GRY	100	2.8	GRAY	P
8916 0084000	#14 STR PVC GRY	4000	80	GRAY	P
8916 008500	#14 STR PVC GRY	500	10.5	GRAY	P
8916 009100	14 STR PVC WHT	100	2.8	WHITE	
8916 0094000	#14 STR PVC WHT	4000	80	WHITE	C P
8916 009500	14 STR PVC WHT	500	10.5	WHITE	
8916 010100	14 STR PVC BLK	100	2.8	BLACK	
8916 0104000	#14 STR PVC BLK	4000	80	BLACK	C

**8916 Hook-up/Lead - UL AWM Style 1015**

8916 010500	14 STR PVC BLK	500	10.5	BLACK	
8916 013100	14 STR PVC D BLU	100	2.8	BLUE, DARK	
8916 0134000	#14 STR PVC DLBLU	4000	80	BLUE, DARK	P
8916 013500	14 STR PVC D BLU	500	10.5	BLUE, DARK	
8916 189100	14 STR PVC GRN/YEL	100	2.8	GREEN/YELLOW	A
8916 189500	14 STR PVC GRN/YEL	500	10.5	GREEN/YELLOW	A

A = STOCKED STRIPE COLORS.

C = CRATE REEL PUT-UP.

P = STRIPE COLORS ON STOCK SOLID COLORS. STRIPING ADDER OF \$8.00/M' FOR 1 OR 2 STRIPES. 10 000' MINIMUM ORDER FOR COLOR COMBINATION. PUT-UP WILL BE SUBJECT TO TWO PIECES (+ OR -) 10% PER SPOOL WITH A MINIMUM LENGTH OF 100'.

Revision Number: 1      Revision Date: 04-26-2005

© Copyright 2006 Belden, Inc  
All Rights Reserved.

Although Belden ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Cable Mfgs. (San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan-2003); Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory. EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); And EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.