

## 19122 Portable Cordage - UL/CSA Types: SPT-1, SPT-2, SP-1 and HPN

 	<p>For more information please call <b>1-800-Belden1</b></p> <p><u>See Put-ups and Colors</u></p>
--	---

### Description:

SPT-1 PVC Parallel Lamp Cord, UL/CSA Listed, 300V, 60°C, one conductor polarity ribbed.

### PHYSICAL CHARACTERISTICS:

#### CONDUCTOR:

Number of Conductors	2
Total Number of Conductors	2
AWG	18
Stranding	42x34
Conductor Material	BC - Bare Copper
Type of Cordage	SPT-1

#### INSULATION:

Insulation Material	PVC - Polyvinyl Chloride
Nom. Insulation Wall Thickness	.032 in.

#### OUTER SHIELD:

Outer Shield Material	Unshielded
-----------------------	------------

#### OVERALL NOMINAL DIAMETER:

Overall Nominal Diameter	.110 x .207 in.
--------------------------	-----------------

### MECHANICAL CHARACTERISTICS:

UL Temperature Rating	60°C
-----------------------	------

### APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

#### APPLICABLE STANDARDS:

NEC/(UL) Specification	SPT-1
CSA Specification	SPT-1
EU CE Mark (Y/N)	Yes
EU RoHS Compliant (Y/N)	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2004

#### PLENUM/NON-PLENUM:

Plenum (Y/N)	N
--------------	---

### ELECTRICAL CHARACTERISTICS:

## 19122 Portable Cordage - UL/CSA Types: SPT-1, SPT-2, SP-1 and HPN

Max. Operating Voltage - UL	300 V RMS
Dielectric Withstand Voltage	1500 V AC Applied for 1 Min.
Max. Recommended Current	10 Amps per conductor @ 25°C, 7 Amps per conductor @ 25°C over 50 ft.

### PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
19122 0011000	2#18 PVC PARALLEL	1000	21	BROWN	G
19122 001250	2#18 PVC PARALLEL	250	5.75	BROWN	F
19122 0091000	2#18 PVC PARALLEL	1000	21	WHITE	G
19122 009250	2#18 PVC PARALLEL	250	5.75	WHITE	F
19122 0101000	2#18 PVC PARALLEL	1000	21	BLACK	C G
19122 010250	2#18 PVC PARALLEL	250	5.75	BLACK	F
19122 3281000	2#18 PVC PARALLEL	1000	21	GRAY, SILVER	C
19122 328250	2#18 PVC PARALLEL	250	5.75	GRAY, SILVER	F

C = CRATE REEL PUT-UP.

F = MAY CONTAIN MORE THAN 1 PIECE. MINIMUM LENGTH OF ANY ONE PIECE IS 50'

G = MAY CONTAIN MORE THAN 1 PIECE. MINIMUM LENGTH OF ANY ONE PIECE IS 100'

Revision Number: 2      Revision Date: 06-21-2005

© Copyright 2006 Belden, Inc  
All Rights Reserved.

Although Belden ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Cable Mfgs. (San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan-2003); Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory. EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); And EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.