

549945 Composite - CCTV Plus Audio or Power or Pan and Tilt CCTV Control App

		<p>For more information please call 1-800-Belden1</p> <p><u>See Put-ups and Colors</u></p>
---	--	---

Description:

20 AWG bare copper conductor, foam polyolefin insulation, bare copper braid shield, PVC jacket.

SUITABLE APPLICATIONS:

Suitable Applications	CCTV plus Audio, Pan and Tilt CCTV Control
-----------------------	--

PHYSICAL CHARACTERISTICS:

COAX:

Number of Coax	1
RG Type (Single Coax)	59/U

CONDUCTOR :

Coax AWG	20
Coax Stranding	Solid
Coax Conductor Diameter	.032 in.
Coax Conductor Material	BC - Bare Copper

INSULATION :

Coax Insulation Material	Gas-injected FHDPE - Foam High Density Polyethylene
Coax Insulation Diameter	.145 in.

INNER SHIELD :

Coax Inner Shield Type	Braid
Coax Inner Shield Material	BC - Bare Copper
Coax Inner Shield % Coverage	95 %

TWISTED PAIR CABLE(S):

CONDUCTOR :

Number of Pairs	1
Twisted Pair AWG	18
Twisted Pair Stranding	7x26
Twisted Pair Conductor Diameter	.046 in.
Twisted Pair Conductor Material	BC - Bare Copper

INSULATION :

Twisted Pair Insulation Material	PVC - Polyvinyl Chloride
Twisted Pair Insulation Diameter	.066 in.

549945 Composite - CCTV Plus Audio or Power or Pan and Tilt CCTV Control App

Twisted Pair Color Code Chart :

Number	Color
1	Black & Red

OVERALL CABLING:

CONDUCTOR :

Total Number of Conductors 3

OUTER SHIELD :

Overall Cabling Outer Shield Material Unshielded

OUTER JACKET :

Overall Cabling Outer Jacket Material PVC - Polyvinyl Chloride

OVERALL DIAMETER :

Overall Composite Cabling Nominal Diameter .232 x .460 in.

MECHANICAL CHARACTERISTICS:

OVERALL CABLING:

Overall Cabling Operating Temperature Range -30°C To +80°C

Overall Cabling UL Temperature Rating 75°C

Overall Cabling Bulk Cable Weight 54 lbs/1000 ft.

Overall Cabling Max. Recommended Pulling Tension 102 lbs.

Overall Cabling Min. Bend Rad.(Install)/Minor Axis 2.5 in.

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

COAX:

APPLICABLE STANDARDS :

Coax EU CE Mark (Y/N) Yes

OVERALL CABLING:

APPLICABLE STANDARDS :

Overall Cabling NEC/(UL) Specification CM

Overall Cabling NEC Articles 800

Overall Cabling CEC/C(UL) Specification CM

Overall Cabling EU RoHS Compliant (Y/N) Yes

Overall Cabling EU RoHS Compliance (mm/dd/yyyy): 549945

FLAME TEST :

Overall Cabling UL Flame Test UL1685 UL Loading

Overall Cabling C(UL) Flame Test FT1

SUITABILITY :

Overall Cabling Suitability - Indoor Yes

Overall Cabling Suitability - Outdoor Yes

Overall Cabling Suitability - Aerial Yes

549945 Composite - CCTV Plus Audio or Power or Pan and Tilt CCTV Control App

PLENUM/NON-PLENUM :

Overall Cabling Plenum (Y/N)	N
Overall Cabling Plenum Number	649948

ELECTRICAL CHARACTERISTICS:

COAX:

Coax Nom. Characteristic Impedance	75 Ohms
Coax Nom. Inductance	.097 μ H/ft
Coax Nom. Capacitance Conductor to Shield	16.3 pF/ft
Coax Nominal Velocity of Propagation	83 %
Coax Nominal Delay	1.22 ns/ft
Coax Nom. Conductor DC Resistance @ 20 Deg. C	10.0 Ohms/1000 ft
Coax Nom. Inner Shield DC Resistance	3.5 Ohms/1000 ft

Coax Nom. Attenuation :

Description	Frequency (MHz)	Start Frequency (MHz)	Stop Frequency (MHz)	Nom. Attenuation (dB/100 ft.)
	1			.30
	5			.65
	10			.90
	50			1.90
	100			2.60
	200			3.60
	400			5.00
	700			7.00
	900			8.00
	1000			8.50

Coax Max. Operating Voltage - UL 300 V RMS

MULTICONDUCTOR CABLE(S):

Multi-Conductor Nom. Cap. Cond. to Cond. @ 1 kHz 30 pF/ft

PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
549945 0091000	1 #18 PR, 1 RG-59/U COAX	1000	60	WHITE	C
549945 009500	1#18,1RG-59/U COAX	500	30	WHITE	C
549945 0101000	1#18,1RG-59/U COAX	1000	60	BLACK	C
549945 010500	1#18,1RG-59/U COAX	500	30	BLACK	C

C = CRATE REEL PUT-UP.

Revision Number: 2 Revision Date: 06-28-2006

549945 Composite - CCTV Plus Audio or Power or Pan and Tilt CCTV Control App

© Copyright 2006 Belden, Inc
All Rights Reserved.

Although Belden ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Cable Mfgs.(San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan-2003);Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory. EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); And EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.