



LOW INPUT CURRENT HIGH GAIN SPLIT DARLINGTON OPTOCOUPERS

**SINGLE CHANNEL:
DUAL CHANNEL:**

**HCPL-0700
HCPL-0730**

**HCPL-0701
HCPL-0731**

DESCRIPTION


The HCPL-0700, HCPL-0701, HCPL-0730 and HCPL-0731 optocouplers consist of an AlGaAs LED optically coupled to a high gain split darlington photodetector housed in a compact 8-pin small outline package. The HCPL-0730 and HCPL-0731 devices have two channels per package for optimum mounting density.

The split darlington configuration separating the input photodiode and the first stage gain from the output transistor permits lower output saturation voltage and higher speed operation than possible with conventional darlington phototransistor optocoupler.


The combination of a very low input current of 0.5 mA and a high current transfer ratio of 2000% makes this family particularly useful for input interface to MOS, CMOS, LSTTL and EIA RS232C, while output compatibility is ensured to CMOS as well as high fan-out TTL requirements.

FEATURES

- Low input current – 0.5 mA
- Superior CTR – 2000%
- Superior CMR – 10 kV/μs
- CTR guaranteed 0-70°C
- U.L. Recognized (file# E90700)
- VDE 0884 recognized (file# 136616)
 - approval pending for HCPL-0730/0731
- BSI recognized (file# 8661, 8662)
 - HCPL-0700/0701 only



PACKAGE DIMENSIONS



APPLICATIONS


- Digital logic ground isolation
- Telephone ring detector
- EIA-RS-232C line receiver
- High common mode noise line receiver
- μP bus isolation
- Current loop receiver

TRUTH TABLE

LED	V _O
ON	LOW
OFF	HIGH

NOTE

All dimensions are in inches (millimeters)





LOW INPUT CURRENT HIGH GAIN SPLIT DARLINGTON OPTOCOUPERS

SINGLE CHANNEL: HCPL-0700
DUAL CHANNEL: HCPL-0730

HCPL-0701
HCPL-0731

ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Value	Units
Storage Temperature	T_{STG}	-40 to +125	°C
Operating Temperature	T_{OPR}	-40 to +85	°C
Reflow Temperature Profile (Refer to fig. 11)			
EMITTER			
DC/Average Forward Input Current	I_F (avg)	20	mA
Peak Forward Input Current (50% duty cycle, 1 ms P.W.)	I_F (pk)	40	mA
Peak Transient Input Current - ($\leq 1 \mu\text{s}$ P.W., 300 pps)	I_F (trans)	1.0	A
Reverse Input Voltage	V_R	5	V
Input Power Dissipation	P_D	35	mW
DETECTOR			
Average Output Current (Pin 6)	I_O (avg)	60	mA
Emitter-Base Reverse Voltage	V_{EBR}	0.5	V
Supply Voltage, Output Voltage	V_{CC}, V_O	-0.5 to 7	V
		-0.5 to 18	
Output power dissipation	P_D	100	mW

ELECTRICAL CHARACTERISTICS ($T_A = 0$ to 70°C Unless otherwise specified)

INDIVIDUAL COMPONENT CHARACTERISTICS

Parameter	Test Conditions		Symbol	Device	Min	Typ**	Max	Unit	
EMITTER	$I_F = 1.6\text{mA}$	$T_A = 25^\circ\text{C}$	V_F	HCLP-0700/01	1.0	1.25	1.7	V	
Input Forward Voltage				HCLP-0730/31		1.35			
				All			1.75		
Input Reverse Breakdown Voltage	$(T_A = 25^\circ\text{C}, I_R = 10 \mu\text{A})$		BV_R	All	5.0				
DETECTOR	$(I_F = 0 \text{ mA}, V_O = V_{\text{CC}} = 18 \text{ V})$		I_{OH}	HCPL-0701/31		0.01	100	μA	
Logic high output current	$(I_F = 0 \text{ mA}, V_O = V_{\text{CC}} = 7 \text{ V})$			HCPL-0700/30		0.01	250		
Logic Low Supply Current	$I_F = 1.6 \text{ mA}, V_O = \text{Open}, V_{\text{CC}} = 18 \text{ V}$	I_{CCL}	HCPL-0700/01		0.4	1.5	mA		
	$I_{F1} = I_{F2} = 1.6\text{mA}$		HCPL-0730		0.8	3			
	$V_{O1} = V_{O2} = \text{Open}$		HCPL-0731		1				
Logic High Supply Current	$I_F = 0 \text{ mA}, V_O = \text{Open}, V_{\text{CC}} = 18 \text{ V}$	I_{CCH}	HCPL-0700/01			10	μA		
	$I_{F1} = I_{F2} = 0, V_{\text{CC}} = 7\text{V}$		HCPL-0730		0.001	20			
	$V_{O1} = V_{O2} = \text{Open}, V_{\text{CC}} = 18 \text{ V}$		HCPL-0731		0.01				



LOW INPUT CURRENT HIGH GAIN SPLIT DARLINGTON OPTOCOUPERS

SINGLE CHANNEL: HCPL-0700
DUAL CHANNEL: HCPL-0730

HCPL-0701
HCPL-0731

TRANSFER CHARACTERISTICS ($T_A = 0$ to 70°C Unless otherwise specified)

Parameter	Test Conditions	Symbol	Device	Min	Typ**	Max	Unit
COUPLED Current transfer ratio (Notes 1,2)	($I_F = 0.5$ mA, $V_O = 0.4$ V, $V_{CC} = 4.5$ V)	CTR	HCPL-0701/31	400		5000	%
	$I_F = 1.6$ mA, $V_O = 0.4$ V, $V_{CC} = 4.5$ V		HCPL-0700	300		2600	
			HCPL-0701	500		2600	
			HCPL-0730	300		5000	
			HCPL-0731	500		5000	
Logic low output voltage output voltage	($I_F = 0.5$ mA, $I_O = 2$ mA, $V_{CC} = 4.5$ V)	V _{OL}	HCPL-0701			0.4	V
	($I_F = 1.6$ mA, $I_O = 8$ mA, $V_{CC} = 4.5$ V)					0.4	
	($I_F = 5$ mA, $I_O = 15$ mA, $V_{CC} = 4.5$ V)					0.4	
	($I_F = 12$ mA, $I_O = 24$ mA, $V_{CC} = 4.5$ V)		HCPL-0731			0.4	
	($I_F = 1.6$ mA, $I_O = 4.8$ mA, $V_{CC} = 4.5$ V)					0.4	
						0.4	

ISOLATION CHARACTERISTICS ($T_A = 0$ to 70°C Unless otherwise specified)

Characteristics	Test Conditions	Symbol	Min	Typ**	Max	Unit
Input-output insulation leakage current	(Relative humidity = 45%) ($T_A = 25^\circ\text{C}$, $t = 5$ s) ($V_{I-O} = 3000$ VDC) (Note 4)	I _{I-O}			1.0	µA
Withstand insulation test voltage	($R_H \leq 50\%$, $T_A = 25^\circ\text{C}$) (Note 4, 5) ($t = 1$ min.)	V _{ISO}	2500			V _{RMS}
Resistance (input to output)	(Note 4) ($V_{I-O} = 500$ VDC)	R _{I-O}		10^{12}		Ω

** All typicals at $T_A = 25^\circ\text{C}$



LOW INPUT CURRENT HIGH GAIN SPLIT DARLINGTON OPTOCOUPERS

**SINGLE CHANNEL:
DUAL CHANNEL:**

**HCPL-0700
HCPL-0730**

**HCPL-0701
HCPL-0731**

SWITCHING CHARACTERISTICS ($T_A = 0$ to 70°C unless otherwise specified., $V_{CC} = 5 \text{ V}$)

Parameter	Test Conditions	Symbol	Device	Min	Typ**	Max	Unit
Propagation delay time to logic low (Note 2) (Fig. 14)	($R_L = 4.7 \text{ k}\Omega$, $I_F = 0.5 \text{ mA}$)	T_{PHL}	HCPL-0701			30	μs
	$T_A = 25^\circ\text{C}$		HCPL-0731			120	
	($R_L = 270 \Omega$, $I_F = 12 \text{ mA}$)		HCPL-0701	3	25		
	$T_A = 25^\circ\text{C}$		HCPL-0731	5	100		
	($R_L = 2.2 \text{ k}\Omega$, $I_F = 1.6 \text{ mA}$)		HCPL-0701			2	
	$T_A = 25^\circ\text{C}$		HCPL-0731			3	
	($R_L = 4.7 \text{ k}\Omega$, $I_F = 0.5 \text{ mA}$)		HCPL-0701	0.3	1		
	$T_A = 25^\circ\text{C}$		HCPL-0731	0.4	2		
	($R_L = 270 \Omega$, $I_F = 12 \text{ mA}$)		HCPL-0700			15	
	$T_A = 25^\circ\text{C}$		HCPL-0730/0731			25	
	($R_L = 2.2 \text{ k}\Omega$, $I_F = 1.6 \text{ mA}$)		HCPL-0700	1	10		
	$T_A = 25^\circ\text{C}$		HCPL-0730/0731	2	20		
Propagation delay time to logic high (Note 2) (Fig. 14)	($R_L = 4.7 \text{ k}\Omega$, $I_F = 0.5 \text{ mA}$)	T_{PLH}	HCPL-0701/31			90	μs
	$T_A = 25^\circ\text{C}$		HCPL-0701/31			12	
	($R_L = 270 \Omega$, $I_F = 12 \text{ mA}$)		HCPL-0701			10	
	$T_A = 25^\circ\text{C}$		HCPL-0731			15	
	($R_L = 2.2 \text{ k}\Omega$, $I_F = 1.6 \text{ mA}$)		HCPL-0701	1.6	7		
	$T_A = 25^\circ\text{C}$		HCPL-0731	1.6	10		
	($R_L = 4.7 \text{ k}\Omega$, $I_F = 0 \text{ mA}$, $ V_{CM} = 10 \text{ V}_{P-P}$)		HCPL-0700/30/31			50	
	$T_A = 25^\circ\text{C}$ ($R_L = 2.2 \text{ k}\Omega$) (Note 3) (Fig. 15)		HCPL-0700/30/31			7	
Common mode transient immunity at logic high		$ CM_H $	ALL	1,000	10,000		$\text{V}/\mu\text{s}$
Common mode transient immunity at logic low	($I_F = 1.6 \text{ mA}$, $ V_{CM} = 10 \text{ V}_{P-P}$, $R_L = 2.2 \text{ k}\Omega$)	$ CM_L $	ALL	1,000	10,000		$\text{V}/\mu\text{s}$
	$T_A = 25^\circ\text{C}$ (Note 3) (Fig. 15)						

NOTES

1. Current Transfer Ratio is defined as a ratio of output collector current, I_O , to the forward LED input current, I_F times 100%.
2. Pin 7 open. Use of a resistor between pins 5 and 7 will decrease gain and delay time.
3. Common mode transient immunity in logic high level is the maximum tolerable (positive) dV_{CM}/dt on the leading edge of the common mode pulse signal, V_{CM} , to assure that the output will remain in a logic high state (i.e., $V_O > 2.0 \text{ V}$). Common mode transient immunity in logic low level is the maximum tolerable (negative) dV_{CM}/dt on the trailing edge of the common mode pulse signal, V_{CM} , to assure that the output will remain in a logic low state (i.e., $V_O < 0.8 \text{ V}$).
4. Device is considered a two terminal device: Pins 1, 2, 3 and 4 are shorted together and Pins 5, 6, 7 and 8 are shorted together.
5. 2500 VAC RMS for 1 minute duration is equivalent to 3000 VAC RMS for 1 second duration.

** All typicals at $T_A = 25^\circ\text{C}$

LOW INPUT CURRENT HIGH GAIN SPLIT DARLINGTON OPTOCOUPERS

SINGLE CHANNEL:
DUAL CHANNEL:

HCPL-0700
HCPL-0730

HCPL-0701
HCPL-0731

TYPICAL PERFORMANCE CURVES

Fig. 1 Propagation Delay vs. Temperature
(HCPL-0700, HCPL-0701)




Fig. 2 Propagation Delay vs. Temperature
(HCPL-0700, HCPL-0701)




Fig. 3 Propagation Delay vs. Temperature
(HCPL-0700, HCPL-0701)




Fig. 4 Logic High Output Current vs. Temperature
(HCPL-0700, HCPL-0701)




Fig. 5 Propagation Delay vs. Input Forward Current
(HCPL-0730, HCPL-0731)





Fig. 6 Output Current vs. Input Forward Current
(HCPL-0700, HCPL-0701)



LOW INPUT CURRENT HIGH GAIN SPLIT DARLINGTON OPTOCOUPERS

SINGLE CHANNEL:
DUAL CHANNEL:

HCPL-0700
HCPL-0730

HCPL-0701
HCPL-0731

TYPICAL PERFORMANCE CURVES

Fig. 7 Input Forward Current vs. Forward Voltage
(HCPL-0700, HCPL-0701)




Fig. 8 Input Forward Current vs. Forward Voltage
(HCPL-0730, HCPL-0731)




Fig. 9 Logic Low Supply Current vs. Input Forward Current
(HCPL-0700, HCPL-0701)




Fig. 10 Supply Current vs. Input Forward Current
(HCPL-0730, HCPL-0731)




Fig. 11 DC Transfer Characteristics
(HCPL-0700, HCPL-0701)





Fig. 12 DC Transfer Characteristics
(HCPL-0730, HCPL-0731)



LOW INPUT CURRENT HIGH GAIN SPLIT DARLINGTON OPTOCOUPERS



SINGLE CHANNEL:
DUAL CHANNEL:

HCPL-0700
HCPL-0730


HCPL-0701
HCPL-0731

TYPICAL PERFORMANCE CURVES

Fig. 13 Current Transfer Ratio vs. Input Forward Current
(HCPL-0700, HCPL-0701)



Test Circuit for HCPL-0700 and HCPL-0701



Test Circuit for HCPL-0730 and HCPL-0731

*Includes probe and fixture capacitance





Fig. 14 Switching Time Test Circuit

**LOW INPUT CURRENT
HIGH GAIN SPLIT
DARLINGTON OPTOCOUPERS**


**SINGLE CHANNEL:
DUAL CHANNEL:**

**HCPL-0700
HCPL-0730**

**HCPL-0701
HCPL-0731**



Test Circuit for HCPL-0700 and HCPL-0701



Test Circuit for HCPL-0730 and HCPL-0731





Fig. 15 Common Mode Immunity Test Circuit




**LOW INPUT CURRENT
HIGH GAIN SPLIT
DARLINGTON OPTOCOUPERS**

**SINGLE CHANNEL:
DUAL CHANNEL:**

**HCPL-0700
HCPL-0730**

**HCPL-0701
HCPL-0731**

8-Pin Small Outline





LOW INPUT CURRENT HIGH GAIN SPLIT DARLINGTON OPTOCOUPERS

SINGLE CHANNEL:
DUAL CHANNEL:


HCPL-0700
HCPL-0730

HCPL-0701
HCPL-0731

ORDERING INFORMATION

Option	Order Entry Identifier	Description
V	V	VDE 0884
R1	R1	Tape and reel (500 units per reel)
R1V	R1V	VDE 0884, Tape and reel (500 units per reel)
R2	R2	Tape and reel (2500 units per reel)
R2V	R2V	VDE 0884, Tape and reel (2500 units per reel)

MARKING INFORMATION



Definitions	
1	Fairchild logo
2	Device number
3	VDE mark (Note: Only appears on parts ordered with VDE option – See order entry table)
4	One digit year code, e.g., '3'
5	Two digit work week ranging from '01' to '53'
6	Assembly package code


**LOW INPUT CURRENT
HIGH GAIN SPLIT
DARLINGTON OPTOCOUPERS**

**SINGLE CHANNEL:
DUAL CHANNEL:**


**HCPL-0700
HCPL-0730**

**HCPL-0701
HCPL-0731**

Carrier Tape Specifications



Reflow Profile



- Peak reflow temperature: 245°C (package surface temperature)
- Time of temperature higher than 183°C for 120–180 seconds
- One time soldering reflow is recommended



LOW INPUT CURRENT HIGH GAIN SPLIT DARLINGTON OPTOCOUPERS

**SINGLE CHANNEL:
DUAL CHANNEL:**

**HCPL-0700
HCPL-0730**

**HCPL-0701
HCPL-0731**

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.