



Integrated
Circuit
Systems, Inc.

ICS8701-01

Low Skew $\div 1, \div 2$ Clock Generator w/Polarity Control


GENERAL DESCRIPTION

 The ICS8701-01 is a low skew, $\div 1, \div 2$ Clock Generator and a member of the HiPerClockS™ family of High Performance Clock Solutions from ICS. The low impedance LVCMS outputs are designed to drive 50Ω series or parallel terminated transmission lines. The effective fanout can be increased from 20 to 40 by utilizing the ability of the outputs to drive two series terminated lines.

The divide select inputs, DIV_SELx, control the output frequency of each bank. The outputs can be utilized in the $\div 1$, $\div 2$ or a combination of $\div 1$ and $\div 2$ modes. The master reset/output enable input, nMR/OE, resets the internal dividers and controls the active and high impedance states of all outputs. The output polarity inputs, INV0:1, control the polarity (inverting or non-inverting) of the outputs of each bank. Outputs QA0-QA4 are inverting for every combination of the INV0:1 input. The timing relationship between the inverting and non-inverting outputs at different frequencies is shown in the Timing Diagrams.

The ICS8701-01 is characterized at 3.3V and mixed 3.3V input supply, and 2.5V output supply operating modes. Guaranteed bank, output and part-to-part skew characteristics make the ICS8701-01 ideal for those clock distribution applications demanding well defined performance and repeatability.


BLOCK DIAGRAM



FEATURES

- 20 LVCMS outputs, 7Ω typical output impedance
- Output frequency up to 250 MHz
- 250ps bank skew, 300ps output skew, 350ps multiple frequency skew, 700ps part-to-part skew
- Selectable inverting and non-inverting outputs
- LVCMS / LVTTL clock input
- LVCMS / LVTTL control inputs
- Bank enable logic allows unused banks to be disabled in reduced fanout applications
- 3.3V or mixed 3.3V input, 2.5V output operating supply modes
- 48 lead low-profile QFP (LQFP), 7mm x 7mm x 1.4mm package body, 0.5mm package lead pitch
- 0°C to 70°C ambient operating temperature
- Other divide values available on request

PIN ASSIGNMENT





Integrated
Circuit
Systems, Inc.

ICS8701-01
Low Skew $\div 1, \div 2$ Clock
Generator w/Polarity Control

TABLE 1. PIN DESCRIPTIONS

Number	Name	Type	Description	
2, 44	VDDOC	Power	Output Bank C power supply. Connect to 3.3V or 2.5V.	
5, 11	VDDOD	Power	Output Bank D power supply. Connect to 3.3V or 2.5V.	
26, 32	VDDOA	Power	Output Bank C power supply. Connect to 3.3V or 2.5V.	
35, 41	VDDOB	Power	Output Bank B power supply. Connect to 3.3V or 2.5V.	
7, 9, 18, 21, 28, 30, 37, 39, 46, 48	GND	Power	Ground. Connect to ground.	
16, 20	VDDI	Power	Input power supply. Connect to 3.3V.	
25, 27, 29, 31, 33	QA0, QA1, QA2, QA3, QA4	Output	Bank A outputs. LVC MOS interface levels. 7Ω typical output impedance.	
34, 36, 38, 40, 42	QB0, QB1, QB2, QB3, QB4	Output	Bank B outputs. LVC MOS interface levels. 7Ω typical output impedance.	
43, 45, 47, 1, 3	QC0, QC1, QC2, QC3, QC4	Output	Bank C outputs. LVC MOS interface levels. 7Ω typical output impedance.	
4, 6, 8, 10, 12	QD0, QD1, QD2, QD3, QD4	Output	Bank D outputs. LVC MOS interface levels. 7Ω typical output impedance.	
22	LVC MOS_CLK	Input	Pullup	Clock input. LVC MOS interface levels.
13	DIV_SELD	Input	Pullup	Controls frequency division for bank D outputs. LVC MOS interface levels.
14	DIV_SELC	Input	Pullup	Controls frequency division for bank C outputs. LVC MOS interface levels.
23	DIV_SELB	Input	Pullup	Controls frequency division for bank B outputs. LVC MOS interface levels.
24	DIV_SELA	Input	Pullup	Controls frequency division for bank A outputs. LVC MOS interface levels.
17, 19	INV1, INV0	Input	Pullup	Determines polarity of outputs by banks. LVC MOS interface levels.
15	nMR/OE	Input	Pullup	Master reset and output enable. Resets non-inverting outputs to LOW. Sets inverting outputs to HIGH. Enables and disables all outputs. LVC MOS interface levels.

TABLE 2. PIN CHARACTERISTICS

Symbol	Parameter	Test Conditions	Minimum	Typical	Maximum	Units
CIN	Input Capacitance					pF
RPULLUP	Input Pullup Resistor			51		K Ω
CPD	Power Dissipation Capacitance (per output)	VDDI, VDDOx = 3.465V				pF
		VDDI = 3.465V, VDDOx = 2.625V				pF
ROUT	Output Impedance			7		Ω

TABLE 3. FUNCTION TABLE

Inputs				Outputs				
nMR/OE	DIV_SELx	INV1	INV0	BANK A	BANK B	BANK C	BANK D	Qx frequency
0	X	X	X	Hi Z	Hi Z	Hi Z	Hi Z	zero
1	0	0	0	Inverting	Non-inverting	Non-inverting	Non-inverting	fIN/2
1	0	0	1	Inverting	Inverting	Non-inverting	Non-inverting	fIN/2
1	0	1	0	Inverting	Inverting	Inverting	Non-inverting	fIN/2
1	0	1	1	Inverting	Inverting	Inverting	Inverting	fIN/2
1	1	0	0	Inverting	Non-inverting	Non-inverting	Non-inverting	fIN
1	1	0	1	Inverting	Inverting	Non-inverting	Non-inverting	fIN
1	1	1	0	Inverting	Inverting	Inverting	Non-inverting	fIN
1	1	1	1	Inverting	Inverting	Inverting	Inverting	fIN



Integrated
Circuit
Systems, Inc.

ICS8701-01
Low Skew $\div 1, \div 2$ Clock
Generator w/Polarity Control

ABSOLUTE MAXIMUM RATINGS

Supply Voltage	4.6V
Inputs	-0.5V to VDDI + 0.5V
Outputs	-0.5V to VDDOx + 0.5V
Ambient Operating Temperature	0°C to 70°C
Storage Temperature	-65°C to 150°C

Stresses beyond those listed under Absolute Maximum Ratings may cause permanent damage to the device. These ratings are stress specifications only and functional operation of product at these condition or any conditions beyond those listed in the *DC Electrical Characteristics* or *AC Electrical Characteristics* is not implied. Exposure to absolute maximum rating conditions for extended periods may affect product reliability.

TABLE 4A. DC ELECTRICAL CHARACTERISTICS, VDDI = VDDOx = 3.3V \pm 5%, TA = 0°C TO 70°C

Symbol	Parameter	Test Conditions	Minimum	Typical	Maximum	Units
VDDI	Input Power Supply Voltage		3.135	3.3	3.465	V
VDDOx	Output Power Supply Voltage		3.135	3.3	3.465	V
VIH	Input High Voltage	VDDI = 3.465V	2		3.765	V
			2		3.765	V
VIL	Input Low Voltage	VDDI = 3.135V	-0.3		0.8	V
			-0.3		1.3	V
IIH	Input High Current	VDDI = VIN = 3.465V			5	µA
IIL	Input Low Current	VDDI = VIN = 0V	-150			µA
IDD	Quiescent Power Supply Current				70	mA
VOH	Output High Voltage	VDDOx = 3.135V IOH = -36mA	2.6			V
VOL	Output Low Voltage	VDDOx = 3.135V IOL = 36mA			0.5	V

TABLE 5A. AC ELECTRICAL CHARACTERISTICS, VDDI = VDDOx = 3.3V \pm 5%, TA=0°C TO 70°C

Symbol	Parameter	Test Conditions	Minimum	Typical	Maximum	Units
fMAX	Maximum Input Frequency				250	MHz
tpLH	Propagation Delay, Low-to-High	0MHz < f \leq 200MHz	2.5		3.5	ns
tpHL	Propagation Delay, High-to-Low	0MHz < f \leq 200MHz	2.5		3.5	ns
tsk(b)	Bank Skew; NOTE 2	Measured on falling edge at VDDOx/2			250	ps
tsk(o)	Output Skew; NOTE 3	Measured on falling edge at VDDOx/2			300	ps
tsk(ω)	Multiple Frequency Skew; NOTE 4	Measured on falling edge at VDDOx/2			350	ps
tsk(pp)	Part to Part Skew; NOTE 5	Measured on falling edge at VDDOx/2			700	ps
tR	Output Rise Time; NOTE 6		150		700	ps
tF	Output Fall Time; NOTE 6		150		700	ps
tPW	Output Pulse Width	0MHz < f < 200MHz	tCYCLE/2 - 0.5	tCYCLE/2	tCYCLE/2 + 0.5	ns
		f = 200MHz	2	2.5	3	ns
tEN	Output Enable Time; NOTE 6				6	ns
tDIS	Output Disable Time; NOTE 6				6	ns

NOTE 1: All parameters measured at 200MHz unless noted otherwise. All outputs terminated with 50Ω to VDDOx/2.

NOTE 2: Defined as skew within a bank of outputs at the same supply voltages and with equal load conditions.

NOTE 3: Defined as skew across banks of outputs switching in the same direction at the same supply voltages and with equal load conditions.

NOTE 4: Defined as skew across banks of outputs switching in the same direction operating at different frequencies with the same supply voltages and equal load conditions.

NOTE 5: Defined as the skew at different outputs switching in the same direction on different devices operating at the same supply voltages and with equal load conditions.

NOTE 6: These parameters are guaranteed by characterization. Not tested in production.



Integrated
Circuit
Systems, Inc.

ICS8701-01
Low Skew $\div 1, \div 2$ Clock
Generator w/Polarity Control

TABLE 4B. DC ELECTRICAL CHARACTERISTICS, VDDI = 3.3V \pm 5%, VDDOx = 2.5V \pm 5%, TA = 0°C TO 70°C

Symbol	Parameter	Test Conditions	Minimum	Typical	Maximum	Units
VDDI	Input Power Supply Voltage		3.135	3.3	3.465	V
VDDOx	Output Power Supply Voltage		2.375	2.5	2.625	V
VIH	Input High Voltage	VDDI = 3.465V	2		3.765	V
			2		3.765	V
VIL	Input Low Voltage	VDDI = 3.135V	-0.3		0.8	V
			-0.3		1.3	V
IIH	Input High Current	VDDI = VIN = 3.465V			5	μ A
IIL	Input Low Current	VDDI = VIN = 0V	-150			μ A
IDD	Quiescent Power Supply Current				70	mA
VOH	Output High Voltage	VDDI = 3.135V VDDOx = 2.375V IOH = -27mA	1.8			V
VOL	Output Low Voltage	VDDI = 3.135V VDDOx = 2.375V IOL = 27mA			0.5	V

TABLE 5B. AC ELECTRICAL CHARACTERISTICS, VD DI = 3.3V \pm 5%, VDDO = 2.5V \pm 5%, TA = 0°C TO 70°C

Symbol	Parameter	Test Conditions	Minimum	Typical	Maximum	Units
fMAX	Maximum Input Frequency				250	MHz
tpLH	Propagation Delay, Low-to-High	0MHz < f \leq 200MHz	2.5		3.5	ns
tpHL	Propagation Delay, High-to-Low	0MHz < f \leq 200MHz	2.5		3.5	ns
tsk(b)	Bank Skew; NOTE 2	Measured on falling edge at VDDOx/2			300	ps
tsk(o)	Output Skew; NOTE 3	Measured on falling edge at VDDOx/2			300	ps
tsk(ω)	Multiple Frequency Skew; NOTE 4	Measured on falling edge at VDDOx/2			350	ps
tsk(pp)	Part to Part Skew; NOTE 5	Measured on falling edge at VDDOx/2			700	ps
tR	Output Rise Time; NOTE 6		150		720	ps
tF	Output Fall Time; NOTE 6		150		720	ps
tPW	Output Pulse Width	0MHz < f < 200MHz	tCYCLE/2 - 0.5	tCYCLE/2	tCYCLE/2 + 0.5	ns
		f = 200MHz	2	2.5	3	ns
tEN	Output Enable Time; NOTE 6				6	ns
tDIS	Output Disable Time; NOTE 6				6	ns

NOTE 1: All parameters measured at 200MHz unless noted otherwise. All outputs terminated with 50 Ω to VDDOx/2.

NOTE 2: Defined as skew within a bank of outputs at the same supply voltages and with equal load conditions.

NOTE 3: Defined as skew across banks of outputs switching in the same direction at the same supply voltages and with equal load conditions.

NOTE 4: Defined as skew across banks of outputs switching in the same direction operating at different frequency with the same supply voltages and equal load conditions.

NOTE 5: Defined as the skew at different outputs switching in the same direction on different devices operating at the same supply voltages and with equal load conditions.

NOTE 6: These parameters are guaranteed by characterization. Not tested in production.



Integrated
Circuit
Systems, Inc.

ICS8701-01
Low Skew $\div 1, \div 2$ Clock
Generator w/Polarity Control

FIGURE 1A, 1B - TIMING DIAGRAMS




FIGURE 1A - ACTIVE, $\div 1$, $\div 2$, INVERTING AND NON-INVERTING




FIGURE 1B - RESET TO ACTIVE, $\div 1$, $\div 2$, INVERTING AND NON-INVERTING



Integrated
Circuit
Systems, Inc.

ICS8701-01
Low Skew $\div 1, \div 2$ Clock
Generator w/Polarity Control

FIGURE 2A, 2B - TIMING WAVEFORMS




FIGURE 2A - PROPAGATION DELAYS

fin = 200MHz, Vamp = 3.3V, tr = tf = 600ps




FIGURE 2B - DISABLE AND ENABLE TIMES

fin = 10MHz, Vamp = 3.3V, tr = tf = 600ps



Integrated
Circuit
Systems, Inc.

ICS8701-01
Low Skew $\div 1, \div 2$ Clock
Generator w/Polarity Control

FIGURE 3A, 3B- SKEW DEFINITIONS & WAVEFORMS

Bank Skew - Skew within a bank of outputs at the same supply voltages and with equal load conditions.




FIGURE 3A - BANK SKEW

$f_{in} = 200\text{MHz}$, $V_{amp} = 3.3\text{V}$, $t_r = t_f = 200\text{ps}$

Output Skew - Skew across banks of outputs switching in the same direction at the same supply voltages and with equal load conditions.




FIGURE 3B - INVERTING OUTPUT SKEW

$f_{in} = 200\text{MHz}$, $V_{amp} = 3.3\text{V}$, $t_r = t_f = 200\text{ps}$



Integrated
Circuit
Systems, Inc.

ICS8701-01

Low Skew $\div 1, \div 2$ Clock Generator w/Polarity Control

FIGURE 3C, 3D- Skew Definitions & Waveforms

Multiple Frequency Skew - Skew across banks of outputs switching in the same direction operating at different frequencies with the same supply voltages and equal load conditions.




FIGURE 3C - MULTIPLE FREQUENCY SKEW

fin = 200MHz, Vamp = 3.3V, tr = tf = 200ps

Part to Part Skew - Skew at different outputs switching in the same direction on different devices operating at the same supply voltages and with equal load conditions.




FIGURE 3B - OUTPUT SKEW






fin = 200MHz, Vamp = 3.3V, tr = tf = 200ps



Integrated
Circuit
Systems, Inc.

ICS8701-01
Low Skew $\div 1, \div 2$ Clock
Generator w/Polarity Control

PACKAGE OUTLINE AND DIMENSIONS - Y SUFFIX



- NOTES:
1. ALL DIMENSIONS AND TOLERANCING CONFORM TO ANSI Y14.5-1982
 2. DATUM PLANE -H- LOCATED AT MOLD PARTING LINE AND COINCIDENT WITH LEAD, WHERE LEAD EXITS PLASTIC BODY AT BOTTOM OF PARTING LINE.
 3. DATUMS A-B AND -D- TO BE DETERMINED AT CENTERLINE BETWEEN LEADS WHERE LEADS EXIT PLASTIC AT DATUM PLANE -H- .
 4. TO BE DETERMINED AT SEATING PLACE -C- .
 5. DIMENSIONS D1 AND E1 DO NOT INCLUDE MOLD PROTRUSION.
 6. "N" IS THE TOTAL NUMBER OF TERMINALS.
 7. THESE DIMENSIONS TO BE DETERMINED AT DATUM PLANE -H-.
 8. PACKAGE TOP DIMENSIONS ARE SMALLER THAN BOTTOM DIMENSIONS AND TOP OF PACKAGE WILL NOT OVERHANG BOTTOM OF PACKAGE.
 9. DIMENSION b DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.08mm TOTAL IN EXCESS OF THE b DIMENSION AT MAXIMUM MATERIAL CONDITION.
 10. CONTROLLING DIMENSION: MILLIMETER.
 11. THIS OUTLINE CONFORMS TO JEDEC PUBLICATION 95 REGISTRATION MS-026, VARIATION BBC.
 12. A1 IS DEFINED AS THE DISTANCE FROM THE SEATING PLANE TO THE LOWEST POINT OF THE PACKAGE.

SYMBOL	JEDEC VARIATION ALL DIMENSIONS IN MILLIMETERS			NOTE	
	BBC				
	MIN.	NOM.	MAX.		
A			1.60		
A ₁	0.05		0.15	12	
A ₂	1.35	1.40	1.45		
D	9.00 BSC.			4	
D ₁	7.00 BSC.			7, 8	
E	9.00 BSC.			4	
E ₁	7.00 BSC.			7, 8	
L	0.45	0.60	0.75		
N	48				
e	0.5 BSC.				
b	0.17	0.22	0.27	9	
b ₁	0.17	0.20	0.23		
ccc			0.08		
ddd			0.08		



Integrated
Circuit
Systems, Inc.

ICS8701-01
Low Skew $\div 1, \div 2$ Clock
Generator w/Polarity Control

ORDERING INFORMATION

Part/Order Number	Marking	Package	Count	Temperature
ICS8701-01Y	ICS8701-01	48 Lead LQFP	250 per tray	0°C to 70°C
ICS8701-01YT	ICS8701-01	48 Lead LQFP on Tape and Reel	2000	0°C to 70°C

While the information presented herein has been checked for both accuracy and reliability, Integrated Circuit Systems, Incorporated (ICS) assumes no responsibility for either its use or for infringement of any patents or other rights of third parties, which would result from its use. No other circuits, patents, or licenses are implied. This product is intended for use in normal commercial applications. Any other applications such as those requiring extended temperature range, high reliability, or other extraordinary environmental requirements are not recommended without additional processing by ICS. ICS reserves the right to change any circuitry or specifications without notice. ICS does not authorize or warrant any ICS product for use in life support devices or critical medical instruments.