



### 3.3V Zero Delay Buffer

#### General Features

- 15MHz to 133MHz operating range, compatible with CPU and PCI bus frequencies.
- Zero input - output propagation delay.
- Multiple low-skew outputs.
  - Output-output skew less than 250pS.
  - Device-device skew less than 700pS.
  - One input drives 9 outputs, grouped as 4 + 4 + 1(ASM5P2309A).
  - One input drives 5 outputs (ASM5P2305A).
- Less than 200 pS cycle-to-cycle jitter is compatible with Pentium® based systems.
- Test Mode to bypass PLL (ASM5P2309A only, Refer Select Input Decoding Table).
- Available in 16pin 150-mil SOIC, 4.4 mm TSSOP (ASM5P2309A), and in 8pin 150-mil SOIC package (ASM5P2305A).
- 3.3V operation, advanced 0.35μ CMOS technology.

#### Functional Description

ASM5P2309A is a versatile, 3.3V zero-delay buffer designed to distribute high-speed clocks. It accepts one reference input and drives out nine low-skew clocks. It is available in a 16-pin package. The ASM5P2305A is the eight-pin version of the ASM5P2309A. It accepts one reference input and drives out five low-skew clocks. The -1H version of the ASM5P23XXA operates at up to

133MHz frequencies, and has higher drive than the -1 devices. All parts have on-chip PLLs that lock to an input clock on the REF pin. The PLL feedback is on-chip and is obtained from the CLKOUT pad.


The ASM5P2309A has two banks of four outputs each, which can be controlled by the Select inputs as shown in the Select Input Decoding Table. The select input also allows the input clock to be directly applied to the outputs for chip and system testing purposes.

Multiple ASM5P2309A and ASM5P2305A devices can accept the same input clock and distribute it. In this case the skew between the outputs of the two devices is guaranteed to be less than 700pS.

All outputs have less than 200pS of cycle-to-cycle jitter. The input and output propagation delay is guaranteed to be less than 350pS, and the output to output skew is guaranteed to be less than 250pS.

The ASM5P2309A and the ASM5P2305A are available in two different configurations, as shown in the ordering information table. The ASM5P2305A-1/ ASM5P2309A-1 is the base part. The ASM5P2305A-1H/ ASM5P2309A-1H is the high drive version of the -1 and its rise and fall times are much faster than -1 part.

#### Block Diagram





Select Input Decoding for ASM5P2309A

| S2 | S1 | Clock A1 - A4 | Clock B1 - B4 | CLKOUT <sup>1</sup> | Output Source | PLL Shut-Down |
|----|----|---------------|---------------|---------------------|---------------|---------------|
| 0  | 0  | Three-state   | Three-state   | Driven              | PLL           | N             |
| 0  | 1  | Driven        | Three-state   | Driven              | PLL           | N             |
| 1  | 0  | Driven        | Driven        | Driven              | Reference     | Y             |
| 1  | 1  | Driven        | Driven        | Driven              | PLL           | N             |


Notes:



1. This output is driven and has an internal feedback for the PLL. The load on this output can be adjusted to change the skew between the reference and the output.

**Zero Delay and Skew Control**

All outputs should be uniformly loaded to achieve Zero Delay between input and output. Since the CLKOUT pin is the internal feedback to the PLL, its relative loading can adjust the input-output delay.

For applications requiring zero input-output delay, all outputs, including CLKOUT, must be equally loaded. Even if CLKOUT is not used, it must have a capacitive load equal to that on other outputs, for obtaining zero-input-output delay.




**rev 1.6**  
**Pin Configuration**

**Pin Description for ASM5P2309A**

| Pin # | Pin Name            | Description                                    |
|-------|---------------------|--|
| 1     | REF <sup>2</sup>    | Input reference frequency, 5V tolerant input   |
| 2     | CLKA1 <sup>3</sup>  | Buffered clock output, bank A                  |
| 3     | CLKA2 <sup>3</sup>  | Buffered clock output, bank A                  |
| 4     | V <sub>DD</sub>     | 3.3V supply                                    |
| 5     | GND                 | Ground   |
| 6     | CLKB1 <sup>3</sup>  | Buffered clock output, bank B                  |
| 7     | CLKB2 <sup>3</sup>  | Buffered clock output, bank B                  |
| 8     | S2 <sup>4</sup>     | Select input, bit 2                            |
| 9     | S1 <sup>4</sup>     | Select input, bit 1                            |
| 10    | CLKB3 <sup>3</sup>  | Buffered clock output, bank B                  |
| 11    | CLKB4 <sup>3</sup>  | Buffered clock output, bank B                  |
| 12    | GND                 | Ground   |
| 13    | V <sub>DD</sub>     | 3.3V supply                                    |
| 14    | CLKA3 <sup>3</sup>  | Buffered clock output, bank A                  |
| 15    | CLKA4 <sup>3</sup>  | Buffered clock output, bank A                  |
| 16    | CLKOUT <sup>3</sup> | Buffered output, internal feedback on this pin |



rev 1.6

## Pin Description for ASM5P2305A

| Pin # | Pin Name            | Description  |
|-------|---------------------|--|
| 1     | REF <sup>2</sup>    | Input reference frequency, 5V-tolerant input         |
| 2     | CLK2 <sup>3</sup>   | Buffered clock output                                |
| 3     | CLK1 <sup>3</sup>   | Buffered clock output                                |
| 4     | GND                 | Ground   |
| 5     | CLK3 <sup>3</sup>   | Buffered clock output                                |
| 6     | V <sub>DD</sub>     | 3.3V supply  |
| 7     | CLK4 <sup>3</sup>   | Buffered clock output                                |
| 8     | CLKOUT <sup>3</sup> | Buffered clock output, internal feedback on this pin |

Notes:

2. Weak pull-down.
3. Weak pull-down on all outputs.
4. Weak pull-up on these inputs.



rev 1.6

**Absolute Maximum Ratings**

| Parameter  | Min  | Max            | Unit |
|--|------|----------------|------|
| Supply Voltage to Ground Potential                       | -0.5 | +7.0           | V    |
| DC Input Voltage (Except REF)                            | -0.5 | $V_{DD} + 0.5$ | V    |
| DC Input Voltage (REF)                                   | -0.5 | 7              | V    |
| Storage Temperature                                      | -65  | +150           | °C   |
| Max. Soldering Temperature (10 sec)                      |      | 260            | °C   |
| Junction Temperature                                     |      | 150            | °C   |
| Static Discharge Voltage<br>(As per JEDEC STD22- A114-B) |      | 2000           | V    |

Note: These are stress ratings only and functional usage is not implied. Exposure to absolute maximum ratings for prolonged periods can affect device reliability.

**Operating Conditions for ASM5P2305A and ASM5P2309A - Commercial Temperature Devices**

| Parameter | Description                                 | Min | Max | Unit |
|-----------|---|-----|-----|------|
| $V_{DD}$  | Supply Voltage                              | 3.0 | 3.6 | V    |
| $T_A$     | Operating Temperature (Ambient Temperature) | 0   | 70  | °C   |
| $C_L$     | Load Capacitance, below 100MHz              |     | 30  | pF   |
| $C_L$     | Load Capacitance, from 100MHz to 133MHz     |     | 10  | pF   |
| $C_{IN}$  | Input Capacitance                           |     | 7   | pF   |



rev 1.6

**Electrical Characteristics for ASM5P2305A and ASM5P2309A - Commercial Temperature Devices**

| Parameter       | Description                      | Test Conditions  | Min | Typ | Max | Unit |
|-----------------|----------------------------------|--|-----|-----|-----|------|
| V <sub>IL</sub> | Input LOW Voltage <sup>5</sup>   |  |     |     | 0.8 | V    |
| V <sub>IH</sub> | Input HIGH Voltage <sup>5</sup>  |  | 2.0 |     |     | V    |
| I <sub>IL</sub> | Input LOW Current                | V <sub>IN</sub> = 0V   |     |     | 50  | μA   |
| I <sub>IH</sub> | Input HIGH Current               | V <sub>IN</sub> = V <sub>DD</sub>                              |     |     | 100 | μA   |
| V <sub>OL</sub> | Output LOW Voltage <sup>6</sup>  | I <sub>OL</sub> = 8mA (-1)<br>I <sub>OH</sub> = 12mA (-1H)     |     |     | 0.4 | V    |
| V <sub>OH</sub> | Output HIGH Voltage <sup>6</sup> | I <sub>OL</sub> = -8mA (-1)<br>I <sub>OH</sub> = -12mA (-1H)   | 2.4 |     |     | V    |
| I <sub>DD</sub> | Supply Current                   | Unloaded outputs at 66.67MHz,<br>SEL inputs at V <sub>DD</sub> |     |     | 34  | mA   |
| Z <sub>o</sub>  | Output Impedance                 |  |     | 23  |     | Ω    |

**Switching Characteristics for ASM5P2305A-1 and ASM5P2309A-1 -- Commercial Temperature Devices<sup>7</sup>**

| Parameter         | Description  | Test Conditions   | Min      | Typ | Max        | Unit |
|-------------------|--|---|----------|-----|------------|------|
| 1/t <sub>1</sub>  | Output Frequency   | 30pF load<br>10pF load  | 15<br>15 |     | 100<br>133 | MHz  |
|                   | Duty Cycle <sup>6</sup> = (t <sub>2</sub> / t <sub>1</sub> ) * 100 | Measured at 1.4V, F <sub>OUT</sub> = 66.67MHz                   | 40       | 50  | 60         | %    |
| t <sub>3</sub>    | Output Rise Time <sup>6</sup>                                      | Measured between 0.8V and 2.0V                                  |          |     | 2.50       | nS   |
| t <sub>4</sub>    | Output Fall Time <sup>6</sup>                                      | Measured between 2.0V and 0.8V                                  |          |     | 2.50       | nS   |
| t <sub>5</sub>    | Output-to-output skew <sup>6</sup>                                 | All outputs equally loaded                                      |          |     | 250        | pS   |
| t <sub>6</sub>    | Delay, REF Rising Edge to CLKOUT Rising Edge <sup>6</sup>          | Measured at V <sub>DD</sub> /2                                  |          | 0   | ±350       | pS   |
| t <sub>7</sub>    | Device-to-Device Skew <sup>6</sup>                                 | Measured at V <sub>DD</sub> /2 on the CLKOUT pins of the device |          | 0   | 700        | pS   |
| t <sub>J</sub>    | Cycle-to-cycle jitter <sup>6</sup>                                 | Measured at 66.67MHz, loaded outputs                            |          |     | 200        | pS   |
| t <sub>LOCK</sub> | PLL Lock Time <sup>6</sup>   | Stable power supply, valid clock presented on REF pin           |          |     | 1.0        | mS   |

Notes:

5. REF input has a threshold voltage of V<sub>DD</sub> /2
6. Parameter is guaranteed by design and characterization. Not 100% tested in production
7. All parameters specified with loaded outputs.


**Switching Characteristics for ASM5P2305A-1H and ASM5P2309A-1H Commercial Temperature Devices<sup>9</sup>**

| Parameter         | Description  | Test Conditions   | Min      | Typ | Max        | Unit |
|-------------------|--|---|----------|-----|------------|------|
| 1/t <sub>1</sub>  | Output Frequency   | 30pF load<br>10pF load  | 15<br>15 |     | 100<br>133 | MHz  |
|                   | Duty Cycle <sup>8</sup> = (t <sub>2</sub> / t <sub>1</sub> ) * 100 | Measured at 1.4 V, F <sub>OUT</sub> = 66.67MHz                  | 40       | 50  | 60         | %    |
|                   | Duty Cycle <sup>8</sup> = (t <sub>2</sub> / t <sub>1</sub> ) * 100 | Measured at 1.4 V, F <sub>OUT</sub> < 50.0MHz                   | 45       | 50  | 55         |      |
| t <sub>3</sub>    | Output Rise Time <sup>8</sup>                                      | Measured between 0.8V and 2.0V                                  |          |     | 1.5        | nS   |
| t <sub>4</sub>    | Output Fall Time <sup>8</sup>                                      | Measured between 2.0V and 0.8V                                  |          |     | 1.5        | nS   |
| t <sub>5</sub>    | Output-to-output skew <sup>8</sup>                                 | All outputs equally loaded                                      |          |     | 250        | pS   |
| t <sub>6</sub>    | Delay, REF Rising Edge to CLKOUT Rising Edge <sup>8</sup>          | Measured at V <sub>DD</sub> /2                                  |          | 0   | ± 350      | pS   |
| t <sub>7</sub>    | Device-to-Device Skew <sup>8</sup>                                 | Measured at V <sub>DD</sub> /2 on the CLKOUT pins of the device |          | 0   | 700        | pS   |
| t <sub>8</sub>    | Output Slew Rate <sup>8</sup>                                      | Measured between 0.8V and 2.0V using Test Circuit #2            | 1        |     |            | V/nS |
| t <sub>J</sub>    | Cycle-to-cycle jitter <sup>8</sup>                                 | Measured at 66.67 MHz, loaded outputs                           |          |     | 200        | pS   |
| t <sub>LOCK</sub> | PLL Lock Time <sup>8</sup>   | Stable power supply, valid clock presented on REF pin           |          |     | 1.0        | mS   |

Notes:

8. Parameter is guaranteed by design and characterization. Not 100% tested in production

9. All parameters specified with loaded outputs.

**Operating Conditions for ASM5I2305A and ASM5I2309A Industrial Temperature Devices**

| Parameter       | Description                                 | Min | Max | Unit |
|-----------------|---|-----|-----|------|
| V <sub>DD</sub> | Supply Voltage                              | 3.0 | 3.6 | V    |
| T <sub>A</sub>  | Operating Temperature (Ambient Temperature) | -40 | 85  | °C   |
| C <sub>L</sub>  | Load Capacitance, below 100MHz              |     | 30  | pF   |
| C <sub>L</sub>  | Load Capacitance, from 100MHz to 133MHz     |     | 15  | pF   |
| C <sub>IN</sub> | Input Capacitance                           |     | 7   | pF   |


**Electrical Characteristics for ASM5I2305A and ASM5I2309A Industrial Temperature Devices**

| Parameter | Description                       | Test Conditions  | Min | Typ | Max | Unit     |
|-----------|-----------------------------------|--|-----|-----|-----|----------|
| $V_{IL}$  | Input LOW Voltage <sup>10</sup>   |  |     |     | 0.8 | V        |
| $V_{IH}$  | Input HIGH Voltage <sup>10</sup>  |  | 2.0 |     |     | V        |
| $I_{IL}$  | Input LOW Current                 | $V_{IN} = 0V$  |     |     | 50  | $\mu A$  |
| $I_{IH}$  | Input HIGH Current                | $V_{IN} = V_{DD}$  |     |     | 100 | $\mu A$  |
| $V_{OL}$  | Output LOW Voltage <sup>11</sup>  | $I_{OL} = 8mA (-1)$<br>$I_{OH} = 12mA (-1H)$                                     |     |     | 0.4 | V        |
| $V_{OH}$  | Output HIGH Voltage <sup>11</sup> | $I_{OL} = -8mA (-1)$<br>$I_{OH} = -12mA (-1H)$                                   | 2.4 |     |     | V        |
| $I_{DD}$  | Supply Current                    | Unloaded outputs at 100MHz,<br>SEL inputs at $V_{DD}$ or GND,<br>at room temp.   |     |     | 50  | mA       |
|           |                                   | Unloaded outputs at 66.67MHz,<br>SEL inputs at $V_{DD}$ or GND,<br>at room temp. |     |     | 34  |          |
|           |                                   | Unloaded outputs at 33MHz,<br>SEL inputs at $V_{DD}$ or GND,<br>at room temp.    |     |     | 19  |          |
| $Z_o$     | Output Impedance                  |  |     | 23  |     | $\Omega$ |

Notes:

10. REF input has a threshold voltage of  $V_{DD}/2$ 

11. Parameter is guaranteed by design and characterization. Not 100% tested in production


**Switching Characteristics for ASM5I2305A-1H and ASM5I2309A-1H - Industrial Temperature Devices<sup>13</sup>**

| Parameter         | Description   | Test Conditions   | Min | Typ | Max   | Unit |
|-------------------|---|---|-----|-----|-------|------|
| 1/t <sub>1</sub>  | Output Frequency  | 30pF load   | 15  |     | 100   | MHz  |
|                   |   | 10pF load   | 15  |     | 133   |      |
|                   | Duty Cycle <sup>12</sup> = (t <sub>2</sub> / t <sub>1</sub> ) * 100 | Measured at 1.4V, F <sub>OUT</sub> = 66.67MHz                   | 40  | 50  | 60    | %    |
|                   | Duty Cycle <sup>12</sup> = (t <sub>2</sub> / t <sub>1</sub> ) * 100 | Measured at 1.4V, F <sub>OUT</sub> < 50.0MHz                    | 45  | 50  | 55    |      |
| t <sub>3</sub>    | Output Rise Time <sup>12</sup>                                      | Measured between 0.8V and 2.0V                                  |     |     | 1.5   | nS   |
| t <sub>4</sub>    | Output Fall Time <sup>12</sup>                                      | Measured between 2.0V and 0.8V                                  |     |     | 1.5   | nS   |
| t <sub>5</sub>    | Output-to-output skew <sup>12</sup>                                 | All outputs equally loaded                                      |     |     | 250   | pS   |
| t <sub>6</sub>    | Delay, REF Rising Edge to CLKOUT Rising Edge <sup>12</sup>          | Measured at V <sub>DD</sub> /2                                  |     | 0   | ± 350 | pS   |
| t <sub>7</sub>    | Device-to-Device Skew <sup>12</sup>                                 | Measured at V <sub>DD</sub> /2 on the CLKOUT pins of the device |     | 0   | 700   | pS   |
| t <sub>8</sub>    | Output Slew Rate <sup>12</sup>                                      | Measured between 0.8V and 2.0V using Test Circuit #2            | 1   |     |       | V/nS |
| t <sub>J</sub>    | Cycle-to-cycle jitter <sup>12</sup>                                 | Measured at 66.67MHz, loaded outputs                            |     |     | 200   | pS   |
| t <sub>LOCK</sub> | PLL Lock Time <sup>12</sup>   | Stable power supply, valid clock presented on REF pin           |     |     | 1.0   | mS   |

## Notes:

12. Parameter is guaranteed by design and characterization. Not 100% tested in production


13. All parameters specified with loaded outputs.




rev 1.6

### Switching Waveforms


#### Duty Cycle Timing




#### All Outputs Rise/Fall Time




#### Output - Output Skew



#### Input - Output Propagation Delay





#### Device - Device Skew





rev 1.6

Test Circuits




For parameter  $t_8$  (output skew rate) on -1H devices



rev 1.6

Package Information


8-lead (150-mil) SOIC Package



| Symbol   | Dimensions |       |             |      |
|----------|------------|-------|-------------|------|
|          | Inches     |       | Millimeters |      |
|          | Min        | Max   | Min         | Max  |
| A1       | 0.004      | 0.010 | 0.10        | 0.25 |
| A        | 0.053      | 0.069 | 1.35        | 1.75 |
| A2       | 0.049      | 0.059 | 1.25        | 1.50 |
| B        | 0.012      | 0.020 | 0.31        | 0.51 |
| C        | 0.007      | 0.010 | 0.18        | 0.25 |
| D        | 0.193 BSC  |       | 4.90 BSC    |      |
| E        | 0.154 BSC  |       | 3.91 BSC    |      |
| e        | 0.050 BSC  |       | 1.27 BSC    |      |
| H        | 0.236 BSC  |       | 6.00 BSC    |      |
| L        | 0.016      | 0.050 | 0.41        | 1.27 |
| $\theta$ | 0°         | 8°    | 0°          | 8°   |




8-lead Thin Shrunk Small Outline Package (4.40-MM Body)



| Symbol | Dimensions |       |             |      |
|--------|------------|-------|-------------|------|
|        | Inches     |       | Millimeters |      |
|        | Min        | Max   | Min         | Max  |
| A      |            | 0.043 |             | 1.10 |
| A1     | 0.002      | 0.006 | 0.05        | 0.15 |
| A2     | 0.033      | 0.037 | 0.85        | 0.95 |
| B      | 0.008      | 0.012 | 0.19        | 0.30 |
| c      | 0.004      | 0.008 | 0.09        | 0.20 |
| D      | 0.114      | 0.122 | 2.90        | 3.10 |
| E      | 0.169      | 0.177 | 4.30        | 4.50 |
| e      | 0.026 BSC  |       | 0.65 BSC    |      |
| H      | 0.252 BSC  |       | 6.40 BSC    |      |
| L      | 0.020      | 0.028 | 0.50        | 0.70 |
| θ      | 0°         | 8°    | 0°          | 8°   |




16-lead (150 Mil) Molded SOIC



| Symbol | Dimensions |       |             |       |
|--------|------------|-------|-------------|-------|
|        | Inches     |       | Millimeters |       |
|        | Min        | Max   | Min         | Max   |
| A      | 0.053      | 0.069 | 1.35        | 1.75  |
| A1     | 0.004      | 0.010 | 0.10        | 0.25  |
| A2     | 0.049      | 0.059 | 1.25        | 1.50  |
| B      | 0.013      | 0.022 | 0.33        | 0.53  |
| C      | 0.008      | 0.012 | 0.19        | 0.27  |
| D      | 0.386      | 0.394 | 9.80        | 10.01 |
| E      | 0.150      | 0.157 | 3.80        | 4.00  |
| e      | 0.050 BSC  |       | 1.27 BSC    |       |
| H      | 0.228      | 0.244 | 5.80        | 6.20  |
| h      | 0.010      | 0.016 | 0.25        | 0.41  |
| L      | 0.016      | 0.035 | 0.40        | 0.89  |
| θ      | 0°         | 8°    | 0°          | 8°    |



16-lead Thin Shrunk Small Outline Package (4.40-MM Body)



| Symbol   | Dimensions |       |             |      |
|----------|------------|-------|-------------|------|
|          | Inches     |       | Millimeters |      |
|          | Min        | Max   | Min         | Max  |
| A        |            | 0.043 |             | 1.20 |
| A1       | 0.002      | 0.006 | 0.05        | 0.15 |
| A2       | 0.031      | 0.041 | 0.80        | 1.05 |
| B        | 0.007      | 0.012 | 0.19        | 0.30 |
| C        | 0.004      | 0.008 | 0.09        | 0.20 |
| D        | 0.193      | 0.201 | 4.90        | 5.10 |
| E        | 0.169      | 0.177 | 4.30        | 4.50 |
| e        | 0.026 BSC  |       | 0.65 BSC    |      |
| H        | 0.252 BSC  |       | 6.40 BSC    |      |
| L        | 0.020      | 0.030 | 0.50        | 0.75 |
| $\theta$ | 0°         | 8°    | 0°          | 8°   |



rev 1.6

## Ordering Codes

| Ordering Code       | Marking    | Package Type                      | Operating Range |
|---------------------|------------|-----------------------------------|-----------------|
| ASM5P2309A-1-16-ST  | 5P2309A-1  | 16-pin 150-mil SOIC-TUBE          | Commercial      |
| ASM5I2309A-1-16-ST  | 5I2309A-1  | 16-pin 150-mil SOIC- TUBE         | Industrial      |
| ASM5P2309A-1-16-SR  | 5P2309A-1  | 16-pin 150-mil SOIC-TAPE & REEL   | Commercial      |
| ASM5I2309A-1-16-SR  | 5I2309A-1  | 16-pin 150-mil SOIC-TAPE & REEL   | Industrial      |
| ASM5P2309A-1-16-TT  | 5P2309A-1  | 16-pin 4.4-mm TSSOP - TUBE        | Commercial      |
| ASM5I2309A-1-16-TT  | 5I2309A-1  | 16-pin 4.4-mm TSSOP - TUBE        | Industrial      |
| ASM5P2309A-1-16-TR  | 5P2309A-1  | 16-pin 4.4-mm TSSOP - TAPE & REEL | Commercial      |
| ASM5I2309A-1-16-TR  | 5I2309A-1  | 16-pin 4.4-mm TSSOP - TAPE & REEL | Industrial      |
| ASM5P2309A-1H-16-ST | 5P2309A-1H | 16-pin 150-mil SOIC-TUBE          | Commercial      |
| ASM5I2309A-1H-16-ST | 5I2309A-1H | 16-pin 150-mil SOIC- TUBE         | Industrial      |
| ASM5P2309A-1H-16-SR | 5P2309A-1H | 16-pin 150-mil SOIC-TAPE & REEL   | Commercial      |
| ASM5I2309A-1H-16-SR | 5I2309A-1H | 16-pin 150-mil SOIC-TAPE & REEL   | Industrial      |
| ASM5P2309A-1H-16-TT | 5P2309A-1H | 16-pin 4.4-mm TSSOP - TUBE        | Commercial      |
| ASM5I2309A-1H-16-TT | 5I2309A-1H | 16-pin 4.4-mm TSSOP - TUBE        | Industrial      |
| ASM5P2309A-1H-16-TR | 5P2309A-1H | 16-pin 4.4-mm TSSOP - TAPE & REEL | Commercial      |
| ASM5I2309A-1H-16-TR | 5I2309A-1H | 16-pin 4.4-mm TSSOP - TAPE & REEL | Industrial      |
| ASM5P2305A-1-08-ST  | 5P2305A-1  | 8-pin 150-mil SOIC-TUBE           | Commercial      |
| ASM5I2305A-1-08-ST  | 5I2305A-1  | 8-pin 150-mil SOIC- TUBE          | Industrial      |
| ASM5P2305A-1-08-SR  | 5P2305A-1  | 8-pin 150-mil SOIC-TAPE & REEL    | Commercial      |
| ASM5I2305A-1-08-SR  | 5I2305A-1  | 8-pin 150-mil SOIC-TAPE & REEL    | Industrial      |
| ASM5P2305A-1-08-TT  | 5P2305A-1  | 8-pin 4.4-mm TSSOP - TUBE         | Commercial      |
| ASM5I2305A-1-08-TT  | 5I2305A-1  | 8-pin 4.4-mm TSSOP - TUBE         | Industrial      |
| ASM5P2305A-1-08-TR  | 5P2305A-1  | 8-pin 4.4-mm TSSOP - TAPE & REEL  | Commercial      |
| ASM5I2305A-1-08-TR  | 5I2305A-1  | 8-pin 4.4-mm TSSOP - TAPE & REEL  | Industrial      |
| ASM5P2305A-1H-08-ST | 5P2305A-1H | 8-pin 150-mil SOIC-TUBE           | Commercial      |
| ASM5I2305A-1H-08-ST | 5I2305A-1H | 8-pin 150-mil SOIC- TUBE          | Industrial      |
| ASM5P2305A-1H-08-SR | 5P2305A-1H | 8-pin 150-mil SOIC-TAPE & REEL    | Commercial      |
| ASM5I2305A-1H-08-SR | 5I2305A-1H | 8-pin 150-mil SOIC-TAPE & REEL    | Industrial      |
| ASM5P2305A-1H-08-TT | 5P2305A-1H | 8-pin 4.4-mm TSSOP - TUBE         | Commercial      |
| ASM5I2305A-1H-08-TT | 5I2305A-1H | 8-pin 4.4-mm TSSOP - TUBE         | Industrial      |
| ASM5P2305A-1H-08-TR | 5P2305A-1H | 8-pin 4.4-mm TSSOP - TAPE & REEL  | Commercial      |
| ASM5I2305A-1H-08-TR | 5I2305A-1H | 8-pin 4.4-mm TSSOP - TAPE & REEL  | Industrial      |



rev 1.6

## Ordering Codes (cont'd)

| Ordering Code        | Marking     | Package Type                              | Operating Range |
|----------------------|-------------|---|-----------------|
| ASM5P2309AF-1-16-ST  | 5P2309AF-1  | 16-pin 150-mil SOIC-TUBE,Pb Free          | Commercial      |
| ASM5I2309AF-1-16-ST  | 5I2309AF-1  | 16-pin 150-mil SOIC- TUBE,Pb Free         | Industrial      |
| ASM5P2309AF-1-16-SR  | 5P2309AF-1  | 16-pin 150-mil SOIC-TAPE & REEL,Pb Free   | Commercial      |
| ASM5I2309AF-1-16-SR  | 5I2309AF-1  | 16-pin 150-mil SOIC-TAPE & REEL,Pb Free   | Industrial      |
| ASM5P2309AF-1-16-TT  | 5P2309AF-1  | 16-pin 4.4-mm TSSOP - TUBE,Pb Free        | Commercial      |
| ASM5I2309AF-1-16-TT  | 5I2309AF-1  | 16-pin 4.4-mm TSSOP - TUBE,Pb Free        | Industrial      |
| ASM5P2309AF-1-16-TR  | 5P2309AF-1  | 16-pin 4.4-mm TSSOP - TAPE & REEL,Pb Free | Commercial      |
| ASM5I2309AF-1-16-TR  | 5I2309AF-1  | 16-pin 4.4-mm TSSOP - TAPE & REEL,Pb Free | Industrial      |
| ASM5P2309AF-1H-16-ST | 5P2309AF-1H | 16-pin 150-mil SOIC-TUBE,Pb Free          | Commercial      |
| ASM5I2309AF-1H-16-ST | 5I2309AF-1H | 16-pin 150-mil SOIC- TUBE,Pb Free         | Industrial      |
| ASM5P2309AF-1H-16-SR | 5P2309AF-1H | 16-pin 150-mil SOIC-TAPE & REEL,Pb Free   | Commercial      |
| ASM5I2309AF-1H-16-SR | 5I2309AF-1H | 16-pin 150-mil SOIC-TAPE & REEL,Pb Free   | Industrial      |
| ASM5P2309AF-1H-16-TT | 5P2309AF-1H | 16-pin 4.4-mm TSSOP - TUBE,Pb Free        | Commercial      |
| ASM5I2309AF-1H-16-TT | 5I2309AF-1H | 16-pin 4.4-mm TSSOP - TUBE,Pb Free        | Industrial      |
| ASM5P2309AF-1H-16-TR | 5P2309AF-1H | 16-pin 4.4-mm TSSOP - TAPE & REEL,Pb Free | Commercial      |
| ASM5I2309AF-1H-16-TR | 5I2309AF-1H | 16-pin 4.4-mm TSSOP - TAPE & REEL,Pb Free | Industrial      |
| ASM5P2305AF-1-08-ST  | 5P2305AF-1  | 8-pin 150-mil SOIC-TUBE,Pb Free           | Commercial      |
| ASM5I2305AF-1-08-ST  | 5I2305AF-1  | 8-pin 150-mil SOIC- TUBE,Pb Free          | Industrial      |
| ASM5P2305AF-1-08-SR  | 5P2305AF-1  | 8-pin 150-mil SOIC-TAPE & REEL,Pb Free    | Commercial      |
| ASM5I2305AF-1-08-SR  | 5I2305AF-1  | 8-pin 150-mil SOIC-TAPE & REEL,Pb Free    | Industrial      |
| ASM5P2305AF-1-08-TT  | 5P2305AF-1  | 8-pin 4.4-mm TSSOP - TUBE,Pb Free         | Commercial      |
| ASM5I2305AF-1-08-TT  | 5I2305AF-1  | 8-pin 4.4-mm TSSOP - TUBE,Pb Free         | Industrial      |
| ASM5P2305AF-1-08-TR  | 5P2305AF-1  | 8-pin 4.4-mm TSSOP - TAPE & REEL,Pb Free  | Commercial      |
| ASM5I2305AF-1-08-TR  | 5I2305AF-1  | 8-pin 4.4-mm TSSOP - TAPE & REEL,Pb Free  | Industrial      |
| ASM5P2305AF-1H-08-ST | 5P2305AF-1H | 8-pin 150-mil SOIC-TUBE,Pb Free           | Commercial      |
| ASM5I2305AF-1H-08-ST | 5I2305AF-1H | 8-pin 150-mil SOIC- TUBE,Pb Free          | Industrial      |
| ASM5P2305AF-1H-08-SR | 5P2305AF-1H | 8-pin 150-mil SOIC-TAPE & REEL,Pb Free    | Commercial      |
| ASM5I2305AF-1H-08-SR | 5I2305AF-1H | 8-pin 150-mil SOIC-TAPE & REEL,Pb Free    | Industrial      |
| ASM5P2305AF-1H-08-TT | 5P2305AF-1H | 8-pin 4.4-mm TSSOP - TUBE,Pb Free         | Commercial      |
| ASM5I2305AF-1H-08-TT | 5I2305AF-1H | 8-pin 4.4-mm TSSOP - TUBE,Pb Free         | Industrial      |
| ASM5P2305AF-1H-08-TR | 5P2305AF-1H | 8-pin 4.4-mm TSSOP - TAPE & REEL,Pb Free  | Commercial      |
| ASM5I2305AF-1H-08-TR | 5I2305AF-1H | 8-pin 4.4-mm TSSOP - TAPE & REEL,Pb Free  | Industrial      |



rev 1.6


## Ordering Codes (cont'd)

| Ordering Code        | Marking     | Package Type                             | Operating Range |
|----------------------|-------------|--|-----------------|
| ASM5P2309AG-1-16-ST  | 5P2309AG-1  | 16-pin 150-mil SOIC-TUBE, Green          | Commercial      |
| ASM5I2309AG-1-16-ST  | 5I2309AG-1  | 16-pin 150-mil SOIC- TUBE, Green         | Industrial      |
| ASM5P2309AG-1-16-SR  | 5P2309AG-1  | 16-pin 150-mil SOIC-TAPE & REEL, Green   | Commercial      |
| ASM5I2309AG-1-16-SR  | 5I2309AG-1  | 16-pin 150-mil SOIC-TAPE & REEL, Green   | Industrial      |
| ASM5P2309AG-1-16-TT  | 5P2309AG-1  | 16-pin 4.4-mm TSSOP - TUBE, Green        | Commercial      |
| ASM5I2309AG-1-16-TT  | 5I2309AG-1  | 16-pin 4.4-mm TSSOP - TUBE, Green        | Industrial      |
| ASM5P2309AG-1-16-TR  | 5P2309AG-1  | 16-pin 4.4-mm TSSOP - TAPE & REEL, Green | Commercial      |
| ASM5I2309AG-1-16-TR  | 5I2309AG-1  | 16-pin 4.4-mm TSSOP - TAPE & REEL, Green | Industrial      |
| ASM5P2309AG-1H-16-ST | 5P2309AG-1H | 16-pin 150-mil SOIC-TUBE, Green          | Commercial      |
| ASM5I2309AG-1H-16-ST | 5I2309AG-1H | 16-pin 150-mil SOIC- TUBE, Green         | Industrial      |
| ASM5P2309AG-1H-16-SR | 5P2309AG-1H | 16-pin 150-mil SOIC-TAPE & REEL, Green   | Commercial      |
| ASM5I2309AG-1H-16-SR | 5I2309AG-1H | 16-pin 150-mil SOIC-TAPE & REEL, Green   | Industrial      |
| ASM5P2309AG-1H-16-TT | 5P2309AG-1H | 16-pin 4.4-mm TSSOP - TUBE, Green        | Commercial      |
| ASM5I2309AG-1H-16-TT | 5I2309AG-1H | 16-pin 4.4-mm TSSOP - TUBE, Green        | Industrial      |
| ASM5P2309AG-1H-16-TR | 5P2309AG-1H | 16-pin 4.4-mm TSSOP - TAPE & REEL, Green | Commercial      |
| ASM5I2309AG-1H-16-TR | 5I2309AG-1H | 16-pin 4.4-mm TSSOP - TAPE & REEL, Green | Industrial      |
| ASM5P2305AG-1-08-ST  | 5P2305AG-1  | 8-pin 150-mil SOIC-TUBE, Green           | Commercial      |
| ASM5I2305AG-1-08-ST  | 5I2305AG-1  | 8-pin 150-mil SOIC- TUBE, Green          | Industrial      |
| ASM5P2305AG-1-08-SR  | 5P2305AG-1  | 8-pin 150-mil SOIC-TAPE & REEL, Green    | Commercial      |
| ASM5I2305AG-1-08-SR  | 5I2305AG-1  | 8-pin 150-mil SOIC-TAPE & REEL, Green    | Industrial      |
| ASM5P2305AG-1-08-TT  | 5P2305AG-1  | 8-pin 4.4-mm TSSOP - TUBE, Green         | Commercial      |
| ASM5I2305AG-1-08-TT  | 5I2305AG-1  | 8-pin 4.4-mm TSSOP - TUBE, Green         | Industrial      |
| ASM5P2305AG-1-08-TR  | 5P2305AG-1  | 8-pin 4.4-mm TSSOP - TAPE & REEL, Green  | Commercial      |
| ASM5I2305AG-1-08-TR  | 5I2305AG-1  | 8-pin 4.4-mm TSSOP - TAPE & REEL, Green  | Industrial      |
| ASM5P2305AG-1H-08-ST | 5P2305AG-1H | 8-pin 150-mil SOIC-TUBE, Green           | Commercial      |
| ASM5I2305AG-1H-08-ST | 5I2305AG-1H | 8-pin 150-mil SOIC- TUBE, Green          | Industrial      |
| ASM5P2305AG-1H-08-SR | 5P2305AG-1H | 8-pin 150-mil SOIC-TAPE & REEL, Green    | Commercial      |
| ASM5I2305AG-1H-08-SR | 5I2305AG-1H | 8-pin 150-mil SOIC-TAPE & REEL, Green    | Industrial      |
| ASM5P2305AG-1H-08-TT | 5P2305AG-1H | 8-pin 4.4-mm TSSOP - TUBE, Green         | Commercial      |
| ASM5I2305AG-1H-08-TT | 5I2305AG-1H | 8-pin 4.4-mm TSSOP - TUBE, Green         | Industrial      |
| ASM5P2305AG-1H-08-TR | 5P2305AG-1H | 8-pin 4.4-mm TSSOP - TAPE & REEL, Green  | Commercial      |
| ASM5I2305AG-1H-08-TR | 5I2305AG-1H | 8-pin 4.4-mm TSSOP - TAPE & REEL, Green  | Industrial      |



rev 1.6  
Device Ordering Information

**A S M 5 P 2 3 0 5 A F - 0 8 - T R**



Licensed under US patent #5,488,627, #6,646,463 and #5,631,920.



Alliance Semiconductor Corporation  
2575 Augustine Drive,  
Santa Clara, CA 95054  
Tel# 408-855-4900  
Fax: 408-855-4999  
www.alsc.com

Copyright © Alliance Semiconductor  
All Rights Reserved  
Part Number: ASM5P2309A  
ASM5P2305A  
Document Version: 1.6

Note: This product utilizes US Patent # 6,646,463 Impedance Emulator Patent issued to Alliance Semiconductor, dated 11-11-2003

© Copyright 2003 Alliance Semiconductor Corporation. All rights reserved. Our three-point logo, our name and Intelliwatt are trademarks or registered trademarks of Alliance. All other brand and product names may be the trademarks of their respective companies. Alliance reserves the right to make changes to this document and its products at any time without notice. Alliance assumes no responsibility for any errors that may appear in this document. The data contained herein represents Alliance's best data and/or estimates at the time of issuance. Alliance reserves the right to change or correct this data at any time, without notice. If the product described herein is under development, significant changes to these specifications are possible. The information in this product data sheet is intended to be general descriptive information for potential customers and users, and is not intended to operate as, or provide, any guarantee or warranty to any user or customer. Alliance does not assume any responsibility or liability arising out of the application or use of any product described herein, and disclaims any express or implied warranties related to the sale and/or use of Alliance products including liability or warranties related to fitness for a particular purpose, merchantability, or infringement of any intellectual property rights, except as express agreed to in Alliance's Terms and Conditions of Sale (which are available from Alliance). All sales of Alliance products are made exclusively according to Alliance's Terms and Conditions of Sale. The purchase of products from Alliance does not convey a license under any patent rights, copyrights; mask works rights, trademarks, or any other intellectual property rights of Alliance or third parties. Alliance does not authorize its products for use as critical components in life-supporting systems where a malfunction or failure may reasonably be expected to result in significant injury to the user, and the inclusion of Alliance products in such life-supporting systems implies that the manufacturer assumes all risk of such use and agrees to indemnify Alliance against all claims arising from such use.

Copyright © Each Manufacturing Company.

All Datasheets cannot be modified without permission.

This datasheet has been download from :

[www.AllDataSheet.com](http://www.AllDataSheet.com)

100% Free DataSheet Search Site.

Free Download.

No Register.

Fast Search System.

[www.AllDataSheet.com](http://www.AllDataSheet.com)