

## 0.5A HIGH-SPEED MOSFET DRIVERS

### FEATURES

- Latch-Up Protected: Will Withstand 500mA Reverse Current
- Input Will Withstand Negative Inputs Up to 5V
- ESD Protected ..... 4kV
- High Peak Output Current ..... 0.5A
- Wide Operating Range ..... 4.5V to 16V
- High Capacitive Load Drive Capability ..... 500pF in 25nsec
- Short Delay Time ..... 35nsec Typ
- Consistent Delay Times With Changes in Supply Voltage
- Matched Delay Times
- Low Supply Current
  - With Logic “1” Input ..... 500µA
  - With Logic “0” Input ..... 150µA
- Low Output Impedance ..... 16Ω
- Pinout Same as TC1411/12/13


### GENERAL DESCRIPTION

The TC1410/1410N are 0.5V CMOS buffer/drivers. They will not latch up under any conditions within their power and voltage ratings. They are not subject to damage when up to 5V of noise spiking of either polarity occurs on the ground pin. They can accept, without damage or logic upset, up to 500mA of current of either polarity being forced back into their output. All terminals are fully protected against up to 4 kV of electrostatic discharge.

As MOSFET drivers, the TC1410/1410N can easily switch 500pF gate capacitance in 25nsec with matched rise and fall times, and provide low enough impedance in both the ON and the OFF states to ensure the MOSFET's intended state will not be affected, even by large transients. The rise and fall time edges are matched to allow driving short-duration inputs with greater accuracy.

**4**


### PIN CONFIGURATIONS



### ORDERING INFORMATION

| Part No.   | Package           | Temp. Range    |
|------------|-------------------|----------------|
| TC1410COA  | 8-Pin SOIC        | 0°C to +70°C   |
| TC1410CPA  | 8-Pin Plastic DIP | 0°C to +70°C   |
| TC1410EOA  | 8-Pin SOIC        | -40°C to +85°C |
| TC1410EPA  | 8-Pin Plastic DIP | -40°C to +85°C |
| TC1410NCOA | 8-Pin SOIC        | 0°C to +70°C   |
| TC1410NCPA | 8-Pin Plastic DIP | 0°C to +70°C   |
| TC1410NEOA | 8-Pin SOIC        | -40°C to +85°C |
| TC1410NEPA | 8-Pin Plastic DIP | -40°C to +85°C |

### FUNCTIONAL BLOCK DIAGRAM



# 0.5A HIGH-SPEED MOSFET DRIVERS

## TC1410 TC1410N

### ABSOLUTE MAXIMUM RATINGS\*

|  |                  |
|--|------------------|
| Supply Voltage .....   | +20V             |
| Input Voltage, IN A or IN B. ( $V_{DD} + 0.3V$ ) to (GND – 5.0V) |                  |
| Maximum Chip Temperature .....                                   | +150°C           |
| Storage Temperature Range .....                                  | – 65°C to +150°C |
| Lead Temperature (Soldering, 10 sec) .....                       | +300°C           |
| Package Thermal Resistance                                       |                  |
| CerDIP $R_{\theta J-A}$ .....                                    | 150°C/W          |
| CerDIP $R_{\theta J-C}$ .....                                    | 50°C/W           |
| PDIP $R_{\theta J-A}$ .....                                      | 125°C/W          |
| PDIP $R_{\theta J-C}$ .....                                      | 42°C/W           |
| SOIC $R_{\theta J-A}$ .....                                      | 155°C/W          |
| SOIC $R_{\theta J-C}$ .....                                      | 45°C/W           |

### Operating Temperature Range

|   |                 |
|---|-----------------|
| C Version .....                                   | 0°C to +70°C    |
| E Version .....                                   | – 40°C to +85°C |
| Power Dissipation ( $T_A \leq 70^\circ\text{C}$ ) |                 |
| Plastic DIP .....                                 | 730mW           |
| CerDIP .....                                      | 800mW           |
| SOIC .....  | 470mW           |

\*Static-sensitive device. Unused devices must be stored in conductive material. Protect devices from static discharge and static fields. Stresses above those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only and functional operation of the device at these or any other conditions above those indicated in the operation sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

**ELECTRICAL CHARACTERISTICS:** Over operating temperature range with  $4.5V \leq V_{DD} \leq 16V$ , unless otherwise specified. Typical values are measured at  $T_A=25^\circ\text{C}$ ;  $V_{DD}=16V$ .

| Symbol                         | Parameter  | Test Conditions   | Min         | Typ | Max     | Unit          |
|--------------------------------|--|---|-------------|-----|---------|---------------|
| <b>Input</b>                   |  |   |             |     |         |               |
| $V_{IH}$                       | Logic 1 High Input Voltage                       |   | 2.0         | —   | —       | V             |
| $V_{IL}$                       | Logic 0 Low Input Voltage                        |   | —           | —   | 0.8     | V             |
| $I_{IN}$                       | Input Current                                    | $-5V \leq V_{IN} \leq V_{DD}$<br>$-40^\circ\text{C} \leq T_A \leq 85^\circ\text{C}$ | – 1<br>– 10 | —   | 1<br>10 | $\mu\text{A}$ |
| <b>Output</b>                  |  |   |             |     |         |               |
| $V_{OH}$                       | High Output Voltage                              | DC Test   | —           | —   | V       |               |
| $V_{OL}$                       | Low Output Voltage                               | DC Test   | —           | —   | 0.025   | V             |
| $R_O$                          | Output Resistance                                | $V_{DD} = 16V, I_O = 10\text{mA}$   | —           | 16  | 22      | $\Omega$      |
|                                |  | $T_A=25^\circ\text{C}$  | —           | 20  | 28      |               |
|                                |  | $0^\circ\text{C} \leq T_A \leq 70^\circ\text{C}$                                    | —           | 20  | 28      |               |
|                                |  | $-40^\circ\text{C} \leq T_A \leq 85^\circ\text{C}$                                  | —           | 20  | 28      |               |
| $I_{PK}$                       | Peak Output Current                              | $V_{DD} = 16V$  | —           | 0.5 | —       | A             |
| $I_{REV}$                      | Latch-Up Protection<br>Withstand Reverse Current | Duty Cycle $\leq 2\%$<br>$t \leq 300 \mu\text{sec}$                                 | 0.5         | —   | —       | A             |
| <b>Switching Time (Note 1)</b> |  |   |             |     |         |               |
| $t_R$                          | Rise Time  | Figure 1  | —           | 25  | 35      | nsec          |
|                                |  |   | —           | 27  | 40      |               |
|                                |  |   | —           | 29  | 40      |               |
| $t_F$                          | Fall Time  | Figure 1  | —           | 25  | 35      | nsec          |
|                                |  |   | —           | 27  | 40      |               |
|                                |  |   | —           | 29  | 40      |               |
| $t_{D1}$                       | Delay Time                                       | Figure 1  | —           | 30  | 40      | nsec          |
|                                |  |   | —           | 33  | 45      |               |
|                                |  |   | —           | 35  | 45      |               |
| $t_{D2}$                       | Delay Time                                       | Figure 1  | —           | 30  | 40      | nsec          |
|                                |  |   | —           | 33  | 45      |               |
|                                |  |   | —           | 35  | 45      |               |
| <b>Power Supply</b>            |  |   |             |     |         |               |
| $I_S$                          | Power Supply Current                             | $V_{IN} = 3V$<br>$V_{IN} = 0V$  | —           | 0.5 | 1.0     | mA            |
|                                |  | $V_{DD} = 16V$  | —           | 0.1 | 0.15    |               |

**NOTE:** 1. Switching times are guaranteed by design.






Figure 1. Switching Time Test Circuit




## TC1410 TC1410N

### TYPICAL CHARACTERISTICS


**Quiescent Supply Current vs. Supply Voltage**  
 $T_A = 25^\circ\text{C}$




**Quiescent Supply Current vs. Temperature**  
 $V_{\text{SUPPLY}} = 16\text{V}$




**Input Threshold vs. Supply Voltage**  
 $T_A = 25^\circ\text{C}$




**Input Threshold vs. Temperature**  
 $V_{\text{SUPPLY}} = 16\text{V}$



**High-State Output Resistance**




**Low-State Output Resistance**




## TYPICAL CHARACTERISTICS (Cont.)


**Rise Time vs. Supply Voltage**  
 $C_{LOAD} = 500\text{pF}$




**Fall Time vs. Supply Voltage**  
 $C_{LOAD} = 500\text{pF}$




**T<sub>D1</sub> Propagation Delay vs. Supply Voltage**  
 $C_{LOAD} = 500\text{pF}$




**T<sub>D2</sub> Propagation Delay vs. Supply Voltage**  
 $C_{LOAD} = 500\text{pF}$



**Rise and Fall Times vs. Capacitive Load**  
 $T_A = 25^\circ\text{C}, V_{DD} = 16\text{V}$



**Propagation Delays vs. Capacitive Load**  
 $T_A = 25^\circ\text{C}, V_{DD} = 16\text{V}$



4

Copyright © Each Manufacturing Company.

All Datasheets cannot be modified without permission.

This datasheet has been download from :

[www.AllDataSheet.com](http://www.AllDataSheet.com)

100% Free DataSheet Search Site.

Free Download.

No Register.

Fast Search System.

[www.AllDataSheet.com](http://www.AllDataSheet.com)