


10524



NOTES

1. Unused outputs should be loaded 100 Ω to ground.
2. $t_{THL} = t_{TLH} = 5.5 \text{ ns} \pm 0.5 \text{ ns}$ (10% - 90%).
3. $t_p = 40 \text{ ns} \pm 2.0 \text{ ns}$.
4. $Z_{OUT} = 50 \Omega$.
5. $C_L = \text{Jig and stray capacitance} \leq 5.0 \text{ pF}$.




Figure 1. Switching Test Circuit and Waveforms

NOTES

1. 50 Ω termination to ground located in each scope channel input.
2. All input and output cables to the scope are equal lengths of 50 Ω coaxial cable. Wire length should be $< 1/4$ inch from TP_{IN} to input pin and TP_{OUT} to output pin.

10524
QUIESCENT LIMIT TABLE *

*** ELECTRICAL CHARACTERISTICS**

Each MECL 10K series circuit has been designed to meet the dc specifications shown in the test table, after thermal equilibrium has been established. The circuit is in a test socket or mounted on a printed circuit board and transverse air flow greater than 500 linear fpm is maintained. Outputs are terminated through a 100 Ω resistor to - 2.0 volts.

Test Temperature	Test Voltage Values (Volts)							
	V _{IH1}	V _{IL1}	V _{IHL}	V _{IHH}	V _{CH}	V _{CG}	V _{EE}	V _{EEL}
T _A = 25 °C	+ 2.4	+ 0.4	+ 1.10	+ 1.80	+ 7.0	+ 2.0	- 5.2	- 3.2
T _A = 125 °C	+ 2.4	+ 0.4	+ 0.80	+ 1.80	+ 7.0	+ 2.0	- 5.2	- 3.2
T _A = - 55 °C	+ 2.4	+ 0.4	+ 1.10	+ 2.00	+ 7.0	+ 2.0	- 5.2	- 3.2

Symbol	Parameter	Limits						Units	TEST VOLTAGE APPLIED TO PINS BELOW									
		+ 25 °C		+ 125 °C		- 55 °C			Pinouts referenced are for DIL package, check Pin Assignments V _{CC} = 5.0 V, I _{IN} = 10 mA, Output Load = 100 Ω to - 2.0 V									
		Subgroup 1	Subgroup 2	Subgroup 3	Min	Max	Min		Max	V _{IH1}	V _{IL1}	V _{IHL}	V _{IHH}	V _{IHL}	V _{IHH}	V _{CH}	V _{CG}	V _{EE}
V _{OH}	High Output Voltage	- 0.93	- 0.76	- 0.825	- 0.63	- 1.08	- 0.88	V	5, 6, 7, 10, 11	6					16	8	9	1 - 4, 12 - 15
V _{OL}	Low Output Voltage	- 1.85	- 1.62	- 1.82	- 1.545	- 1.92	- 1.655	V	5, 6, 7, 10, 11	6					16	8	9	1 - 4, 12 - 15
V _{OH1}	High Output Voltage	- 0.95		- 0.845		- 1.10		V	5, 6, 7, 10, 11		5, 6, 7, 10, 11			16	8	9	1 - 4, 12 - 15	
V _{OL1}	Low Output Voltage		- 1.60		- 1.525		- 1.635	V	5, 6, 7, 10, 11		5, 6, 7, 10, 11			16	8	9	1 - 4, 12 - 15	
I _{EE}	Power Supply Current		- 66		- 73		- 73	mA						16	8	9	8	
I _{IH1}	Input Current High		50		85		85	μA	5, 7, 10, 11					6, 16	8	9	5, 7, 10, 11	
I _{IL1}	Input Current Low	- 3.2		- 5.5		- 3.2		mA	6	5, 7, 10, 11				16	8	9	5, 7, 10, 11	
I _{IH2}	Input Current High		200		340		340	μA	6					5, 7, 10, 11, 16	8	9	6	
I _{IL2}	Input Current Low	- 12.8		- 22		- 12.8		mA		6				16	8	9	6	
V _{IC}	Input Clamp Voltage	- 1.5						V						5 - 7, 10, 11	8	9	5 - 7, 10, 11	

PACKAGE OUTLINE DIMENSIONS

A letter suffix to the MECL logic function part number is used to specify the package style (see drawings below). See appropriate selector guide for specific packaging available for a given device type.

L SUFFIX CERAMIC PACKAGE CASE 620-09																																																																										
<table border="1"> <thead> <tr> <th rowspan="2">DIM</th> <th colspan="2">MILLIMETERS</th> <th colspan="2">INCHES</th> </tr> <tr> <th>MIN</th> <th>MAX</th> <th>MIN</th> <th>MAX</th> </tr> </thead> <tbody> <tr> <td>A</td> <td>19.05</td> <td>19.81</td> <td>0.750</td> <td>0.780</td> </tr> <tr> <td>B</td> <td>6.27</td> <td>6.98</td> <td>0.245</td> <td>0.275</td> </tr> <tr> <td>C</td> <td>4.08</td> <td>5.08</td> <td>0.160</td> <td>0.200</td> </tr> <tr> <td>D</td> <td>0.28</td> <td>0.51</td> <td>0.011</td> <td>0.020</td> </tr> <tr> <td>F</td> <td>1.40</td> <td>1.65</td> <td>0.055</td> <td>0.065</td> </tr> <tr> <td>G</td> <td colspan="2">2.54 BSC</td> <td colspan="2">0.100 BSC</td> </tr> <tr> <td>H</td> <td>0.51</td> <td>1.14</td> <td>0.020</td> <td>0.045</td> </tr> <tr> <td>J</td> <td>0.20</td> <td>0.30</td> <td>0.008</td> <td>0.012</td> </tr> <tr> <td>K</td> <td>3.18</td> <td>4.08</td> <td>0.125</td> <td>0.160</td> </tr> <tr> <td>L</td> <td>7.37</td> <td>7.87</td> <td>0.290</td> <td>0.310</td> </tr> <tr> <td>M</td> <td colspan="2">15°</td> <td colspan="2">15°</td> </tr> <tr> <td>N</td> <td>0.51</td> <td>1.02</td> <td>0.020</td> <td>0.040</td> </tr> </tbody> </table> <p>NOTES: 1. LEADS WITHIN 0.13 mm (0.005) RADIUS OF TRUE POSITION AT SEATING PLANE AT MAXIMUM MATERIAL CONDITION. 2. PACKAGE INDEX: NOTCH IN LEAD NOTCH IN CERAMIC OR INK DOT. 3. DIM "L" TO CENTER OF LEADS WHEN FORMED PARALLEL.</p>						DIM	MILLIMETERS		INCHES		MIN	MAX	MIN	MAX	A	19.05	19.81	0.750	0.780	B	6.27	6.98	0.245	0.275	C	4.08	5.08	0.160	0.200	D	0.28	0.51	0.011	0.020	F	1.40	1.65	0.055	0.065	G	2.54 BSC		0.100 BSC		H	0.51	1.14	0.020	0.045	J	0.20	0.30	0.008	0.012	K	3.18	4.08	0.125	0.160	L	7.37	7.87	0.290	0.310	M	15°		15°		N	0.51	1.02	0.020	0.040
DIM	MILLIMETERS		INCHES																																																																							
	MIN	MAX	MIN	MAX																																																																						
A	19.05	19.81	0.750	0.780																																																																						
B	6.27	6.98	0.245	0.275																																																																						
C	4.08	5.08	0.160	0.200																																																																						
D	0.28	0.51	0.011	0.020																																																																						
F	1.40	1.65	0.055	0.065																																																																						
G	2.54 BSC		0.100 BSC																																																																							
H	0.51	1.14	0.020	0.045																																																																						
J	0.20	0.30	0.008	0.012																																																																						
K	3.18	4.08	0.125	0.160																																																																						
L	7.37	7.87	0.290	0.310																																																																						
M	15°		15°																																																																							
N	0.51	1.02	0.020	0.040																																																																						

L SUFFIX CERAMIC PACKAGE CASE 623-05 (LW SUFFIX FOR MC10H181 ONLY)																																																																					
<table border="1"> <thead> <tr> <th rowspan="2">DIM</th> <th colspan="2">MILLIMETERS</th> <th colspan="2">INCHES</th> </tr> <tr> <th>MIN</th> <th>MAX</th> <th>MIN</th> <th>MAX</th> </tr> </thead> <tbody> <tr> <td>A</td> <td>31.24</td> <td>32.77</td> <td>1.230</td> <td>1.290</td> </tr> <tr> <td>B</td> <td>12.70</td> <td>15.49</td> <td>0.500</td> <td>0.610</td> </tr> <tr> <td>C</td> <td>4.08</td> <td>5.59</td> <td>0.160</td> <td>0.220</td> </tr> <tr> <td>D</td> <td>0.41</td> <td>0.51</td> <td>0.016</td> <td>0.020</td> </tr> <tr> <td>F</td> <td>1.27</td> <td>1.52</td> <td>0.050</td> <td>0.060</td> </tr> <tr> <td>G</td> <td colspan="2">2.54 BSC</td> <td colspan="2">0.100 BSC</td> </tr> <tr> <td>J</td> <td>0.20</td> <td>0.30</td> <td>0.008</td> <td>0.012</td> </tr> <tr> <td>K</td> <td>3.18</td> <td>4.08</td> <td>0.125</td> <td>0.160</td> </tr> <tr> <td>L</td> <td colspan="2">15.24 BSC</td> <td colspan="2">0.600 BSC</td> </tr> <tr> <td>M</td> <td colspan="2">0° 15°</td> <td colspan="2">0° 15°</td> </tr> <tr> <td>N</td> <td>0.51</td> <td>1.27</td> <td>0.020</td> <td>0.050</td> </tr> </tbody> </table> <p>NOTES: 1. DIM "L" TO CENTER OF LEADS WHEN FORMED PARALLEL. 2. LEADS WITHIN 0.13 mm (0.005) RADIUS OF TRUE POSITION AT SEATING PLANE AT MAXIMUM MATERIAL CONDITION. (WHEN FORMED PARALLEL).</p>						DIM	MILLIMETERS		INCHES		MIN	MAX	MIN	MAX	A	31.24	32.77	1.230	1.290	B	12.70	15.49	0.500	0.610	C	4.08	5.59	0.160	0.220	D	0.41	0.51	0.016	0.020	F	1.27	1.52	0.050	0.060	G	2.54 BSC		0.100 BSC		J	0.20	0.30	0.008	0.012	K	3.18	4.08	0.125	0.160	L	15.24 BSC		0.600 BSC		M	0° 15°		0° 15°		N	0.51	1.27	0.020	0.050
DIM	MILLIMETERS		INCHES																																																																		
	MIN	MAX	MIN	MAX																																																																	
A	31.24	32.77	1.230	1.290																																																																	
B	12.70	15.49	0.500	0.610																																																																	
C	4.08	5.59	0.160	0.220																																																																	
D	0.41	0.51	0.016	0.020																																																																	
F	1.27	1.52	0.050	0.060																																																																	
G	2.54 BSC		0.100 BSC																																																																		
J	0.20	0.30	0.008	0.012																																																																	
K	3.18	4.08	0.125	0.160																																																																	
L	15.24 BSC		0.600 BSC																																																																		
M	0° 15°		0° 15°																																																																		
N	0.51	1.27	0.020	0.050																																																																	

P SUFFIX PLASTIC PACKAGE CASE 626-04																																																																										
<table border="1"> <thead> <tr> <th rowspan="2">DIM</th> <th colspan="2">MILLIMETERS</th> <th colspan="2">INCHES</th> </tr> <tr> <th>MIN</th> <th>MAX</th> <th>MIN</th> <th>MAX</th> </tr> </thead> <tbody> <tr> <td>A</td> <td>9.40</td> <td>10.16</td> <td>0.370</td> <td>0.400</td> </tr> <tr> <td>B</td> <td>6.10</td> <td>6.60</td> <td>0.240</td> <td>0.260</td> </tr> <tr> <td>C</td> <td>3.94</td> <td>4.45</td> <td>0.155</td> <td>0.175</td> </tr> <tr> <td>D</td> <td>0.28</td> <td>0.51</td> <td>0.011</td> <td>0.020</td> </tr> <tr> <td>F</td> <td>1.02</td> <td>1.52</td> <td>0.040</td> <td>0.060</td> </tr> <tr> <td>G</td> <td colspan="2">2.54 BSC</td> <td colspan="2">0.100 BSC</td> </tr> <tr> <td>H</td> <td>0.76</td> <td>1.27</td> <td>0.030</td> <td>0.050</td> </tr> <tr> <td>J</td> <td>0.20</td> <td>0.30</td> <td>0.008</td> <td>0.012</td> </tr> <tr> <td>K</td> <td>2.92</td> <td>3.43</td> <td>0.115</td> <td>0.135</td> </tr> <tr> <td>L</td> <td colspan="2">7.62 BSC</td> <td colspan="2">0.300 BSC</td> </tr> <tr> <td>M</td> <td colspan="2">10°</td> <td colspan="2">10°</td> </tr> <tr> <td>N</td> <td>0.51</td> <td>0.76</td> <td>0.020</td> <td>0.030</td> </tr> </tbody> </table> <p>NOTES: 1. LEAD POSITIONAL TOLERANCE: $\pm 0.13 (0.005) \text{ T A } \textcircled{B}$ 2. DIMENSION L TO CENTER OF LEADS WHEN FORMED PARALLEL. 3. PACKAGE CONTOUR OPTIONAL (ROUND OR SQUARE CORNERS). 4. DIMENSIONS A AND B ARE DATUMS. 5. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.</p>						DIM	MILLIMETERS		INCHES		MIN	MAX	MIN	MAX	A	9.40	10.16	0.370	0.400	B	6.10	6.60	0.240	0.260	C	3.94	4.45	0.155	0.175	D	0.28	0.51	0.011	0.020	F	1.02	1.52	0.040	0.060	G	2.54 BSC		0.100 BSC		H	0.76	1.27	0.030	0.050	J	0.20	0.30	0.008	0.012	K	2.92	3.43	0.115	0.135	L	7.62 BSC		0.300 BSC		M	10°		10°		N	0.51	0.76	0.020	0.030
DIM	MILLIMETERS		INCHES																																																																							
	MIN	MAX	MIN	MAX																																																																						
A	9.40	10.16	0.370	0.400																																																																						
B	6.10	6.60	0.240	0.260																																																																						
C	3.94	4.45	0.155	0.175																																																																						
D	0.28	0.51	0.011	0.020																																																																						
F	1.02	1.52	0.040	0.060																																																																						
G	2.54 BSC		0.100 BSC																																																																							
H	0.76	1.27	0.030	0.050																																																																						
J	0.20	0.30	0.008	0.012																																																																						
K	2.92	3.43	0.115	0.135																																																																						
L	7.62 BSC		0.300 BSC																																																																							
M	10°		10°																																																																							
N	0.51	0.76	0.020	0.030																																																																						

L SUFFIX CERAMIC PACKAGE CASE 632-08																																																																					
<table border="1"> <thead> <tr> <th rowspan="2">DIM</th> <th colspan="2">MILLIMETERS</th> <th colspan="2">INCHES</th> </tr> <tr> <th>MIN</th> <th>MAX</th> <th>MIN</th> <th>MAX</th> </tr> </thead> <tbody> <tr> <td>A</td> <td>19.05</td> <td>19.94</td> <td>0.750</td> <td>0.785</td> </tr> <tr> <td>B</td> <td>6.23</td> <td>7.11</td> <td>0.245</td> <td>0.280</td> </tr> <tr> <td>C</td> <td>3.94</td> <td>5.08</td> <td>0.155</td> <td>0.200</td> </tr> <tr> <td>D</td> <td>0.38</td> <td>0.50</td> <td>0.015</td> <td>0.020</td> </tr> <tr> <td>F</td> <td>1.40</td> <td>1.65</td> <td>0.055</td> <td>0.065</td> </tr> <tr> <td>G</td> <td colspan="2">2.54 BSC</td> <td colspan="2">0.100 BSC</td> </tr> <tr> <td>J</td> <td>0.21</td> <td>0.38</td> <td>0.008</td> <td>0.015</td> </tr> <tr> <td>K</td> <td>3.18</td> <td>4.31</td> <td>0.125</td> <td>0.170</td> </tr> <tr> <td>L</td> <td colspan="2">7.62 BSC</td> <td colspan="2">0.300 BSC</td> </tr> <tr> <td>M</td> <td colspan="2">0° 15°</td> <td colspan="2">0° 15°</td> </tr> <tr> <td>N</td> <td>0.51</td> <td>1.01</td> <td>0.020</td> <td>0.040</td> </tr> </tbody> </table> <p>NOTES: 1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982. 2. CONTROLLING DIMENSION: INCH. 3. DIMENSION L TO CENTER OF LEAD WHEN FORMED PARALLEL. 4. DIM F MAY NARROW TO 0.26 (0.030) WHERE THE LEAD ENTERS THE CERAMIC BODY.</p>						DIM	MILLIMETERS		INCHES		MIN	MAX	MIN	MAX	A	19.05	19.94	0.750	0.785	B	6.23	7.11	0.245	0.280	C	3.94	5.08	0.155	0.200	D	0.38	0.50	0.015	0.020	F	1.40	1.65	0.055	0.065	G	2.54 BSC		0.100 BSC		J	0.21	0.38	0.008	0.015	K	3.18	4.31	0.125	0.170	L	7.62 BSC		0.300 BSC		M	0° 15°		0° 15°		N	0.51	1.01	0.020	0.040
DIM	MILLIMETERS		INCHES																																																																		
	MIN	MAX	MIN	MAX																																																																	
A	19.05	19.94	0.750	0.785																																																																	
B	6.23	7.11	0.245	0.280																																																																	
C	3.94	5.08	0.155	0.200																																																																	
D	0.38	0.50	0.015	0.020																																																																	
F	1.40	1.65	0.055	0.065																																																																	
G	2.54 BSC		0.100 BSC																																																																		
J	0.21	0.38	0.008	0.015																																																																	
K	3.18	4.31	0.125	0.170																																																																	
L	7.62 BSC		0.300 BSC																																																																		
M	0° 15°		0° 15°																																																																		
N	0.51	1.01	0.020	0.040																																																																	

PACKAGE OUTLINE DIMENSIONS (continued)

T-90-20

**P SUFFIX
PLASTIC PACKAGE
CASE 646-06**

DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	18.16	19.58	0.715	0.770
B	6.10	6.60	0.240	0.260
C	3.69	4.69	0.145	0.185
D	0.38	0.53	0.015	0.021
F	1.02	1.78	0.040	0.070
G	2.54 BSC			
H	1.32	2.41	0.052	0.095
J	0.20	0.38	0.008	0.015
K	2.92	3.43	0.115	0.135
L	7.62 BSC			
M	0°	10°	0°	10°
N	0.39	1.01	0.015	0.039

NOTES:
 1. LEADS WITHIN 0.13 mm (0.005) RADIUS OF TRUE POSITION AT SEATING PLANE AT MAXIMUM MATERIAL CONDITION.
 2. DIMENSION "L" TO CENTER OF LEADS WHEN FORMED PARALLEL.
 3. DIMENSION "B" DOES NOT INCLUDE MOLD FLASH.
 4. ROUNDED CORNERS OPTIONAL.

**P SUFFIX
PLASTIC PACKAGE
CASE 648-08**

DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	18.80	19.95	0.750	0.770
B	6.35	6.85	0.250	0.270
C	3.69	4.44	0.145	0.175
D	0.39	0.53	0.015	0.021
F	1.02	1.77	0.040	0.070
G	2.54 BSC			
H	1.27 BSC			
J	0.21	0.38	0.008	0.015
K	2.80	3.30	0.110	0.130
L	7.50	7.74	0.295	0.305
M	0°	10°	0°	10°
S	0.51	1.01	0.020	0.040

NOTES:
 1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
 2. CONTROLLING DIMENSION: INCH.
 3. DIMENSION "L" TO CENTER OF LEADS WHEN FORMED PARALLEL.
 4. DIMENSION "B" DOES NOT INCLUDE MOLD FLASH.
 5. ROUNDED CORNERS OPTIONAL.

**P SUFFIX
PLASTIC PACKAGE
CASE 649-03**

**(PW SUFFIX
FOR MC10H181
ONLY)**

DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	31.50	32.13	1.240	1.265
B	13.21	13.72	0.520	0.540
C	4.70	5.21	0.185	0.205
D	0.38	0.51	0.015	0.020
F	1.02	1.52	0.040	0.060
G	2.54 BSC			
H	1.65	2.15	0.065	0.085
J	0.20	0.30	0.008	0.012
K	2.92	3.43	0.115	0.135
L	14.99	15.49	0.590	0.610
M	— 10°			
N	0.51	1.02	0.020	0.040
P	0.13	0.38	0.005	0.015
O	0.51	0.76	0.020	0.030

NOTES:
 1. LEADS WITHIN 0.13 mm (0.005) RADIUS OF TRUE POSITION AT SEATING PLANE AT MAXIMUM MATERIAL CONDITION.
 2. DIMENSION "L" TO CENTER OF LEADS WHEN FORMED PARALLEL.

**F SUFFIX
CERAMIC PACKAGE
CASE 650-05**

DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	9.40	9.90	0.370	0.390
B	6.23	6.80	0.245	0.260
C	1.53	2.15	0.060	0.085
D	0.38	0.48	0.014	0.019
G	1.27 BSC			
H	0.64	0.61	0.025	0.040
J	0.11	0.17	0.004	0.007
K	6.35	9.39	0.250	0.370
L	18.93	—	0.745	—
N	—	0.50	—	0.020


NOTES:
 1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
 2. CONTROLLING DIMENSION: INCH.
 3. DIMENSION "A" AND "B" ALLOW FOR LID MISALIGNMENT, AND GLASS MENISCUS.
 4. DIMENSION "H" SHALL BE MEASURED AT THE POINT OF EXIT OF THE LEAD FROM THE BODY.
 5. LEAD NUMBER 1 IDENTIFIED BY TAB ON LEAD OR DOT ON COVER.
 6. DIMENSION "J" INCLUDES SOLDER LEAD FINISH.
 7. LEAD NUMBERS SHOWN FOR REFERENCE ONLY.

1

PACKAGE OUTLINE DIMENSIONS (continued)

T-90-20


**L SUFFIX
CERAMIC PACKAGE
CASE 693-02**



DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	9.91	10.92	0.390	0.430
B	6.22	6.99	0.245	0.275
C	4.32	5.08	0.170	0.200
D	0.41	0.51	0.016	0.020
F	1.40	1.65	0.056	0.065
G	2.54 BSC		0.100 BSC	
H	1.14	1.65	0.045	0.065
J	0.20	0.30	0.008	0.012
K	3.18	4.06	0.125	0.160
L	7.37	7.87	0.290	0.310
M	0°	15°		15°
N	0.51	1.02	0.020	0.040

- NOTES:
1. LEADS WITHIN 0.13 mm (0.005) RAD OF TRUE POSITION AT SEATING PLANE AT MAXIMUM MATERIAL CONDITION.
2. DIMENSION "L" TO CENTER OF LEADS WHEN FORMED PARALLEL.


**P SUFFIX
PLASTIC PACKAGE
CASE 707-02**



DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	22.22	23.24	0.875	0.915
B	6.10	6.60	0.240	0.260
C	3.56	4.57	0.140	0.180
D	0.36	0.56	0.014	0.022
F	1.27	1.78	0.050	0.070
G	2.54 BSC		0.100 BSC	
H	1.02	1.52	0.040	0.060
J	0.20	0.30	0.008	0.012
K	2.92	3.43	0.115	0.135
L	7.62 BSC		0.300 BSC	
M	0°	15°		15°
N	0.51	1.02	0.020	0.040

- NOTES:
1. POSITIONAL TOLERANCE OF LEADS (D), SHALL BE WITHIN 0.25mm(0.010) AT MAXIMUM MATERIAL CONDITION, IN RELATION TO SEATING PLANE AND EACH OTHER.
2. DIMENSION "L" TO CENTER OF LEADS WHEN FORMED PARALLEL.
3. DIMENSION B DOES NOT INCLUDE MOLD FLASH.


**P SUFFIX
PLASTIC PACKAGE
CASE 724-03**



DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	31.25	32.13	1.230	1.265
B	6.35	6.95	0.250	0.270
C	3.69	4.44	0.145	0.175
D	0.38	0.51	0.015	0.020
E	1.27 BSC		0.050 BSC	
F	1.02	1.52	0.040	0.060
G	2.54 BSC		0.100 BSC	
J	0.18	0.30	0.007	0.012
K	2.80	3.55	0.110	0.140
L	7.62 BSC		0.300 BSC	
M	0°	15°		15°
N	0.51	1.01	0.020	0.040

- NOTES:
1. CHAMFERED CONTOUR OPTIONAL.
2. DIM "L" TO CENTER OF LEADS WHEN FORMED PARALLEL.
3. DIMENSIONS AND TOLERANCES PER ANSI Y14.5M, 1982.
4. CONTROLLING DIMENSION: INCH.

**L SUFFIX
CERAMIC PACKAGE
CASE 726-04**




DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	22.35	23.11	0.880	0.910
B	6.10	7.49	0.240	0.295
C		5.08		0.200
D	0.38	0.53	0.015	0.021
F	1.40	1.78	0.055	0.070
G	2.54 BSC		0.100 BSC	
H	0.51	1.14	0.020	0.045
J	0.20	0.30	0.008	0.012
K	3.18	4.32	0.125	0.170
L	7.62 BSC		0.300 BSC	
M	0°	15°		15°
N	0.51	1.02	0.020	0.040

- NOTES:
1. LEADS, TRUE POSITIONED WITHIN 0.25 mm (0.010) DIA. AT SEATING PLANE, AT MAXIMUM MATERIAL CONDITION.
2. DIM "L" TO CENTER OF LEADS WHEN FORMED PARALLEL.
3. DIM "A" & "B" INCLUDES MENISCUS.
4. "F" DIMENSION IS FOR FULL LEADS. "HALF" LEADS ARE OPTIONAL AT LEAD POSITIONS 1, 9, 10, AND 18.

PACKAGE OUTLINE DIMENSIONS (continued)


**L SUFFIX
CERAMIC PACKAGE
CASE 732-03**



DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	22.68	25.15	0.940	0.990
B	6.60	7.43	0.260	0.295
C	3.81	5.08	0.150	0.200
D	0.38	0.56	0.015	0.022
F	1.40	1.65	0.055	0.065
G	2.54 BSC		0.100 BSC	
H	0.51	1.27	0.020	0.050
J	0.20	0.30	0.008	0.012
K	3.18	4.06	0.125	0.160
L	7.62 BSC		0.300 BSC	
M	0°	15°	0°	15°
N	0.25	1.02	0.010	0.040

- NOTES:
- LEADS WITHIN 0.25 mm (0.010) DIA. TRUE POSITION AT SEATING PLANE, AT MAXIMUM MATERIAL CONDITION.
 - DIM L TO CENTER OF LEADS WHEN FORMED PARALLEL.
 - DIM A AND B INCLUDES MENISCUS.


**P SUFFIX
PLASTIC PACKAGE
CASE 738-03**



DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	25.65	27.17	1.010	1.070
B	6.10	6.60	0.240	0.260
C	3.81	4.57	0.150	0.180
D	0.39	0.55	0.015	0.022
E	1.27 BSC		0.050 BSC	
F	1.27	1.77	0.050	0.070
G	2.54 BSC		0.100 BSC	
J	0.21	0.38	0.008	0.015
K	2.80	3.55	0.110	0.140
L	7.62 BSC		0.300 BSC	
M	0°	15°	0°	15°
N	0.51	1.01	0.020	0.040

- NOTES:
- DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
 - CONTROLLING DIMENSION: INCH.
 - DIMENSION "L" TO CENTER OF LEAD WHEN FORMED PARALLEL.
 - DIMENSION "B" DOES NOT INCLUDE MOLD FLASH.


**D SUFFIX
PLASTIC SOIC PACKAGE
CASE 751-03**



DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	4.80	5.00	0.189	0.196
B	3.80	4.00	0.150	0.157
C	1.25	1.75	0.054	0.068
D	0.25	0.49	0.010	0.019
F	0.40	1.25	0.016	0.049
G	1.27 BSC		0.050 BSC	
J	0.18	0.25	0.007	0.009
K	0.10	0.25	0.004	0.009
M	0°	7°	0°	7°
P	5.80	6.20	0.229	0.244
R	0.25	0.50	0.010	0.019

- NOTES:
- DIMENSIONS "A" AND "B" ARE DATUMS AND "T" IS A DATUM SURFACE.
 - DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
 - CONTROLLING D.M.: MILLIMETER.
 - DIMENSION "A" AND "B" DO NOT INCLUDE MOLD PROTRUSION.
 - MAXIMUM MOLD PROTRUSION 0.15 (0.006) PER SIDE.



**L SUFFIX
CERAMIC PACKAGE
CASE 758-01**



DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	31.50	32.64	1.250	1.285
B	7.24	7.75	0.285	0.305
C	3.68	4.44	0.145	0.175
D	0.38	0.53	0.015	0.021
F	1.14	1.57	0.045	0.062
G	2.54 BSC		0.100 BSC	
J	0.20	0.33	0.008	0.013
K	2.54	4.19	0.100	0.165
L	7.62	7.87	0.300	0.310
N	0.51	1.27	0.020	0.050
P	3.14	10.16	0.125	0.400

- NOTES:
- DIMENSION A IS DATUM.
 - POSITIONAL TOLERANCE FOR LEADS: 24 PLACES
 - "T" IS SEATING PLANE.
 - DIMENSION L TO CENTER OF LEADS WHEN FORMED PARALLEL.
 - DIMENSIONING AND TOLERANCING PER ANSI Y14.5, 1973.

1



MECL Logic Surface Mount

WHY SURFACE MOUNT?

Surface Mount Technology is now being utilized to offer answers to many problems that have been created in the use of insertion technology.

Limitations have been reached with insertion packages and PC board technology. Surface Mount Technology offers the opportunity to continue to advance the State-of-the-Art designs that cannot be accomplished with Insertion Technology.

Surface Mount Packages allow more optimum device performance with the smaller Surface Mount configuration. Internal lead lengths, parasitic capacitance and inductance that placed limitations on chip performance have been reduced.

The lower profile of Surface Mount Packages allows more boards to be utilized in a given amount of space. They are stacked closer together and utilize less total volume than insertion populated PC boards.

Printed circuit costs are lowered with the reduction of the number of board layers required. The elimination or reduction of the number of plated through holes in the board, contribute significantly to lower PC board prices.

Surface Mount assembly does not require the preparation of components that are common on insertion technology lines. Surface Mount components are sent directly to the assembly line, eliminating an intermediate step.

Automatic placement equipment is available that can place Surface Mount components at the rate of a few thousand per hour to hundreds of thousands of components per hour.

Surface Mount Technology is cost effective, allowing the manufacturer the opportunity to produce smaller units and offer increased functions with the same size product.

MECL AVAILABILITY IN SURFACE MOUNT

Motorola is now offering MECL 10K and MECL 10KH in the PLCC (Plastic Leaded Chip Carrier) packages.

MECL in PLCC may be ordered in conventional plastic rails or on Tape and Reel. Refer to the Tape and Reel section for ordering details.

TAPE AND REEL


Motorola has now added the convenience of Tape and Reel packaging for our growing family of standard Integrated Circuit products. The packaging fully conforms to

the latest EIA RS-481A specification. The antistatic embossed tape provides a secure cavity sealed with a peel-back cover tape.

GENERAL INFORMATION

- Reel Size 13 inch (330 mm) Suffix: R2
- Tape Width 16 mm
- Units/Reel 1000

MECHANICAL POLARIZATION



ORDERING INFORMATION

- Minimum Lot Size/Device Type = 3000 Pieces.
- No Partial Reel Counts Available.
- To order devices which are to be delivered in Tape and Reel, add the appropriate suffix to the device number being ordered.

EXAMPLE:

ORDERING CODE

MC10100FN
MC10100FNR2
MC10H100FN
MC10H100FNR2
MC12015D
MC12015DR2

SHIPMENT METHOD

Magazines (Rails)
13 inch Tape and Reel
Magazines (Rails)
13 inch Tape and Reel
Magazines (Rails)
13 inch Tape and Reel

DUAL-IN-LINE PACKAGE TO PLCC PIN CONVERSION DATA

The following tables give the equivalent I/O pinouts of Dual-In-Line (DIL) packages and Plastic Leaded Chip Carrier (PLCC) packages.

Conversion Tables

16 PIN DIL	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
20 PIN PLCC	2	3	4	5	7	8	9	10	12	13	14	15	17	18	19	20

20 PIN DIL	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
20 PIN PLCC	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20

24 PIN DIL	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24
28 PIN PLCC	2	3	4	5	6	7	9	10	11	12	13	14	16	17	18	19	20	21	23	24	25	26	27	28