

## PRIMO RANGE FRONT CUTTING PLIERS

NF E 73104 / ISO 5748 / DIN ISO 5748

### mechanics front cutting pliers

- Double induction treatment of cutting edges to cut hard wires max 200 kg/mm<sup>2</sup>.
- Axis offset towards cutting edges for maximum cutting demultiplication.
- Orange PVC sleeve with guards.

L1	1	*	O	w	7 g
160	117320	9	3	-	172
160	117325	4	1	C2	192



### Front cutter


- Double induction treatment of cutting edges to cut hard wires max 200 kg/mm<sup>2</sup>.
- Axis offset towards cutting edges for maximum cutting demultiplication.
- Orange PVC sleeve.

L1	1	*	O	w	7 g
190	115345	4	1	C3	420
220	115355	3	1	C4	520



## PRIMO RANGE UNIVERSAL PLIERS

NF 73-103/ ISO 5746/ DIN ISO 5746



L1	1	*	O	w	7 g
160	117200	4	6	-	172
160	117205	9	3	C2	192
180	117210	3	6	-	202
180	117215	8	3	C3	222
200	117220	2	6	-	277
200	117225	7	3	C4	287

- Double induction treatment of cutting edges to cut the hardest wires.
- Piano wire 200 kg/mm<sup>2</sup>.
- Orange PVC sleeve with guards.

\* For a full EAN, add the following before the code: 303254

**Bost**

Catalogue 2005