




# SBD Type :11EQS04

## FEATURES

- \* Miniature Size
- \* Low Forward Voltage Drop
- \* High Surge Capability
- \* 30volts trough 100volts Types Available
- \* 26mm and 52mm Inside Tape Spacing Package Available

## OUTLINE DRAWING



## Maximum Ratings

Approx Net Weight:0.17g

Rating	Symbol	11EQS04			Unit
Repetitive Peak Reverse Voltage	$V_{RRM}$	40			V
Non-repetitive Peak Reverse Voltage	$V_{RSM}$	45			V
Average Rectified Output Current	$I_O$	1.0	$T_a=25^{\circ}C$	Half Sine Wave Resistive Load	A
		1.0	$T_a=48^{\circ}C$		
RMS Forward Current	$I_{F(RMS)}$	1.57			A
Surge Forward Current	$I_{FSM}$	40	Half Sine Wave,1cycle,Non-repetitive		A
Operating JunctionTemperature Range	$T_{jw}$	- 40 to + 150			$^{\circ}C$
Storage Temperature Range	$T_{stg}$	- 40 to + 150			$^{\circ}C$

## Electrical • Thermal Characteristics

Characteristics	Symbol	Conditions	Min	Typ	Max	Unit
Peak Reverse Current	$I_{RM}$	$T_j= 25^{\circ}C, V_{RM}= V_{RRM}$	-	-	1	mA
Peak Forward Voltage	$V_{FM}$	$T_j= 25^{\circ}C, I_{FM}= 1 A$	-	-	0.55	V
Thermal Resistance(Junction to Ambient)	$R_{th(j-a)}$	Without Fin or P.C.Board	-	-	140	$^{\circ}C/W$
		P.C.Board mounted *	-	-	110	

\* :Print Lands = 5x5 mm,Both Sides

11EQS04 OUTLINE DRAWING (Dimensions in mm)

