



**FEATURES**

- Guard Ring Die Construction for Transient Protection
- Ideally Suited for Automatic Assembly
- Low Power Loss, High Efficiency
- Surge Overload Rating to 175A Peak
- For Use in Low Voltage, High Frequency Inverters, Free Wheeling, and Polarity Protection Application
- Plastic Material - UL Flammability Classification 94V-0

MECHANICAL DATA

- Case: Molded Plastic
- Terminals: Solder Plated Terminal Solderable per MIL-STD-202, Method 208
- Polarity: Cathode Band or Cathode Notch
- Approx. Weight: 0.21grams
- Marking: Type Number

DO-214AB(SMC)



Dimensions in inches and (millimeters)

Maximum Ratings and Electrical Characteristics

Single phase, half wave, 60Hz, resistive or inductive load.

For capacitive load, derate current by 20%.

Characteristic	Symbol	B520C	B530C	B540C	B550C	B560C	Unit
Peak Repetitive Reverse Voltage Working Peak Reverse Voltage DC Blocking Voltage	V_{RRM} V_{RWM} V_R	20	30	40	50	60	V
RMS Reverse Voltage	$V_{R(RMS)}$	14	21	28	35	42	V
Average Rectified Output Current @ $T_T = 90^{\circ}\text{C}$	I_O	5.0					A
Non-Repetitive Peak Forward Surge Current, 8.3 ms single half-sine-wave Superimposed on Rated Load (JEDEC method)	I_{FSM}	175					A
Forward Voltage @ $I_F = 5.0\text{A DC}$	V_{FM}	0.55			0.70		V
Peak Reverse Current @ $T_A = 25^{\circ}\text{C}$ at Rated DC Blocking Voltage @ $T_A = 100^{\circ}\text{C}$	I_{RM}	0.5 20					mA
Typical Junction Capacitance (Note 2)	C_j	300					pF
Typical Thermal Resistance, Junction to Terminal (Note 1)	$R_{\theta JT}$	10					K/W
Typical Thermal Resistance, Junction to Ambient	$R_{\theta JA}$	50					$^{\circ}\text{C/W}$
Operating Temperature Range	T_j	-55 to +125					$^{\circ}\text{C}$
Storage Temperature Range	T_{STG}	-55 to +150					$^{\circ}\text{C}$

Notes: 1. Thermal Resistance: Junction to terminal, unit mounted on PC board with 5.0 mm² (0.013 mm thick) copper pads as heat sink.
2. Measured at 1.0 MHz and applied reverse voltage of 4.0V DC.



TAYCHIPST

SURFACE MOUNT SCHOTTKY BARRIER RECTIFIER

B520C THRU B560C

20V-60V 5.0A




Fig. 1 Forward Current Derating Curve




Fig. 2 Typical Forward Characteristics




Fig. 3 Max Non-Repetitive Peak Fwd Surge Current




Fig. 4 Typical Junction Capacitance




Fig. 5 Typical Reverse Characteristics