



TAYCHIPST

SURFACE MOUNT SCHOTTKY BARRIER RECTIFIERS

SS32 THRU SS320
20V-200V 3.0A


FEATURES

- Plastic Package has Underwriters Laboratory Flammability Classification 94V-0
- Metal silicon junction, majority carrier conduction
- For surface mount applications
- Guard ring for overvoltage protection
- Low power loss, high efficiency
- High current capability, Low forward voltage drop
- High surge capability
- For use in low voltage, high frequency inverters, free wheeling, and polarity protection applications
- High temperature soldering guaranteed : 250 °C/10 seconds at terminals

MECHANICAL DATA

- Case : JEDEC SMB(DO-214AC) molded plastic body
- Terminals : Solder Plate, solderable per MIL-STD-750, Method 2026
- Polarity : Color band denotes cathode end
- Weight : 0.003 ounce, 0.093 gram

DO-214AC(SMA)



Dimensions in inches and (millimeters)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Rating at 25 °C ambient temperature unless otherwise specified.

Single phase, half wave, 60 Hz, resistive or inductive load.

For capacitive load, derate current by 20%

Type Number	Symbol	SS 32	SS 33	SS 34	SS 35	SS 36	SS 39	SS 310	SS 315	SS 320	Unit	
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	20	30	40	50	60	90	100	150	200	V	
Maximum RMS Voltage	V_{RMS}	14	21	28	35	42	63	70	105	140	V	
Maximum DC Blocking Voltage	V_{DC}	20	30	40	50	60	90	100	150	200	V	
Maximum Average Forward Rectified Current	$I_{F(AV)}$	3.0									A	
Peak Forward Surge Current, 8.3 ms Single Half Sine-wave Superimposed on Rated Load (JEDEC method)	I_{FSM}	100			70						A	
Maximum Instantaneous Forward Voltage (Note 1) @ 3.0A	V_F	$T_A=25^\circ C$ 0.5		0.75		0.85		0.95		V		
		$T_A=100^\circ C$ 0.4		0.65		0.70		0.80				
Maximum Reverse Current @ Rated VR	I_R	$T_A=25^\circ C$ 0.5			0.1						mA	
		$T_A=100^\circ C$ 10			5			-				
		$T_A=125^\circ C$ -			0.5							
Typical Thermal Resistance	$R_{\theta JL}$ $R_{\theta JA}$	17					55					$^\circ C/W$
Operating Temperature Range	T_J	- 55 to + 125				- 55 to + 150						$^\circ C$
Storage Temperature Range	T_{STG}	- 55 to + 150										$^\circ C$

Note 1: Pluse Test with PW=300 usec, 1% Duty Cycle



RATINGS AND CHARACTERISTIC CURVES

SS32 THRU SS320

FIG.1 FORWARD CURRENT DERATING CURVE




FIG. 2 MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




FIG. 3 TYPICAL FORWARD CHARACTERISTICS




FIG. 4 TYPICAL REVERSE CHARACTERISTICS




FIG. 5 TYPICAL JUNCTION CAPACITANCE




FIG. 6 TYPICAL TRANSIENT THERMAL IMPEDANCE

