



Voltage regulator double Diodes

BZB784Series


FEATURES

- Total power dissipation: max. 350 mW
- Approx. 5% V_z tolerance
- Working voltage range: nom. 2.4 to 15 V (E24 range).



APPLICATIONS

- General regulation functions
- ESD and surge protection



ORDERING INFORMATION

Type No.	Marking	Package Code
BZB784Series	See Table on page2	SOT-323

MARKING

TYPE NUMBER	MARKING CODE	TYPE NUMBER	MARKING CODE	TYPE NUMBER	MARKING CODE	TYPE NUMBER	MARKING CODE
BZB784-C2V4	91	BZB784-C3V9	96	BZB784-C6V2	9B	BZB784-C10	9G
BZB784-C2V7	92	BZB784-C4V3	97	BZB784-C6V8	9C	BZB784-C11	9H
BZB784-C3V0	93	BZB784-C4V7	98	BZB784-C7V5	9D	BZB784-C12	9J
BZB784-C3V3	94	BZB784-C5V1	99	BZB784-C8V2	9E	BZB784-C13	9K
BZB784-C3V6	95	BZB784-C5V6	9A	BZB784-C9V1	9F	BZB784-C15	9L



Voltage regulator double Diodes

BZB784Series

MAXIMUM RATING @ Ta=25°C unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN.	MAX.	UNIT
I _F	continuous forward current		–	200	mA
I _{ZSM}	non-repetitive peak reverse current	t _p = 100 μs; square wave; T _{amb} = 25 °C; prior to surge	see Table 1		
P _{tot}	total power dissipation; note 1	T _{amb} = 25 °C; 2 diodes loaded	–	350	mW
		T _{amb} = 25 °C; 1 diode loaded	–	180	mW
P _{ZSM}	non-repetitive peak reverse dissipation	t _p = 100 μs; square wave; T _{amb} = 25 °C; prior to surge	–	40	W
T _{stg}	storage temperature		–65	+150	°C
T _j	junction temperature		–	150	°C

Note:

1. Device mounted on an FR4 printed-circuit board.

SYMBOL	PARAMETER	CONDITIONS	VALUE	UNIT
R _{th j-s}	thermal resistance from junction to soldering point	2 diodes loaded; note 1	140	K/W
		1 diode loaded; note 1	265	K/W
R _{th j-a}	thermal resistance from junction to ambient	2 diodes loaded; note 2	355	K/W
		1 diode loaded; note 2	680	K/W

Notes

1. Solder points on cathode tabs.
2. Device mounted on a FR4 printed-circuit board.



Voltage regulator double Diodes

BZB784Series

ELECTRICAL CHARACTERISTICS @ Ta=25°C unless otherwise specified




SYMBOL	PARAMETER	CONDITIONS	MAX.	UNIT
V_F	forward voltage	$I_F = 10 \text{ mA}$; see Fig.2	0.9	V
I_R	reverse current			
	BZB784-C2V4	$V_R = 1 \text{ V}$	50	μA
	BZB784-C2V7	$V_R = 1 \text{ V}$	20	μA
	BZB784-C3V0	$V_R = 1 \text{ V}$	10	μA
	BZB784-C3V3	$V_R = 1 \text{ V}$	5	μA
	BZB784-C3V6	$V_R = 1 \text{ V}$	5	μA
	BZB784-C3V9	$V_R = 1 \text{ V}$	3	μA
	BZB784-C4V3	$V_R = 1 \text{ V}$	3	μA
	BZB784-C4V7	$V_R = 2 \text{ V}$	3	μA
	BZB784-C5V1	$V_R = 2 \text{ V}$	2	μA
	BZB784-C5V6	$V_R = 2 \text{ V}$	1	μA
	BZB784-C6V2	$V_R = 4 \text{ V}$	3	μA
	BZB784-C6V8	$V_R = 4 \text{ V}$	2	μA
	BZB784-C7V5	$V_R = 5 \text{ V}$	1	μA
	BZB784-C8V2	$V_R = 5 \text{ V}$	700	nA
	BZB784-C9V1	$V_R = 6 \text{ V}$	500	nA
	BZB784-C10	$V_R = 7 \text{ V}$	200	nA
	BZB784-C11	$V_R = 8 \text{ V}$	100	nA
	BZB784-C12	$V_R = 8 \text{ V}$	100	nA
	BZB784-C13	$V_R = 8 \text{ V}$	100	nA
	BZB784-C15	$V_R = 10.5 \text{ V}$	50	nA

BZB784-C XXX	WORKING VOLTAGE V_Z (V) at $I_Z = 5 \text{ mA}$		DIFFERENTIAL RESISTANCE r_{dif} (Ω)				TEMP. COEFFICIENT S_Z (mV/K) at $I_{Ztest} = 5 \text{ mA}$ (see Figs 3 and 4)	DIODE CAP. C_d (pF) at $f = 1 \text{ MHz}$; $V_R = 0 \text{ V}$	NON-REPETITIVE PEAK REVERSE CURRENT I_{ZSM} (A) at $t_p = 100 \mu\text{s}$; $T_{amb} = 25 \text{ }^\circ\text{C}$
	Tot. $\approx 5\%$		at $I_Z = 1 \text{ mA}$		at $I_Z = 5 \text{ mA}$				
	MIN.	MAX.	TYP.	MAX.	TYP.	MAX.			
2V4	2.2	2.6	275	600	70	100	-1.3	450	6.0
2V7	2.5	2.9	300	600	75	100	-1.4	450	6.0
3V0	2.8	3.2	325	600	80	95	-1.6	450	6.0
3V3	3.1	3.5	350	600	85	95	-1.8	450	6.0
3V6	3.4	3.8	375	600	85	90	-1.9	450	6.0
3V9	3.7	4.1	400	600	85	90	-1.9	450	6.0
4V3	4.0	4.6	410	600	80	90	-1.7	450	6.0
4V7	4.4	5.0	425	500	50	80	-1.2	300	6.0
5V1	4.8	5.4	400	480	40	60	-0.5	300	6.0
5V6	5.2	6.0	80	400	15	40	1.0	300	6.0
6V2	5.8	6.6	40	150	6	10	2.2	200	6.0
6V8	6.4	7.2	30	80	6	15	3.0	200	6.0
7V5	7.0	7.9	30	80	6	15	3.6	150	4.0
8V2	7.7	8.7	40	80	6	15	4.3	150	4.0
9V1	8.5	9.6	40	100	6	15	5.2	150	3.0
10	9.4	10.6	50	150	8	20	6.0	90	3.0
11	10.4	11.6	50	150	10	20	6.9	90	2.5
12	11.4	12.7	50	150	10	25	7.9	85	2.5
13	12.4	14.1	50	170	10	30	8.8	80	2.5
15	13.8	15.6	50	200	10	30	10.7	75	2.0

Voltage regulator double Diodes

BZB784Series

TYPICAL CHARACTERISTICS @ Ta=25°C unless otherwise specified




Voltage regulator double Diodes

BZB784Series


PACKAGE OUTLINE

Plastic surface mounted package

SOT-23



SOLDERING FOOTPRINT



PACKAGE INFORMATION

Device	Package	Shipping
BZB784-C series	SOT-323	3000/Tape&Reel