

10kV 300mA HIGH VOLTAGE DIODE

CL03-10F is high reliability resin molded type high voltage diode in small size package which is sealed a multilayered mesa type silicon chip by epoxy resin.

Features

- High speed switching
- Low VF
- High surge resistivity for CRT discharge
- High reliability design
- Ultra small package


Applications

- X light Power supply
- Laser
- Voltage doubler circuit
- Microwave emission power

Maximum Ratings and Characteristics

- Absolute Maximum Ratings

Outline Drawings : mm



Cathode Mark

Type	Mark
CL03-10F	

Items	Symbols	Condition	CL03-10F	Units
Repetitive Peak Reverse Voltage	V_{RRM}		10	kV
Average Output Current	I_o	Ta=25°C, Resistive Load	300	mA
Surge Current	I_{FSM}		15	A _{peak}
Junction Temperature	T_j		155	°C
Allowable Operation Case Temperature	T_c		125	°C
Storage Temperature	T_{stg}		-40 to +155	°C

Electrical Characteristics (Ta=25°C Unless otherwise specified)

Items	Symbols	Conditions	CL03-10F	Units
Maximum Forward Voltage Drop	V_F	at 25°C, $I_F=I_{F(AV)}$	25	V
Maximum Reverse Current	IR1	at 25°C, $V_R=V_{RRM}$	5.0	μA
	IR2	at 100°C, $V_R=V_{RRM}$	50	μA
Maximum Reverse Recovery Time	T_{rr}	at 25°C	80	nS
Junction Capacitance	C_j	at 25°C, $V_R=0V, f=1MHz$	15	pF