



Dual surface mount switching diode


DAN202U

FEATURES

- For types of packaging are available.
- High speed switching.
- Suitable for high packing density layout.
- High reliability.



Lead-free



APPLICATIONS

- For general purpose switching applications.

ORDERING INFORMATION

Type No.	Marking	Package Code
DAN202U	N	SOT-323

MAXIMUM RATING @ Ta=25°C unless otherwise specified

Parameter	Symbol	Limits	Unit
Non-Repetitive Peak reverse voltage	V_{RM}	80	V
Diode reverse voltage	V_R	80	V
Forward continuous Current (peak)	I_F	300	mA
Average forward current	I_O	100	mA
Power Dissipation	P_d	200	mW
Junction temperature	T_j	150	°C
Storage temperature range	T_{stg}	-65 to +150	°C



Dual surface mount switching diode

DAN202U

ELECTRICAL CHARACTERISTICS @ Ta=25°C unless otherwise specified

Parameter	Symbol	Test conditions	MIN	MAX	UNIT
Reverse breakdown voltage	$V_{(BR)R}$	$I_R = 100\mu A$	80		V
Reverse voltage leakage current	I_R	$V_R = 70V$		0.1	μA
Forward voltage	V_F	$I_F = 100mA$		1.2	V
Diode capacitance	C_D	$V_R = 6V$ $f = 1MHz$		3.5	pF
Reverse recovery time	t_{rr}	$V_R = 6V, I_F = 5mA$		4	nS

TYPICAL CHARACTERISTICS @ Ta=25°C unless otherwise specified




Fig.1 Power attenuation curve




Fig.2 Forward characteristics (P Type)




Fig.3 Reverse characteristics (P Type)




Fig.4 Forward characteristics (N Type)




Fig.5 Reverse characteristics (N Type)




Fig.6 Capacitance between terminals characteristics




Dual surface mount switching diode

DAN202U


PACKAGE OUTLINE

Plastic surface mounted package

SOT-323



SOLDERING FOOTPRINT



PACKAGE INFORMATION

Device	Package	Shipping
DAN202U	SOT-323	3000/Tape&Reel