

Dual surface mount switching diode

DAP202

FEATURES


- High speed.
- High reliability.
- Suitable for high packing density layout.



Lead-free

APPLICATIONS

- Ultra high speed switching.
- Silicon epitaxial planar.



ORDERING INFORMATION

Type No.	Marking	Package Code
DAP202	P	SOT-23

MAXIMUM RATING @ Ta=25°C unless otherwise specified

Parameter	Symbol	Limits	Unit
Non-Repetitive Peak reverse voltage	V_{RM}	80	V
DC Reverse Voltage	V_R	80	V
Forward continuous Current(Single)	I_{FM}	300	mA
Average rectified forward current(Single)	I_O	100	mA
Surge Current (t=1.0us)	I_{surge}	4	A
Power Dissipation	P_d	200	mW
Junction temperature	T_j	150	°C
Storage temperature range	T_{stg}	-55 to +150	°C


Dual surface mount switching diode

DAP202


ELECTRICAL CHARACTERISTICS @ $T_a=25^\circ\text{C}$ unless otherwise specified

Parameter	Symbol	Test conditions	MIN	MAX	UNIT
Reverse voltage leakage current	I_R	$V_R=70\text{V}$		0.1	μA
Forward voltage	V_F	$I_F=100\text{mA}$		1.2	V
Total capacitance	C_T	$V_R=6\text{V}, f=1\text{MHz}$		3.5	pF
Reverse recovery time	t_{rr}	$I_F=5\text{mA}, V_R=6\text{V}, R_L=50\Omega$		4	ns


TYPICAL CHARACTERISTICS @ $T_a=25^\circ\text{C}$ unless otherwise specified



Power attenuation curve



Forward characteristics



Reverse characteristics


Dual surface mount switching diode

DAP202


PACKAGE OUTLINE

Plastic surface mounted package

SOT-23



SOLDERING FOOTPRINT



PACKAGE INFORMATION

Device	Package	Shipping
DAP202	SOT-23	3000/Tape&Reel