

Silicon Bridge Rectifiers

GBU6005--GBU610

FEATURES

- Ideal for printed circuit board
- Reliable low cost construction utilizing molded plastic technique
- Plastic material has U/L flammability classification 94V-O
- Mounting position: Any
- Glass passivated chip junctions



Lead-free

Maximum Ratings (@TA = 25°C unless otherwise specified)

Characteristic	Symbol	GBU 6005	GBU 601	GBU 602	GBU 604	GBU 605	GBU 606	GBU 608	GBU 610	UNITS
Maximum recurrent peak reverse voltage	V_{RRM}	50	100	200	400	500	600	800	1000	V
Maximum RMS voltage	V_{RMS}	35	70	140	280	350	420	560	700	V
Maximum DC blocking voltage	V_{DC}	50	100	200	400	500	600	800	1000	V
50Hz sine wave, R-load Without heat sink Ta=25°C 50Hz sine wave, R-load With heat sink Tc=50°C	$I_{F(AV)}$	2.3 6.0								A
Peak forward surge current 8.3ms single half-sine-wave superimposed on rated load	I_{FSM}	175								A

Thermal Characteristics

Characteristic	Symbol	GBU 6005	GBU 601	GBU 602	GBU 604	GBU 605	GBU 606	GBU 608	GBU 610	UNITS
Typical junction capacitance per element(note 3)	C_J	211					94			p F
Typical thermal resistance(note1) (note2)	$R_{\theta JA}$ $R_{\theta JC}$	7.4 2.2								°C/W
Operating junction temperature range	T_J	- 55 ---- + 150								°C
Storage temperature range	T_{STG}	- 55 ---- + 150								°C

Electrical Characteristics (@TA = 25°C unless otherwise specified)

Characteristic	Symbol	GBU 6005	GBU 601	GBU 602	GBU 604	GBU 605	GBU 606	GBU 608	GBU 610	UNITS
Maximum instantaneous forward voltage @3.0A	V_F	1.0								V
Maximum reverse current @TA=25 °C at rated DC blocking voltage @TA=125°C	I_R	5.0 0.5								μ A mA

NOTE: 1. Unit case mounted on 2.6x1.4x0.06" thick (6.5x3.5x0.15cm) Al. Plate.

2. Recommended mounting position is to bolt down on heatsink with silicone thermal compound f or maximum heat transfer with #6 screws


3. Measured at 1.0 MHz and applied reverse voltage of 4.0 volts.



Silicon Bridge Rectifiers

GBU6005--GBU610

PACKAGE OUTLINE DIMENSIONS



PACKAGE INFORMATION

Device	Package	Shipping
GBU6005--GBU610	GBU	500 Units/Box



Silicon Bridge Rectifiers

GBU6005--GBU610

FIG.1 – DERATING CURVE FOR OUTPUT RECTIFIED CURRENT




FIG.2 – TYPICAL FORWARD CHARACTERISTIC




FIG.3 – MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG.4 – TYPICAL REVERSE CHARACTERISTIC




FIG.5 – TYPICAL JUNCTION CAPACITANCE PER LEG




FIG.6 – TYPICAL TRANSIENT THERMAL IMPEDANCE

