

450mA 12kV HIGH VOLTAGE DIODES

Finds use in applications such as Monitors,
Static electricity dust collectors,Laser power
supplies,ect..

Features

- High speed switching
- High Current
- High surge resisitivity for CRT discharge
- High reliability design
- High Voltage


Applications

- X light Power supply
- Laser
- Voltage doubler circuit
- Microwave emission power

Maximum Ratings and Characteristics

- Absolute Maximum Ratings

Outline Drawings : mm



Cathode Mark

Type	Mark
HV500F12	

Items	Symbols	Condition	HV500F12	Units
Repetitive Peak Reverse Voltage	V_{RRM}		12	kV
Average Output Current	I_O	$T_a=25^{\circ}\text{C}$, Resistive Load	450	mA
Surge Current	I_{FSM}		30	A peak
Junction Temperature	T_J		120	$^{\circ}\text{C}$
Allowable Operation Case Temperature	T_c		120	$^{\circ}\text{C}$
Storage Temperature	T_{stg}		-40 to +120	$^{\circ}\text{C}$

- Electrical Characteristics ($T_a=25^{\circ}\text{C}$ Unless otherwise specified)

Items	Symbols	Conditions	HV500F12	Units
Maximum Forward Voltage Drop	V_F	at 25°C , $I_F = I_{F(AV)}$	18	V
Maximum Reverse Current	I_{R1}	at 25°C , $V_R = V_{RRM}$	5.0	μA
	I_{R2}	at 100°C , $V_R = V_{RRM}$	50	μA
Maximum Reverse Recovery Time	T_{rr}	at 25°C	100	nS
Junction Capacitance	C_j	at 25°C , $V_R=0\text{V}$, $f=1\text{MHz}$	--	pF