

Surface Mount Rectifiers

US3AB--US3MB

FEATURES

- Plastic package has underwriters laboratories flammability classification 94V-0
- For surface mount applications
- Low profile package
- Easy pick and place
- Ultrafast recovery times for high efficiency
- Low forward voltage, low power loss
- Built-in strain relief, ideal for automated placement
- High temperature soldering:250°C/10 seconds on terminals



Lead-free



MECHANICAL DATA

- Case: JEDEC DO-214AA,molded plastic body over passivated chip
- Terminals: Solder Plated, solderable per MIL-STD-750,Method 2026
- Polarity: Color band denotes cathode end
- Weight: 0.003 ounces, 0.093 gram

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified


		US3AB	US3BB	US3DB	US3GB	US3JB	US3KB	US3MB	UNITS
Device marking code		US3AB	US3BB	US3DB	US3GB	US3JB	US3KB	US3MB	
Maximum recurrent peak reverse voltage	V _{RRM}	50	100	200	400	600	800	1000	V
Maximum RMS voltage	V _{RWS}	35	70	140	280	420	560	700	V
Maximum DC blocking voltage	V _{DC}	50	100	200	400	600	800	1000	V
Maximum average forward rectified current at T _L =110℃	I _{F(AV)}	3.0							A
Peak forward surge current 8.3ms single half sine-wave super imposed on rated load (JEDEC Method)	I _{FSM}	100							A
Maximum instantaneous forward voltage at 3.0A	V _F	1.0				1.7			V
Maximum DC reverse current @T _A =25℃ at rated DC blocking voltage @T _A =125℃	I _R	10.0 500							μ A
Maximum reverse recovery time at I _F =0.5A I _R =1.0A I _{rr} =0.25A	t _{rr}	50				75			ns
Typical junction capacitance at 4.0V,1MHZ	C _J	70				50			p F
Maximum thermal resistance (NOTE1)	R _{θJA}	25							℃/W
Operating temperature range	T _J	-55----+150							℃
Storage temperature range	T _{STG}	-55----+150							℃

NOTE: 1.P.C.B.mounted on 0.2X0.2"(5.0X5.0mm) copper pad area


Surface Mount Rectifiers

US3AB--US3MB

PACKAGE OUTLINE DIMENSIONS



SOLDERING FOOTPRINT



Unit : mm

PACKAGE INFORMATION

Device	Package	Shipping
US3AB--US3MB	DO-214AA(SMB)	3000/Tape&Reel

Surface Mount Rectifiers

US3AB--US3MB

FIG.1 – FORWARD CURRENT DERATING CURVE






FIG.3 – TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




INSTANTANEOUS FORWARD VOLTAGE(V)

FIG.5 – TYPICAL JUNCTION CAPACITANCE




REVERSE VOLTAGE(V)

FIG.2 – MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




NUMBER OF CYCLES AT 60HZ

FIG.4 – TYPICAL REVERSE CHARACTERISTICS



PERCENT OF RATED PEAK REVERSE VOLTAGE.(%)

FIG.6 – TYPICAL TRANSIENT THERMAL IMPEDANCE



Tj PULSE DURATION,