

PRODUCT SUMMARY			
V_{DS} (V)	$r_{DS(on)}$ (Ω)	I_D (A) ^{a, e}	Q_g (Typ)
25	0.0086 @ $V_{GS} = 10$ V	62	18.5 nC
	0.012 @ $V_{GS} = 4.5$ V	52	



FEATURES

- TrenchFET® Power MOSFET
- 100% R_g Tested
- RoHS Compliant



APPLICATIONS

- DC/DC Conversion, High-Side
– Desktop PC



Ordering Information: SUD50N025-09BP—E3 (Lead (Pb)-free)

N-Channel MOSFET

ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$ UNLESS OTHERWISE NOTED)				
Parameter		Symbol	Limit	Unit
Drain-Source Voltage		V_{DS}	25	V
Gate-Source Voltage		V_{GS}	± 20	
Continuous Drain Current ($T_J = 175^\circ\text{C}$)	$T_C = 25^\circ\text{C}$	I_D	62 ^e	A
	$T_C = 70^\circ\text{C}$		51 ^e	
	$T_A = 25^\circ\text{C}$		26 ^{b, c}	
	$T_A = 70^\circ\text{C}$		22 ^{b, c}	
Pulsed Drain Current		I_{DM}	100	
Continuous Source-Drain Diode Current	$T_C = 25^\circ\text{C}$	I_S	37	
	$T_A = 25^\circ\text{C}$		6.7 ^{b, c}	
Avalanche Current Pulse		I_{AS}	28	
Single Pulse Avalanche Energy		E_{AS}	39.2	mJ
Maximum Power Dissipation	$T_C = 25^\circ\text{C}$	P_D	55	W
	$T_C = 70^\circ\text{C}$		39	
	$T_A = 25^\circ\text{C}$		10 ^{b, c}	
	$T_A = 70^\circ\text{C}$		7 ^{b, c}	
Operating Junction and Storage Temperature Range		T_J, T_{stg}	-55 to 175	$^\circ\text{C}$

THERMAL RESISTANCE RATINGS					
Parameter		Symbol	Typical	Maximum	Unit
Maximum Junction-to-Ambient ^{b, d}	$t \leq 10$ sec	R_{thJA}	12	15	$^\circ\text{C/W}$
Maximum Junction-to-Case	Steady State	R_{thJC}	2.2	2.7	

Notes:

- Based on $T_C = 25^\circ\text{C}$.
- Surface mounted on 1" x 1" FR4 board.
- $t = 10$ sec
- Maximum under steady state conditions is 50°C/W .
- Calculated based on maximum junction temperature. Package limitation current is 50 A.

SPECIFICATIONS (T_J = 25 °C UNLESS OTHERWISE NOTED)						
Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
Static						
Drain-Source Breakdown Voltage	V _{DS}	V _{GS} = 0 V, I _D = 250 μA	25			V
V _{DS} Temperature Coefficient	ΔV _{DS} /T _J	I _D = 250 μA		20		mV/°C
V _{GS(th)} Temperature Coefficient	ΔV _{GS(th)} /T _J			-6.3		
Gate-Source Threshold Voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D = 250 μA	1.2		2.4	V
Gate-Source Leakage	I _{GSS}	V _{DS} = 0 V, V _{GS} = ±20 V			±100	nA
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} = 25 V, V _{GS} = 0 V			1	μA
		V _{DS} = 25 V, V _{GS} = 0 V, T _J = 55°C			10	
On-State Drain Current ^a	I _{D(on)}	V _{DS} ≥ 5 V, V _{GS} = 10 V	100			A
Drain-Source On-State Resistance ^a	r _{DS(on)}	V _{GS} = 10 V, I _D = 26 A		0.007	0.0086	Ω
		V _{GS} = 4.5 V, I _D = 22 A		0.0096	0.012	
Forward Transconductance ^a	g _{fs}	V _{DS} = 15 V, I _D = 26 A		46		S
Dynamic^b						
Input Capacitance	C _{iss}	V _{DS} = 12 V, V _{GS} = 0 V, f = 1 MHz		2020		pF
Output Capacitance	C _{oss}			485		
Reverse Transfer Capacitance	C _{rss}			245		
Total Gate Charge	Q _g	V _{DS} = 12 V, V _{GS} = 10 V, I _D = 26 A		38	57	nC
		V _{DS} = 12 V, V _{GS} = 4.5 V, I _D = 26 A		18.5	28	
Gate-Source Charge	Q _{gs}	V _{DS} = 12 V, V _{GS} = 4.5 V, I _D = 26 A		7		nC
Gate-Drain Charge	Q _{gd}			6.5		
Gate Resistance	R _g		f = 1 MHz		0.9	
Turn-On Delay Time	t _{d(on)}	V _{DD} = 12 V, R _L = 0.54 Ω I _D ≅ 22 A, V _{GEN} = 10 V, R _g = 1 Ω		9	14	ns
Rise Time	t _r			8	12	
Turn-Off Delay Time	t _{d(off)}			20	30	
Fall Time	t _f			8	12	
Turn-On Delay Time	t _{d(on)}	V _{DD} = 12 V, R _L = 0.54 Ω I _D ≅ 22 A, V _{GEN} = 4.5 V, R _g = 1 Ω		17	26	
Rise Time	t _r			15	23	
Turn-Off Delay Time	t _{d(off)}			17	26	
Fall Time	t _f			8	12	
Drain-Source Body Diode Characteristics						
Continuous Source-Drain Diode Current	I _S	T _C = 25°C			37	A
Pulse Diode Forward Current ^a	I _{SM}				100	
Body Diode Voltage	V _{SD}	I _S = 6.7 A		0.9	1.5	V
Body Diode Reverse Recovery Time	t _{rr}	I _F = 6.7 A, di/dt = 100 A/μs, T _J = 25°C		26	40	ns
Body Diode Reverse Recovery Charge	Q _{rr}			16	24	nC
Reverse Recovery Fall Time	t _a			12		ns
Reverse Recovery Rise Time	t _b			14		


Notes

- a. Pulse test; pulse width ≤ 300 μs, duty cycle ≤ 2%.
 b. Guaranteed by design, not subject to production testing.


Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

TYPICAL CHARACTERISTICS (25°C UNLESS NOTED)


Output Characteristics




Transfer Characteristics




On-Resistance vs. Drain Current




Capacitance








Gate Charge






On-Resistance vs. Junction Temperature




TYPICAL CHARACTERISTICS (25°C UNLESS NOTED)



TYPICAL CHARACTERISTICS (25°C UNLESS NOTED)



TYPICAL CHARACTERISTICS (25°C UNLESS NOTED)



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

freestyle Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "freestyle"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

freestyle makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, freestyle disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on freestyle's knowledge of typical requirements that are often placed on freestyle products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify freestyle's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, freestyle products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the freestyle product could result in personal injury or death. Customers using or selling freestyle products not expressly indicated for use in such applications do so at their own risk and agree to fully indemnify and hold freestyle and its distributors harmless from and against any and all claims, liabilities, expenses and damages arising or resulting in connection with such use or sale, including attorneys fees, even if such claim alleges that freestyle may

Material Category Policy

freestyle Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.

Please note that some freestyle documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.