



P - Channel Logic Level MOSFET

These miniature surface mount MOSFETs utilize High Cell Density process. Low $r_{DS(on)}$ assures minimal power loss and conserves energy, making this device ideal for use in power management circuitry. Typical applications are voltage control small signal switch, power management in portable and battery-powered products and most low current high side switch.

- Low $r_{DS(on)}$ Provides Higher Efficiency and Extends Battery Life
- Fast Switch
- Low Gate Charge
- High Saturation Current
- Miniature SOT-23 Surface Mount Package Saves Board Space



PRODUCT SUMMARY		
V_{DS} (V)	$r_{DS(on)}$ (Ω)	I_D (A)
-60	10 @ $V_{GS} = -10$ V	-0.2
	20 @ $V_{GS} = -4.5$ V	-0.12

ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$ UNLESS OTHERWISE NOTED)				
Parameter		Symbol	Maximum	Units
Drain-Source Voltage		V_{DS}	-60	V
Gate-Source Voltage		V_{GS}	± 20	
Continuous Drain Current ^a	$T_A = 25^\circ\text{C}$	I_D	± 0.12	A
	$T_A = 70^\circ\text{C}$		± 0.09	
Pulsed Drain Current ^b		I_{DM}	± 1	
Continuous Source Current (Diode Conduction) ^a		I_S	0.24	A
Power Dissipation ^a	$T_A = 25^\circ\text{C}$	P_D	0.36	W
	$T_A = 70^\circ\text{C}$		0.29	
Operating Junction and Storage Temperature Range		T_J, T_{stg}	-55 to 150	$^\circ\text{C}$

THERMAL RESISTANCE RATINGS				
Parameter		Symbol	Maximum	Units
Maximum Junction-to-Ambient ^a	$t \leq 5$ sec	R_{THJA}	350	$^\circ\text{C}/\text{W}$
	Steady-State		400	

Notes

- a. Surface Mounted on 1" x 1" FR4 Board.
- b. Pulse width limited by maximum junction temperature

SPECIFICATIONS ($T_A = 25^\circ\text{C}$ UNLESS OTHERWISE NOTED)						
Parameter	Symbol	Test Conditions	Limits			Unit
			Min	Typ	Max	
Switch Off Characteristics						
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	$V_{GS} = 0\text{ V}, I_D = -10\ \mu\text{A}$	-60			
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS} = -48\text{ V}, V_{GS} = 0\text{ V}$			-1	μA
		$V_{DS} = -48\text{ V}, V_{GS} = 0\text{ V}, T_J = 55^\circ\text{C}$			-150	
Gate-Body Leakage	I_{GSS}	$V_{DS} = 0\text{ V}, V_{GS} = \pm 20\text{ V}$			± 10	nA
Switch On Characteristics						
Gate-Threshold Voltage	$V_{GS(th)}$	$V_{DS} = V_{GS}, I_D = 1\text{ mA}$	-1.0	-1.7	-3.5	V
On-State Drain Current ^A	$I_{D(on)}$	$V_{DS} = -5\text{ V}, V_{GS} = -4.5\text{ V}$	-0.6			A
Drain-Source On-Resistance ^A	$r_{DS(on)}$	$V_{GS} = -10\text{ V}, I_D = -0.5\text{ A}$		1	10	Ω
		$V_{GS} = -10\text{ V}, I_D = -0.5\text{ A}, T_J = 55^\circ\text{C}$		1.5	12	
		$V_{GS} = -4.5\text{ V}, I_D = -0.25\text{ A}$		1.3	20	
Forward Transconductance ^A	g_{fs}	$V_{DS} = -5\text{ V}, I_D = -1.1\text{ A}$	75	435		mS
Diode Forward Voltage	V_{SD}	$I_S = 0.4\text{ A}, V_{GS} = 0\text{ V}$		-0.80	-1.5	V
Dynamic^b						
Total Gate Charge	Q_g	$V_{DS} = -48\text{ V}, V_{GS} = -10\text{ V},$ $I_D = -0.5\text{ A}$		1.8	2.5	nC
Gate-Source Charge	Q_{gs}			0.3		
Gate-Drain Charge	Q_{gd}			0.4		
Switching						
Turn-On Delay Time	$t_{d(on)}$	$V_{DS} = -25\text{ V}, I_D = -0.5\text{ A},$ $R_G = 6\ \Omega, V_{GEN} = -10\text{ V}$		2.7	5.5	ns
Rise Time	t_r			6.8	13	
Turn-Off Delay Time	$t_{d(off)}$			10	16	
Fall-Time	t_f			7.8	16	

Notes

- Pulse test: $PW \leq 300\ \mu\text{s}$ duty cycle $\leq 2\%$.
- Guaranteed by design, not subject to production testing.

FREESCALE reserves the right to make changes without further notice to any products herein. freescale makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does freescale assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in freescale data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. freescale does not convey any license under its patent rights nor the rights of others. freescale products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the APL product could create a situation where personal injury or death may occur. Should Buyer purchase or use freescale products for any such unintended or unauthorized application, Buyer shall indemnify and hold freescale and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that freescale was negligent regarding the design or manufacture of the part. APL is an Equal Opportunity/Affirmative Action Employer.

Typical Electrical Characteristics




Figure 1. On-Region Characteristics




Figure 2. On-Resistance Variation with Drain Current and Gate Voltage




Figure 3. On-Resistance Variation with Temperature




Figure 4. On-Resistance Variation with Gate to Source Voltage




Figure 5. Transfer Characteristics




Figure 6. Body Diode Forward Voltage Variation with Source Current and Temperature

Typical Electrical Characteristics




Figure 7. Gate Charge Characteristics.




Figure 8. Capacitance Characteristics.




Figure 9. Capacitance Characteristic




Figure 10. Gate Charge Characteristic

Normalized Thermal Transient Impedance, Junction to Ambient





Figure 11. Transient Thermal Response Curve

Package Information



DIM.	MILLIMETERS		
	MIN	NOM	MAX
A	0.935	0.95	1.10
A1	0.01	---	0.10
A2	0.85	0.90	0.925
b	0.30	0.40	0.50
c	0.10	0.15	0.25
D	2.70	2.90	3.10
E	2.60	2.80	3.00
E1	1.40	1.60	1.80
e	0.95 BSC		
e1	1.90 BSC		
L	0.30	0.40	0.60
L1	0.60REF		
L2	0.25BSC		
R	0.10	---	---
θ	0°	4°	8°
θ1	7°NOM		

