



## Blue Shower® II

# General Purpose Degreaser 1667

Introduction

Modeled after Techspray's popular Blue Shower® 1657, Blue Shower® II was developed for general cleaning and degreasing. Non-flammable and safe on plastics, Blue Shower® II is the standard for precision cleaning of polar and non-polar soils, including hand oils, solder oils, greases, silicone, fluxes, and similar soils. Excellent for tape head cleaning and general degreasing.

Features / Benefits
Non-Flammable
Rapidly Evaporating
Safe on Most Plastics
Zero Residue
Low Ozone Depletion Potential
Non-Corrosive
Replacement for CFC-113
Replacement for HCFC-141b

**EPA SNAP Approved** 

Physical Properties		
Boiling Point 58°C / 136°F		
Flash Point (TCC)	None	
Evaporation Rate	>1	
Surface Tension	0.52 (TCE=1)	
Kauri-Butanol (KB Value)	40	

### **Chemical Components**

3,3-Dichloro-1,1,1,2,2-pentafluoropropane (422-56-0)	32-37%-Aerosol 40-45%-Bulk
1,3-Dichloro-1,1,2,2,3-pentafluoropropane (507-55-1)	37-45%-Aerosol 48-55%-Bulk
Methanol(67-56-1)	.5-2%-Aerosol 1-2%-Bulk
Ethanol(64-17-5)	5-7%-Aerosol 7-8%-Bulk
Nitromethane(75-52-5)	< .5%
Aerosol-1,1,1,2-Tetrafluoroethane(811-97-2)	18-22%
Carbon Dioxide (Aerosol Propellant)(124-38-9)	1-3%

#### Plastic Compatibility

Material	Compatibility	Material	Compatibility
ABS	Not Compatible	PMMA	Not Compatible
Nylon	Excellent	POM	Excellent
Lexan	Not Compatible	PP	Excellent
HDPE	Excellent	PS	Excellent
LDPE	Excellent	PTFE	Good
C. E. Phenolic	Excellent	PVC	*

\*Not recommended for stressed PVC-R or PVC-P

Techspray® is committed to developing products to ensure a safer and cleaner environment. We will continue to meet and sustain the regulations of all federal, state and local government agencies.

#### Packaging and Availability

Blue Shower® II may be ordered in the following container sizes:

1667-8S 8 Ounce Aerosol 1667-18S 18 Ounce Aerosol 50 Pounds in Metal 1667-5G

#### Resources

Techspray® products are supported by a global sales, technical and customer services resources.

For additional technical information on this product or other Techspray® products in the United States, call the technical sales department at 800-858-4043, email tsales@techspray.com or visit our web site at: www.techspray.com.

North America Tech Spray L.P. P.O. Box 949 Amarillo, TX 79105 800-858-4043

email: tsales@techspray.com

Europe **Techspray International** UNIT 4, 44/46 Bunyan Road, Kempston Bedford MK42 8HL United Kingdom +44 (0) 1234 855443

email: tseurope@techspray.com

Countries Outside US Call to locate a distributor in your country.

Important Notice to Purchaser/User: The information in this publication is based on tests that we believe are reliable. The results may vary due to differences in tests type and conditions. We recommend that each user evaluate the product to determine its suitability for the intended application. Conditions of use are outside our control and vary widely. Techspray's only obligation and your only solution is replacement of product that is shown to be defective when you receive it. In no case will Techspray® be liable for any special, incidental, or consequential damages based on breach of warranty, negligence or any other theory.



Tech Spray, L.P. P.O. Box 949 Amarillo, TX 79105 www.techspray.com Aerosol English <u>French</u> German Italian Spanish

Bulk **English** French German Italian **Spanish** 



