



Product Information

Asahiklin AK225 T

General Duty Defluxer

1669

Introduction

Asahiklin AK225 T is a blend of Asahiklin AES and cyclohexane designed to remove fluxes prone to white residue. Designed for vapor degreasing, batch cleaning and hand operation, the solvent performs similar to the straight Asahiklin AES 1666. Note: As AK225 is not an azeotrope, the density should be monitored and AES added to maintain consistent operation.

Features / Benefits

- Non-Flammable
- Rapidly Evaporating
- Safe on Most Plastics
- Zero Residue
- Vapor Degreasing Blend
- Non-Corrosive
- Replacement for CFC-113
- Replacement for HCFC-141b
- EPA SNAP Approved

Physical Properties

Boiling Point	54°C / 129°F
Flash Point (TCC)	None
Evaporation Rate	>1
Surface Tension	
Kauri-Butanol (KB Value)	

Chemical Components

3,3-Dichloro-1,1,1,2,2-pentafluoropropane.... (422-56-0)	34-43%
1,3-Dichloro-1,1,2,2,3-pentafluoropropane.... (507-55-1)	42-52%
Ethanol..... (64-17-5)	4-5%
Cyclohexane..... (110-82-7)	10%
Nitromethane..... (75-52-5)	< .5%

Environmental Policy

Techspray® is committed to developing products to ensure a safer and cleaner environment. We will continue to meet and sustain the regulations of all federal, state and local government agencies.

Packaging and Availability

Asahiklin AK225 T may be ordered in the following container sizes:

1669-5G	44 Pounds in Metal
1669-55G	550 Pounds in Metal

Resources

Techspray® products are supported by a global sales, technical and customer services resources.

For additional technical information on this product or other Techspray® products in the United States, call the technical sales department at 800-858-4043, email tsales@techspray.com or visit our web site at: www.techspray.com.

North America
Tech Spray L.P.
P.O. Box 949
Amarillo, TX 79105
800-858-4043
email: tsales@techspray.com

Europe
Techspray International
UNIT 4, 44/46 Bunyan Road, Kempston
Bedford MK42 8HL United Kingdom
+44 (0) 1234 855443
email: tseurope@techspray.com

Countries Outside US
Call to locate a distributor
in your country.

Important Notice to Purchaser/User: The information in this publication is based on tests that we believe are reliable. The results may vary due to differences in tests type and conditions. We recommend that each user evaluate the product to determine its suitability for the intended application. Conditions of use are outside our control and vary widely. Techspray's only obligation and your only solution is replacement of product that is shown to be defective when you receive it. In no case will Techspray® be liable for any special, incidental, or consequential damages based on breach of warranty, negligence or any other theory.



Tech Spray, L.P.
P.O. Box 949
Amarillo, TX 79105
www.techspray.com

[English MSDS](#)
[French MSDS](#)
[German MSDS](#)
[Italian MSDS](#)
[Spanish MSDS](#)