

International
IR Rectifier

SCHOTTKY RECTIFIER
HIGH EFFICIENCY SERIES

PD - 94219A

16SYQ060C

16A, 60V


Major Ratings and Characteristics

Characteristics	16SYQ060C	Units
$I_F(AV)$	16	A
V_{RRM}	60	V
I_{FSM} @ $t_p = 8.3ms$ half-sine	250	A
V_F @ 16Apk, $T_J = 125^\circ C$	0.63	V
T_J, T_{stg} Operating and storage	-55 to 150	$^\circ C$

Description/Features

The 16SYQ060C Schottky rectifier has been expressly designed to meet the rigorous requirements of hi-rel environments. It is packaged in the hermetic isolated TO-257AA ceramic package. The device's forward voltage drop and reverse leakage current are optimized for the lowest power loss and the highest circuit efficiency for typical high frequency switching power supplies and resonant power converters. Full MIL-PRF-19500 quality conformance testing is available on source control drawings to TX, TXV and S levels.

- Hermetically Sealed
- Ceramic Eyelets
- Low Forward Voltage Drop
- High Frequency Operation
- Guard Ring for Enhanced Ruggedness and Long term Reliability
- Lightweight



16SYQ060C

International
IOR Rectifier

Voltage Ratings

Part number	16SYQ060C
V_R Max. DC Reverse Voltage (V)	60
V_{RWM} Max. Working Peak Reverse Voltage (V)	

Absolute Maximum Ratings

Parameters	Limits	Units	Conditions
$I_{F(AV)}$ Max. Average Forward Current See Fig. 5	16	A	50% duty cycle @ $T_C = 125^\circ\text{C}$, square waveform
I_{FSM} Max. Peak One Cycle Non - Repetitive Surge Current	250	A	@ $t_p = 8.3$ ms half-sine

Electrical Specifications

Parameters	Limits	Units	Conditions
V_{FM} Max. Forward Voltage Drop See Fig. 1①	0.66	V	@ 16A $T_J = -55^\circ\text{C}$
	0.87	V	@ 32A
	0.65	V	@ 16A $T_J = 25^\circ\text{C}$
	0.94	V	@ 32A
	0.63	V	@ 16A $T_J = 125^\circ\text{C}$
	1.04	V	@ 32A
I_{RM} Max. Reverse Leakage Current See Fig. 2①	0.5	mA	$T_J = 25^\circ\text{C}$
	50	mA	$T_J = 100^\circ\text{C}$
	190	mA	$T_J = 125^\circ\text{C}$
C_T Max. Junction Capacitance	2100	pF	$V_R = 5V_{DC}$ (1MHz, 25°C)
L_S Typical Series Inductance	9.8	nH	Measured from anode lead to cathode lead 6mm (0.025 in.) from package

Thermal-Mechanical Specifications

Parameters	Limits	Units	Conditions
T_J Max. Junction Temperature Range	-55 to 150	$^\circ\text{C}$	
T_{stg} Max. Storage Temperature Range	-55 to 150	$^\circ\text{C}$	
R_{thJC} Max. Thermal Resistance, Junction to Case	1.15	$^\circ\text{C/W}$	DC operation See Fig. 4
w_t Weight (Typical)	4.3	g	
Die Size	200X200	mils	
Case Style	TO-257AA		

① Pulse Width < 300 μs , Duty Cycle < 2%




Fig. 1 - Max. Forward Voltage Drop Characteristics




Fig. 2 - Typical Values of Reverse Current Vs. Reverse Voltage






Fig. 3 - Typical Junction Capacitance Vs. Reverse Voltage

Fig. 4 - Max. Thermal Impedance Z_{thJC} CharacteristicsFig. 5 - Max. Allowable Case Temperature Vs.
Average Forward Current