## Honeywell




Fenwal and Elmwood brand products are now a part of Honeywell.

Thermal

| ▼ About | ▼ News | ▼ Product | ▼ Solutions

**Back** 

## Uni-Curve® Series



All illustration dimensions are in inches

## **FEATURES**

- Surface mountable for automated pick and place
- Accuracy
- High stability
- High reliability
- Long life
- Cost saving
- Small size
- Epoxy coated
- D.C. 0.75 mW/o C minimum
- T.C. 15 sec. maximum
- Max. Temp. 125o C

**UNI-CURVE® INTERCHANGEABLE THERMISTORS** are high quality, low cost resistance temperature matched interchangeable thermistors. They offer additional cost savings by eliminating the need for individual resistance temperature calibration, as well as standardization of circuit components and simplification of design and replacement problems. They are particularly well suited for use in applications such as temperature measurement, indication and control. Other applications include: compensation of ambient temperature effects on copper coils, transistors, integrated circuits and other semiconductor devices. Fenwal Electronics' high volume Uni-Curvel manufacturing capability provides availability of interchangeable thermistors at low cost with the quality and ruggedness to meet the rigid design requirements of MIL-T-23648.

Resis. at 25° C (Ohms)	Temp Range ° C	R-T Curve	± .2° C Tolerance Part(D) Number	± .5° C Tolerance  Part Number	± 1.0° C Tolerance Part Number
2,252**	0° C to 70° C	16	192-222LET-A01	192-222LEV-A01®	192-222LEW-A01
3,000**	0° C to 70° C	16	192-302LET-A01	192-302LEV-A01	192-302LEW-A010
5,000	0° C to 70° C	16	192-502LET-A01	192-502LEV-A01	192-502LEW-A010
10,000	0° C to 70° C	16	192-103LET-A01	192-103LEV-A01	192-103LEW-A010
30,000	0° C to 70° C	18	192-303KET-A01	192-303KEV-A01	192-303KEW-A010
30,000	0° C to 70° C	1	192-303QET-A01	192-303QEV-A01	192-303QEW-A010
50,000	0° C to 70° C	1	192-503QET-A01	192-503QEV-A01	192-503QEW-A010
100,000	0° C to 70° C	1	192-104QET-A01	192-104QEV-A01®	192-104QEWA01

<sup>\*</sup>Leads are tinned copper.

Fenwal Electronics, Inc. provides special order CUSTOMIZED SERVICE to fulfill unique Uni-Curve® requirements. This service offers the capability of other resistance values and matching resistance temperature tolerances from 300 Ohms through 100k Ohms at 25° C and from .05° C to 1° C accuracy over a variety of temperature ranges, maintaining curve-matched resistance temperature characteristics.

<sup>\*\*</sup>Diameter of 2,252 Ohm and 3,000 Ohm parts is .120" max.

<sup>(</sup>i) = Distributor item