



## Product Information

# Blue High Voltage Putty

High Dielectric Material  
1976

## Introduction

---

Special compound designed to rebuild fly-back transformers wires that have melted. Also excellent for stopping corona and arcing from anode buttons and yolk connections. **NOTE:** The typical dielectric strength of this material is 1000 volts per mil on a 10 mil thick sample. Also please note that the dielectric strength changes with thickness.

## Chemical Components

---

This product does not contain any hazardous ingredients as per OSHA 29 CFR 1910.1200 Subpt.(z).

## Environmental Policy

---

Techspray® is committed to developing products that have minimal effects on the environment. We will continue to meet and sustain the regulations of all federal, state and local government agencies.

## Packaging and Availability

---

Blue High Voltage Putty is available in the following sizes:

1976-DP      2 Ounces

## Resources

---

Techspray® products are supported by a global sales, technical and customer services resources.

For additional technical information on this product or other Techspray® products in the United States, call the technical sales department at 800-858-4043, email [tsales@techspray.com](mailto:tsales@techspray.com) or visit our web site at: [www.techspray.com](http://www.techspray.com).

### North America

Tech Spray L.P.  
P.O. Box 949  
Amarillo, TX 79105  
800-858-4043  
email: [tsales@techspray.com](mailto:tsales@techspray.com)

### Europe

Techspray International  
UNIT 4, 44/46 Bunyan Road, Kempston  
Bedford MK42 8HL United Kingdom  
+44 (0) 1234 855443  
email: [tseurope@techspray.com](mailto:tseurope@techspray.com)

### Countries Outside US

Call to locate a distributor  
in your country.

Important Notice to Purchaser/User: The information in this publication is based on tests that we believe are reliable. The results may vary due to differences in tests type and conditions. We recommend that each user evaluate the product to determine its suitability for the intended application. Conditions of use are outside our control and vary widely. Techspray's only obligation and your only solution is replacement of product that is shown to be defective when you receive it. In no case will Techspray® be liable for any special, incidental, or consequential damages based on breach of warranty, negligence or any other theory.



Tech Spray, L.P.  
P.O. Box 949  
Amarillo, TX 79105  
[www.techspray.com](http://www.techspray.com)

