# ■ MASTER-MITE ESD™ HEAT GUN



# **Quick Jump:**

# A bench-top heating system that eliminates housing related ESD (electrostatic discharge)

- Comes standard with black 800°F/427°C heating element, shrink attachment and adjustable stand
- Housing surface conductivity 500 ohms/square. Conductive housing will not build up or hold a static charge
- Housing helps to shield against EMI & RFI (electromagnetic & radio frequency interference)
- A totally grounded system
- A long life, quiet running, maintenance free shaded pole motor
- Low velocity air will not blow components around the workstation
- 3 optional interchangeable plug-in heating elements available









Speed Dry Conformal Coatings



Terminate Specialty Connectors

#### ORDERING INFORMATION

MODEL NO.	VOLTS	Hz.	AMPS	Ship Wt.
10012	120	60	4.5	3 lbs.
10014	100	50/60	4.9	3 lbs.

#### REPLACEMENT HEATING ELEMENTS - OPTIONAL

PART NO.	COLOR	TEMP °F	TEMP °C	VOLTS	WATTS
20012	Blue	500	260	120	340
20013	Silver	650	343	120	475
20014	Black	800	427	120	525







40060

30201

50675

## **OPTIONAL ACCESSORIES**

MODEL NO.	DESCRIPTION
40060	Heat shrink attachment
30201	Solder preform attachment
50675	Bench stand

## **SPECIFICATIONS**

Ave. Air Volume: 3.8 CFM

Ave. Air Velocity: 700 FPM

■ Motor: Shaded Pole 3300 RPM

■ Dimensions: 8.8" L x 3.3" W x 7" H

Nozzle Opening: 1" Dia.

Cordset: 7 ft.

■ Net Weight: 1.75 lbs.

■ Shipping Weight: 3 lbs.

Users should independently evaluate the suitability of the product for their application.

HOME BACK TO PRODUCT LISTING