



MIC860

Teeny™ Ultra Low Power Op Amp

General Description

The MIC860 is a rail-to-rail output, operational amplifier in Teeny™ SC70 packaging. The MIC860 provides 4MHz gain-bandwidth product while consuming an incredibly low 30µA supply current.

The SC70 packaging achieves significant board space savings over devices packaged in SOT-23 or MSOP-8 packaging. The SC70 occupies approximately half the board area of a SOT-23 package.

Features

- Teeny™ SC70 packaging
- 4MHz gain-bandwidth product
- 30µA supply current
- Rail-to-Rail output
- Ground sensing at input common mode to GND
- Common mode to GND
- Drive large capacitive loads

Applications


- Portable equipment
- PDAs
- Pagers
- Cordless Phones
- Consumer Electronics

Ordering Information


Part Number				Ambient Temp. Range	Package
Standard	Marking	Pb-Free	Marking*		
MIC860BC5	A32	MIC860YC5	A32	-40°C to +85°C	SC-70-5

* Underbar marking may not be to scale.

Pin Configuration



Functional Pinout



Absolute Maximum Ratings (Note 1)

Supply Voltage ($V_{V+} - V_-$)	+6.0V
Differential Input Voltage ($ V_{IN+} - V_{IN-} $), Note 4	+6.0V
Input Voltage ($V_{IN+} - V_{IN-}$)	$V_+ + 0.3V$, $V_- - 0.3V$
Lead Temperature (soldering, 5 sec.)	260°C
Output Short Circuit Current Duration	Indefinite
Storage Temperature (T_S)	150°C
ESD Rating, Note 3	

Operating Ratings (Note 2)

Supply Voltage ($V_+ - V_-$)	+2.43V to +5.25V
Ambient Temperature Range	-40°C to +85°C
Package Thermal Resistance	450°C/W

Electrical Characteristics

$V_+ = +2.7V$, $V_- = 0V$, $V_{CM} = V_+/2$; $R_L = 500k\Omega$ to $V_+/2$; $T_A = 25^\circ C$, unless otherwise noted. **Bold** values indicate $-40^\circ C \leq T_A \leq +85^\circ C$.

Symbol	Parameter	Condition	Min	Typ	Max	Units
V_{OS}	Input Offset Voltage		-20	-5	15	mV
			-25		20	mV
	Input Offset Voltage Temp Coefficient			20		$\mu V/^\circ C$
I_B	Input Bias Current			20		pA
I_{OS}	Input Offset Current			10		pA
V_{CM}	Input Voltage Range	CMRR > 60dB	1	1.8		V
CMRR	Common-Mode Rejection Ratio	$0 < V_{CM} < 1.35V$	38	76		dB
PSRR	Power Supply Rejection Ratio	Supply voltage change of 3V	40	78		dB
A_{VOL}	Large-Signal Voltage Gain	$R_L = 5k$, V_{OUT} 2V peak to peak	50	66		dB
		$R_L = 100k$, V_{OUT} 2V peak to peak	66	81		dB
		$R_L = 500k$, V_{OUT} 2V peak to peak	76	91		dB
V_{OUT}	Maximum Output Voltage Swing	$R_L = 5k$	$V_+ - 70mV$	$V_+ - 34mV$		V
		$R_L = 500k$	$V_+ - 2mV$	$V_+ - 0.7mV$		V
V_{OUT}	Minimum Output Voltage Swing	$R_L = 5k$		$V_+ - 11mV$	$V_+ - 50mV$	mV
		$R_L = 500k$		$V_+ - 0.2mV$	$V_+ - 2mV$	mV
GBW	Gain-Bandwidth Product			4		MHz
SR	Slew Rate			3		V/ μs
I_{SC}	Short-Circuit Output Current	Source	4.5	6		mA
		Sink	10	16		mA
I_S	Supply Current	No Load		30	50	μA

$V_+ = +5V$, $V_- = 0V$, $V_{CM} = V_+/2$; $R_L = 500k\Omega$ to $V_+/2$; $T_A = 25^\circ C$, unless otherwise noted. **Bold** values indicate $-40^\circ C \leq T_A \leq +85^\circ C$.

Symbol	Parameter		-20	-5	20	mV
V_{OS}	Input Offset Voltage					
	Input Offset Voltage Temp Coefficient			20		$\mu V/^\circ C$
I_B	Input Bias Current			20		pA
I_{OS}	Input Offset Current			10		pA
V_{CM}	Input Voltage Range	CMRR > 60dB	3.5	4.2		V
CMRR	Common-Mode Rejection Ratio	$0 < V_{CM} < 3.5V$	44	77		dB
PSRR	Power Supply Rejection Ratio	Supply voltage change of 1V	40	79		dB
A_{VOL}	Large-Signal Voltage Gain	$R_L = 5k$, V_{OUT} 4.8V peak to peak	52	66		dB
		$R_L = 100k$, V_{OUT} 4.8V peak to peak	67	80		dB
		$R_L = 500k$, V_{OUT} 4.8V peak to peak	75	90		dB

Symbol	Parameter	Condition	Min	Typ	Max	Units
V_{OUT}	Maximum Output Voltage Swing	$R_L = 5k$	$V+75mV$	$V+37mV$		V
		$R_L = 500k$	$V+35mV$	$V+4mV$		V
V_{OUT}	Minimum Output Voltage Swing	$R_L = 5k$		$V-+14mV$	$V-+40mV$	mV
		$R_L = 500k$		$V-+0.4mV$	$V-+5mV$	mV
GBW	Gain-Bandwidth Product			4		MHz
SR	Slew Rate			3		V/ μ s
I_{SC}	Short-Circuit Output Current	Source	15	23		mA
		Sink	30	47		mA
I_S	Supply Current	No Load		33	55	μ A






Note 1. Exceeding the absolute maximum rating may damage the device.

Note 2. The device is not guaranteed to function outside its operating rating.

Note 3. Devices are ESD sensitive. Handling precautions recommended. Human body model, 1.5k in series with 100pF. Pin 4 is ESD sensitive













Note 4. Exceeding the maximum differential input voltage will damage the input stage and degrade performance (in particular, input bias current is likely to increase).



Test Circuits

Test Circuit 1. $A_V = 10$ Test Circuit 2. $A_V = 2$ Test Circuit 3. $A_V = 1$ Test Circuit 4. $A_V = -1$ 








Test Circuit 5. Positive Power Supply Rejection Ratio Measurement


Typical Characteristics








Functional Characteristics









Small Signal Response
Test Circuit 4: $A_v = -1$




Small Signal Response
Test Circuit 4: $A_v = -1$






Small Signal Response
Test Circuit 4: $A_v = -1$



Small Signal Response
Test Circuit 4: $A_v = -1$





Applications Information

Power Supply Bypassing

Regular supply bypassing techniques are recommended. A 10 μ F capacitor in parallel with a 0.1 μ F capacitor on both the positive and negative supplies are ideal. For best performance all bypassing capacitors should be located as close to the op amp as possible and all capacitors should be low ESL (equivalent series inductance), ESR (equivalent series resistance). Surface-mount ceramic capacitors are ideal.


Supply and Loading Considerations

The MIC860 is intended for single supply applications configured with a grounded load. It is not advisable to operate the MIC860 with either:


- 1). A grounded load and split supplies (+/-V) or
- 2). A single supply where the load is terminated above ground.

Under the above conditions, if the load is less than 20kOhm and the output swing is greater than 1V(peak), there may be some instability when the output is sinking current.


Package Information



TOP VIEW



END VIEW



SIDE VIEW

SC70-5

NOTE:

1. ALL DIMENSIONS ARE IN MILLIMETERS.
2. DIMENSIONS ARE INCLUSIVE OF PLATING.
3. DIMENSIONS ARE EXCLUSIVE OF MOLD FLASH & METAL BURR.

MICREL INC. 2180 FORTUNE DRIVE SAN JOSE, CA 95131 USA
 TEL + 1 (408) 944-0800 FAX + 1 (408) 474-1000 WEB <http://www.micrel.com>

This information furnished by Micrel in this data sheet is believed to be accurate and reliable. However no responsibility is assumed by Micrel for its use.
 Micrel reserves the right to change circuitry and specifications at any time without notification to the customer.

Micrel Products are not designed or authorized for use as components in life support appliances, devices or systems where malfunction of a product can reasonably be expected to result in personal injury. Life support devices or systems are devices or systems that (a) are intended for surgical implant into the body or (b) support or sustain life, and whose failure to perform can be reasonably expected to result in a significant injury to the user. A Purchaser's use or sale of Micrel Products for use in life support appliances, devices or systems is a Purchaser's own risk and Purchaser agrees to fully indemnify

Micrel for any damages resulting from such use or sale.