

**EUP7559**

Low Noise Dual 300mA LDO with Independent Shutdown

DESCRIPTION

The EUP7559 is a dual low dropout linear regulator capable of sourcing 300mA current per regulator.

The EUP7559 is stable with small ceramic output capacitors. The performance of EUP7559 is optimized for battery power systems to deliver low noise, low dropout voltage, low quiescent current and excellent line and load transient response.

The EUP7559 is available in fixed output voltages in the 8-pin 3mmx3mm TDFN leadless package.


FEATURES

- Input Voltage Range: 2.5V to 6V
- 300mA Output Current per LDO
- Low Dropout Voltage of 55mV@100mA
- Low Quiescent Current of 115 μ A per LDO
- High PSRR 70dB at 1kHz
- Low Output Noise
- Thermal Shutdown Protection
- Current Limit Protection
- Separate Enable pin per LDO
- Stable with Ceramic Output Capacitor
- 1.5V to 3.3V Pre-set Output
- 3mmx3mm TDFN-8 Package
- RoHS Compliant and 100% Lead (Pb)-Free


APPLICATIONS

- Cellular Phones
- PDAs and Palmtop Computers
- Wireless LAN Cards
- Hand-Held Instruments


Typical Application



Block Diagram



Pin Configurations

| Package Type | Pin Configurations |
|--------------|---|
| TDFN-8 | <p style="text-align: center;">TOP VIEW</p>  |

Pin Description


| PIN | PIN | DESCRIPTION |
|------|-----|--|
| INA | 1 | LDO A Regulator Input. Connect to INB. Input voltage can range from 2.5V to 6V. Bypass INA with a ceramic capacitor to GND. |
| ENA | 2 | Shutdown A Input. A logic-low on ENA shuts down regulator A. If ENA and ENB are both low, both regulators and the internal reference are off and the supply current is reduced to 10nA (typ). If either ENA or ENB is a logic high, the internal reference is on. Connect ENA to INA for always-on operation of regulator A. |
| ENB | 3 | Shutdown B Input. A logic-low on ENB shuts down regulator B. If ENA and ENB are both low, both regulators and the internal reference are off and the supply current is reduced to 10nA (typ). If either ENA or ENB is a logic high, the internal reference is on. Connect ENB to INB for always-on operation of regulator B. |
| INB | 4 | LDO B Regulator Input. Connect to INA. Input voltage can range from 2.5V to 6V. Bypass INB with a ceramic capacitor to GND. |
| OUTB | 5 | Regulator B Output. OUTB can source up to 300mA continuous current. Bypass OUTB with a ceramic capacitor to GND. During shutdown, OUTB is internally discharged to GND through a 300 . resistor. |
| GND | 6 | Ground. |
| BP | 7 | Reference Noise Bypass. Bypass BP with a low-leakage 0.01 μ F ceramic capacitor for reduced noise at both outputs. |
| OUTA | 8 | Regulator A Output. OUTA can source up to 300mA continuous current. Bypass OUTA with a ceramic capacitor to GND. During shutdown, OUTA is internally discharged to GND through a 300 . resistor. |

Ordering Information

| Order Number | Package Type | Marking | Operating Temperature range |
|-----------------------|--------------|-----------------|-----------------------------|
| EUP7559-1.5/1.5JIR1 | TDFN-8 | XXXXX 7559-V | -40 °C to 125°C |
| EUP7559-1.5/2.8JIR1 | TDFN-8 | XXXXX 7559-C | -40 °C to 125°C |
| EUP7559-1.8/2.8JIR1 | TDFN-8 | XXXXX 7559-A | -40 °C to 125°C |
| EUP7559-1.8/3.3JIR1 | TDFN-8 | XXXXX 7559-H | -40 °C to 125°C |
| EUP7559-1.85/1.5JIR1 | TDFN-8 | XXXXX 7559-a | -40 °C to 125°C |
| EUP7559-2.5/2.8JIR1 | TDFN-8 | XXXXX 7559-D | -40 °C to 125°C |
| EUP7559-2.85/1.8JIR1 | TDFN-8 | XXXXX 7559-b | -40 °C to 125°C |
| EUP7559-2.85/1.85JIR1 | TDFN-8 | XXXXX 7559-X | -40 °C to 125°C |
| EUP7559-2.85/2.85JIR1 | TDFN-8 | XXXXX 7559-G | -40 °C to 125°C |
| EUP7559-3.15/2.8JIR1 | TDFN-8 | XXXXX 7559-Z | -40 °C to 125°C |
| EUP7559-3.3/2.85JIR1 | TDFN-8 | XXXXX 7559-W | -40 °C to 125°C |
| EUP7559-3.3/3.0JIR1 | TDFN-8 | XXXXX 7559-Y | -40 °C to 125°C |

EUP7559

/



Lead Free Code

1: Lead Free 0: Lead

Packing

R: Tape & Reel

Operating temperature range

I: Industry Standard

Package Type

J: TDFN

Output Voltage Option

Absolute Maximum Ratings

| | |
|---------------------------------------|--------------------|
| ■ V _{IN} , V _{EN} | -0.3V to 6.5V |
| ■ Power Dissipation (P _D) | Internally Limited |
| ■ Junction Temperature | -40°C to +125°C |
| ■ Storage Temperature | -65°C to +150°C |
| ■ Lead Temp | 260°C |

Operating Ratings

| | |
|---|-----------|
| ■ V _{IN} | 2.5 to 6V |
| ■ V _{EN} | 0V to 6V |
| ■ Junction Temperature | 150°C |
| ■ Thermal Resistance θ_{JA} (TDFN-8) | 60°C/W |







Electrical CharacteristicsV_{IN}=3.8V, V_{ENA}=V_{ENB}=V_{IN}, I_O=10mA, C_{IN}=C_{OUT}=2.2uF, T_A= -40°C ~85°C.

| Parameter | Symbol | Conditions | Min | Typ | Max | Units |
|---|-----------------------------------|--|-------|-------|------|-------|
| Input Voltage Range | V _{IN} | | 2.5 | | 6 | V |
| Undervoltage-Lockout Threshold | V _{UVLO} | V _{IN} Rising , hysteresis is 40mV(typ) | 2.15 | 2.3 | 2.45 | V |
| Output Voltage Accuracy | V _O | T _A =25 , I _{OUT1} =I _{OUT2} =1mA | -1.5 | | 1.5 | % |
| | | T _A =-40 to 85 , I _{OUT1} =I _{OUT2} =1mA | -2.5 | | 2.5 | |
| | | T _A =-40 to 85 , I _{OUT1} or I _{OUT2} =0.1mA to 300mA | -3 | | 3 | |
| Maximum Output Current | I _{OUT} | | 300 | | | mA |
| Output Current Limit | I _{LIM} | | 320 | 500 | 780 | mA |
| Ground Current | I _Q | No Load | | 180 | 280 | μA |
| | | No Load, one LDO Shutdown | | 115 | | |
| | | I _{OUT1} =I _{OUT2} = 100mA | | 240 | | |
| Dropout Voltage | V _{IN} -V _{OUT} | I _{OUT} =1mA | | 0.6 | | mV |
| | | I _{OUT} =100mA | | 55 | 110 | |
| Line Regulation | V _{LNR} | V _{IN} =(V _O +0.1)V to 6V, I _{OUT} =1mA | -0.15 | 0.02 | 0.15 | %V |
| Output Voltage Noise | | 100Hz to 100kHz, C _{OUT} =10uF, I _{OUT} =1mA, C _{BP} =0.01uF | | 35 | | μVrms |
| | | 100Hz to 100kHz, C _{OUT} =10uF, I _{OUT} =1mA, C _{BP} =not installed | | 124 | | |
| Power Supply Ripple Rejection | PSRR | C _{OUT} =2.2uF,I _{OUT} =50mA,C _{BP} =0.01uF, f=1kHz | | 70 | | dB |
| | | C _{OUT} =2.2uF,I _{OUT} =50mA,C _{BP} =0.01uF, f=10kHz | | 60 | | |
| | | C _{OUT} =2.2uF,I _{OUT} =50mA,C _{BP} =0.01uF, f=100kHz | | 46 | | |
| Shutdown Supply Current | I _{SHDN} | V _{EN} =0, T _A =25 | | 0.01 | 1 | μA |
| | | T _A =-40 to 85 | | 0.1 | | |
| Enable Input Threshold | V _{IH} | Input high voltage | 1.6 | | | V |
| | V _{IL} | Input low voltage | | | 0.4 | |
| Enable Input Bias Current | | V _{EN} =0 or IN, T _A =25 | | 0.1 | 10 | nA |
| | | T _A =-40 to 85 | | 1 | | |
| V _{OUT} Discharge Resistance in Shutdown | | V _{EN} =0 | | 300 | | |
| Thermal Shutdown Temperature | T _{SHDN} | T _J Rising | | 160 | | |
| Thermal Shutdown Hysteresis | ΔT _{SHDN} | | | 15 | | |
| Output Capacitor | C _{OUT} | I _{OUT} =0 to 300mA | | 2.2uF | | |



Typical Operating Characteristics


Unless otherwise specified, $C_{IN}=C_{OUT}=2.2\mu F$, $C_{BP}=0.01\mu F$, $V_{IN}=3.8V$, $V_{ENA}=V_{ENB}=V_{IN}$, $I_o=10mA$, $V_{OUTA}=V_{OUTB}=2.85V$.




Typical Operating Characteristics (continued)

Unless otherwise specified, $C_{IN}=C_{OUT}=2.2\mu F$, $C_{BP}=0.01\mu F$, $V_{IN}=3.8V$, $V_{ENA}=V_{ENB}=V_{IN}$, $I_o=10mA$, $V_{OUTA}=V_{OUTB}=2.85V$.


LINE TRANSIENT




LOAD TRANSIENT




LOAD TRANSIENT NEAR DROPOUT




SHUTDOWN RESPONSE



SHORT CIRCUIT CURRENT





Overcurrent Protection



Typical Operating Characteristics (continued)

Unless otherwise specified, $C_{IN}=C_{OUT}=2.2\mu F$, $C_{BP}=0.01\mu F$, $V_{IN}=3.8V$, $V_{ENA}=V_{ENB}=V_{IN}$, $I_o=10mA$, $V_{OUTA}=V_{OUTB}=2.85V$.



Application Note

The EUP7559 is a high performance, low quiescent current power management IC consisting of two μ Cap low dropout regulators. The first regulator is capable of sourcing 300mA at output voltages from 1.5V to 3.3V. The second regulator is capable of sourcing 300mA of current at output voltages from 1.5V to 3.3V. These outputs are stable with 2.2uF output capacitor at any load.

Enable A and B

The enable inputs allow for logic control of both output voltages with individual enable inputs. The EUP7559 is turned off by pulling the V_{EN} pin low, and turned on by pulling it high. If this feature is not used, the V_{EN} pin should be tied to V_{IN} to keep the regulator output on at all time. To assure proper operation, the signal source used to drive the V_{EN} input must be able to swing above and below the specified turn-on/off voltage thresholds listed in the Electrical Characteristics section under V_{IL} and V_{IH} .

External Capacitors

Like any low-dropout regulator, the EUP7559 requires external capacitors for regulator stability. The EUP7559 is specifically designed for portable applications requiring minimum board space and smallest components. These capacitors must be correctly selected for good performance.

Input Capacitor

An input capacitance of $\approx 2.2\mu F$ or greater is required between the EUP7559 input pin and ground (the amount of the capacitance may be increased without limit). This capacitor must be located a distance of not more than 1cm from the input pin and returned to a clean analog ground. Any good quality ceramic, tantalum, or film capacitor may be used at the input.

Output Capacitor

The EUP7559 is designed specifically to work with very small ceramic output capacitors. A ceramic capacitor (temperature characteristics X7R, X5R, Z5U, or Y5V) in 2.2 μ F to 22 μ F range with 5m Ω to 500m Ω ESR range is suitable in the EUP7559 application circuit.

The output capacitor must meet the requirement for minimum amount of capacitance and also have an ESR (Equivalent Series Resistance) value which is within a stable range (5m Ω to 500m Ω)

No-Load Stability

The EUP7559 will remain stable and in regulation with no external load. This is specially important in CMOS RAM keep-alive applications.

Capacitor Characteristics

The EUP7559 is designed to work with ceramic capacitors on the output ceramic capacitors are the smallest, least expensive and have the lowest ESR values (which makes them best for eliminating high frequency noise). The ESR of a typical 2.2 μ F ceramic capacitor is in the range of 10m Ω to 40m Ω , which easily meets the ESR requirement for stability by the EUP7559.

The ceramic capacitor's capacitance can vary with temperature. The capacitor type X7R, which operates over a temperature range of -55°C to +125°C, will only vary the capacitance to within $\pm 15\%$. Most large value ceramic capacitors ($\approx 2.2\mu F$) are manufactured with Z5U or Y5V temperature characteristics. Their capacitance can drop by more than 50% as the temperature goes from 25°C to 85°C. Therefore, X7R is recommended over Z5U and Y5V in applications where the ambient temperature will change significantly above or below 25°C.

Noise Bypass Capacitor


Connecting a 0.01 μ F capacitor between the BP pin and ground significantly reduces noise on the regulator output. This cap is connected directly to a high impedance node in the bandgap reference circuit. Any significant loading on this node will cause a change on the regulated output voltage. For this reason, DC leakage current through this pin must be kept as low as possible for best output voltage accuracy. The types of capacitors best suited for the noise bypass capacitor are ceramic and film.

Unlike many other LDO's, addition of a noise reduction capacitor does not effect the load transient response of the device.



Packaging Information

TDFN-8



DETAIL A
Thermal Pad Option

| SYMBOLS | MILLIMETERS | | INCHES | |
|---------|-------------|------|--------|-------|
| | MIN. | MAX. | MIN. | MAX. |
| A | 0.70 | 0.80 | 0.028 | 0.031 |
| A1 | 0.00 | 0.05 | 0.000 | 0.002 |
| b | 0.20 | 0.40 | 0.008 | 0.016 |
| D | 2.90 | 3.10 | 0.114 | 0.122 |
| D1 | 2.30 | | 0.090 | |
| E | 2.90 | 3.10 | 0.114 | 0.122 |
| E1 | 1.50 | | 0.059 | |
| e | 0.65 | | 0.026 | |
| L | 0.25 | 0.45 | 0.010 | 0.018 |