

xDSL Differential Line Driver

The ISL1558 is a quad operational amplifier designed for VDSL2 and ADSL2+ line driving in DMT based solutions. This device features a high drive capability of 750mA while consuming only 6mA of supply current per amplifier at low bias and operating from a single 4.5V to 12V supply. The driver achieves a typical distortion of -80dBc, at 200kHz into a 50Ω differential load.

The ISL1558 is available in the thermally-enhanced 24 Ld QFN package and is specified for operation over the full -40°C to +85°C temperature range. The ISL1558 has control pins C₀ and C₁ for controlling the bias and enable/disable of the outputs. These controls allow for lowering the power to fit the performance/power ratio for the application.

The ISL1558 is ideal for VDSL2 and ADSL2+ central office line driving applications, including both 14.5dBm and 21dBm applications.

Features

- 21dBm output power capability
- Drives up to 750mA from a +12V supply
- 20V_{P-P} differential output drive into 21Ω
- -80dBc typical driver output distortion at full output at 200kHz
- -75dBc typical driver output distortion at 4MHz
- -71dBc typical driver output distortion at 10MHz
- -75dBc typical driver output distortion at 17MHz
- Low quiescent current of 6mA per amplifier
- Supply range
 - ±2.25V to ±6V, 4.5V to 12V
- 300MHz bandwidth
- Thermal shutdown
- Pb-free plus anneal available (RoHS compliant)

Applications

- VDSL2/ADSL2+ line drivers

Get Full Datasheet

Ordering Information

PART NUMBER (Note)	PART MARKING	TAPE AND REEL	TEMP. RANGE (°C)	PACKAGE (Pb-Free)	PKG. DWG. #
ISL1558IRZ	1558 IRZ	-	-40 to +85	24 Ld QFN	MDP0046
ISL1558IRZ-T13	1558 IRZ	13"	-40 to +85	24 Ld QFN	MDP0046
ISL1558IVEZ	ISL1558 IVEZ	-	-40 to +85	24 Ld HTSSOP	MDP0048
ISL1558IVEZ-T13	ISL1558 IVEZ	13"	-40 to +85	24 Ld HTSSOP	MDP0048

NOTE: Intersil Pb-free plus anneal products employ special Pb-free material sets; molding compounds/die attach materials and 100% matte tin plate termination finish, which are RoHS compliant and compatible with both SnPb and Pb-free soldering operations. Intersil Pb-free products are MSL classified at Pb-free peak reflow temperatures that meet or exceed the Pb-free requirements of IPC/JEDEC J STD-020.



ISL1558

All Intersil U.S. products are manufactured, assembled and tested utilizing ISO9000 quality systems.
Intersil Corporation's quality certifications can be viewed at www.intersil.com/design/quality

Intersil products are sold by description only. Intersil Corporation reserves the right to make changes in circuit design, software and/or specifications at any time without notice. Accordingly, the reader is cautioned to verify that data sheets are current before placing orders. Information furnished by Intersil is believed to be accurate and reliable. However, no responsibility is assumed by Intersil or its subsidiaries for its use; nor for any infringements of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Intersil or its subsidiaries.

For information regarding Intersil Corporation and its products, see www.intersil.com