

# **Absolute Maximum Ratings**

		$(Ta = 25^{\circ}C)$	
Item	Symbol	Ratings	Unit
Collector to base voltage	V <sub>CBO</sub>	-120	V
Collector to emitter voltage	V <sub>CEO</sub>	-100	V
Emitter to base voltage	V <sub>EBO</sub>	-6	V
Collector current	Ι <sub>C</sub>	-1.0	A
Collector peak current	I <sub>C (peak)</sub> * <sup>1</sup>	-2.0	A
Collector power dissipation	Pc	0.9	W
Junction temperature	Tj	150	°C
Storage temperature	Tstg	-55 to +150	°C


Note : 1. PW  $\leq$  10 ms, Duty cycle  $\leq$  20%



## **Electrical Characteristics**


						$(Ta = 25^{\circ}C)$
Item	Symbol	Min	Тур	Max	Unit	Test conditions
Collector to base breakdown voltage	V <sub>(BR)CBO</sub>	-120	—		V	$I_{\rm C} = -100 \ \mu \text{A}, \ I_{\rm E} = 0$
Collector to emitter breakdown voltage	V <sub>(BR)CEO</sub>	-100	—		V	$I_{C}$ = -10 mA, $R_{BE}$ = $\infty$
Emitter to base breakdown voltage	V <sub>(BR)EBO</sub>	-6	—	_	V	$I_{E} = -100 \ \mu A, I_{C} = 0$
Collector cutoff current	I <sub>CBO</sub>	_	—	-500	nA	$V_{CB} = -120 \text{ V}, I_E = 0$
Emitter cutoff current	I <sub>EBO</sub>	—	—	-500	nA	$V_{EB} = -6 V, I_{C} = 0$
DC current transfer ratio	h <sub>FE1</sub>	140	—	350	—	$V_{CE} = -2 V, I_{C} = -150 mA$
	h <sub>FE2</sub>	40	—		—	$V_{CE} = -5 V, I_{C} = -1 A$
Collector to emitter saturation voltage	V <sub>CE(sat)</sub>		—	-0.5	V	$I_{\rm C}$ = -500 mA, $I_{\rm B}$ = -50 mA
Base to emitter saturation voltage	V <sub>BE(sat)</sub>		—	-1.1	V	$I_{\rm C}$ = -500 mA, $I_{\rm B}$ = -50 mA

### **Main Characteristics**



### HIT647

### **Package Dimensions**



# **Ordering Information**

Part Name	Quantity	Shipping Container
HIT647-EQ	2500 pcs	Bulk, Vinyl Bag
HIT647TZ-EQ	2500 pcs	Hold Box, Radial Taping

Note: This product is designed for consumer use and not for automotive.

### RenesasTechnology Corp. sales Strategic Planning Div. Nippon Bldg., 2-6-2, Ohte-machi, Chiyoda-ku, Tokyo 100-0004, Japan

- Notes:
  1. This document is provided for reference purposes only so that Renesas customers may select the appropriate Renesas products for their use. Renesas neither makes warranties or representations with respect to the accuracy or completeness of the information contained in this document nor grants any license to any intellectual property rights or any other rights of Renesas or any third party with respect to the information in this document.
  2. Renesas shall have no liability for damages or infringement of any intellectual property or other rights arising out of the use of any information in this document, including, but not limited to, product data, diagrams, charts, programs, algorithms, and application circuit examples.
  3. You should not use the products or the technology described in this document for the purpose of military applications such as the development of weapons of mass and regulations, and procedures required by such laws and regulations.
  4. All information included in this document such as product data, diagrams, charts, programs, algorithms, and application circuit examples, is current as of the date this document is lissued. Such information, however, is subject to change without any prior notice. Before purchasing or using any Renesas products listed in this document, please confirm the latest product information included in this document, but Renesas assumes no liability whatsoever for any damages incurred as a result of errors or omissions in the information included in this document, but Renesas products for the total application. Renesas as suitable for automobile applications, Renesas products or septicability arising out of the application of the subject for any particular application and use of the information in this document.
  6. When using or otherwise relying on the information included in this document, but Renesas products are reasonable applications.
  7. With the exception of products specified by Renesas as suita

- undersea communication transmission. If you are considering the use of our products for such purposes, please contact a Renesa's sales office beforehand. Renesa's sha have no liability for damages arising out of the uses set forth above.
  Notwithstanding the preceding paragraph, you should not use Renesas products for the purposes listed below:

  artificial life support devices or systems
  surgical implantations
  healthcare intervention (e.g., excision, administration of medication, etc.)
  ary other purposes that poses a direct threat to human life

  Renesas shall have no liability for damages arising out of the uses set forth in the above and purchasers who elect to use Renesas products in any of the foregoing applications shall indemnify and hold harmless Renesas Technology Corp. its affiliated companies and their officers, directors, and employees against any and all damages arising out of such applications.
  You should use the products described herein within the range specified by Renesas, especially with respect to the maximum rating, operating supply voltage range, movement power voltage range, heat radiation characteristics, installation and other product characteristics. Renesas shall have no liability for malfunctions or damages arising out of the use of Renesas products beyond such specified ranges.

  Although Renesas endeavors to improve the quality and reliability of its products, IC products have specific characteristics such as the occurrence of failure at a certain rate and malfunctions, appropriate treatment for aging degradation or any other applicable measures to guard against the possibility of physical injury, and injury or damage alone is very difficult, please evaluate the safety of the final products or system manufactured by you.
  In case Renesas products listed in this document are detached from the products owhich the Renesas products may not be easily detached from your products. Ren



### **RENESAS SALES OFFICES**

Refer to "http://www.renesas.com/en/network" for the latest and detailed information.

Renesas Technology America, Inc. 450 Holger Way, San Jose, CA 95134-1368, U.S.A Tel: <1> (408) 382-7500, Fax: <1> (408) 382-7501

Renesas Technology Europe Limited Dukes Meadow, Millboard Road, Bourne End, Buckinghamshire, SL8 5FH, U.K. Tel: <44> (1628) 585-100, Fax: <44> (1628) 585-900

Renesas Technology (Shanghai) Co., Ltd. Unit 204, 205, AZIACenter, No.1233 Lujiazui Ring Rd, Pudong District, Shanghai, China 200120 Tel: <86> (21) 5877-1818, Fax: <86> (21) 6887-7898

Renesas Technology Hong Kong Ltd. 7th Floor, North Tower, World Finance Centre, Harbour City, 1 Canton Road, Tsimshatsui, Kowloon, Hong Kong Tel: <852> 2265-6688, Fax: <852> 2730-6071

Renesas Technology Taiwan Co., Ltd. 10th Floor, No.99, Fushing North Road, Taipei, Taiwan Tel: <886> (2) 2715-2888, Fax: <886> (2) 2713-2999

Renesas Technology Singapore Pte. Ltd. 1 Harbour Front Avenue, #06-10, Keppel Bay Tower, Singapore 098632 Tel: <65> 6213-0200, Fax: <65> 6278-8001

Renesas Technology Korea Co., Ltd. Kukje Center Bldg. 18th Fl., 191, 2-ka, Hangang-ro, Yongsan-ku, Seoul 140-702, Korea Tel: <82> (2) 796-3115, Fax: <82> (2) 796-2145

Renesas Technology Malaysia Sdn. Bhd Unit 906, Block B, Menara Amcorp, Amcorp Trade Centre, No.18, Jalan Persiaran Barat, 46050 Petaling Jaya, Selangor Darul Ehsan, Malaysia Tel: <603> 7955-9390, Fax: <603> 7955-9510

http://www.renesas.com