

$V_{CE} = 6500\text{ V}$
 $I_C = 400\text{ A}$




ABB HiPak™

IGBT Module

5SNA 0400J650100

Doc. No. 5SYA 1592-01 Jun 07

- Low-loss, rugged SPT chip-set
- Smooth switching SPT chip-set for good EMC
- High insulation package
- AlSiC base-plate for high power cycling capability
- AlN substrate for low thermal resistance



Maximum rated values ¹⁾

Parameter	Symbol	Conditions	min	max	Unit
Collector-emitter voltage	V_{CES}	$V_{GE} = 0\text{ V}$, $T_{vj} \geq 25\text{ °C}$		6500	V
DC collector current	I_C	$T_c = 85\text{ °C}$		400	A
Peak collector current	I_{CM}	$t_p = 1\text{ ms}$, $T_c = 85\text{ °C}$		800	A
Gate-emitter voltage	V_{GES}		-20	20	V
Total power dissipation	P_{tot}	$T_c = 25\text{ °C}$, per switch (IGBT)		7350	W
DC forward current	I_F			400	A
Peak forward current	I_{FRM}			800	A
Surge current	I_{FSM}	$V_R = 0\text{ V}$, $T_{vj} = 125\text{ °C}$, $t_p = 10\text{ ms}$, half-sinewave		4000	A
IGBT short circuit SOA	t_{psc}	$V_{CC} = 4400\text{ V}$, $V_{CEM\text{CHIP}} \leq 6500\text{ V}$ $V_{GE} \leq 15\text{ V}$, $T_{vj} \leq 125\text{ °C}$		10	μs
Isolation voltage	V_{isol}	1 min, $f = 50\text{ Hz}$		10200	V
Junction temperature	T_{vj}			125	°C
Junction operating temperature	$T_{vj(op)}$		-40	125	°C
Case temperature	T_c		-40	125	°C
Storage temperature	T_{stg}		-40	125	°C
Mounting torques ²⁾	M_s	Base-heatsink, M6 screws	4	6	Nm
	M_{t1}	Main terminals, M8 screws	8	10	
	M_{t2}	Auxiliary terminals, M4 screws	2	3	

¹⁾ Maximum rated values indicate limits beyond which damage to the device may occur per IEC 60747

²⁾ For detailed mounting instructions refer to ABB Document No. 5SYA2039

IGBT characteristic values ³⁾

Parameter	Symbol	Conditions	min	typ	max	Unit
Collector (-emitter) breakdown voltage	$V_{(BR)CES}$	$V_{GE} = 0 \text{ V}$, $I_C = 10 \text{ mA}$, $T_{vj} = 25 \text{ }^{\circ}\text{C}$	6500			V
Collector-emitter ⁴⁾ saturation voltage	$V_{CE \text{ sat}}$	$I_C = 400 \text{ A}$, $V_{GE} = 15 \text{ V}$, $T_{vj} = 25 \text{ }^{\circ}\text{C}$		4.2	4.8	V
		$T_{vj} = 125 \text{ }^{\circ}\text{C}$		5.4	5.9	V
Collector cut-off current	I_{CES}	$V_{CE} = 6500 \text{ V}$, $V_{GE} = 0 \text{ V}$, $T_{vj} = 25 \text{ }^{\circ}\text{C}$			8	mA
		$T_{vj} = 125 \text{ }^{\circ}\text{C}$		35	80	mA
Gate leakage current	I_{GES}	$V_{CE} = 0 \text{ V}$, $V_{GE} = \pm 20 \text{ V}$, $T_{vj} = 125 \text{ }^{\circ}\text{C}$	-500		500	nA
Gate-emitter threshold voltage	$V_{GE(TO)}$	$I_C = 160 \text{ mA}$, $V_{CE} = V_{GE}$, $T_{vj} = 25 \text{ }^{\circ}\text{C}$	6	7.4	8	V
Gate charge	Q_{ge}	$I_C = 400 \text{ A}$, $V_{CE} = 3600 \text{ V}$, $V_{GE} = -15 \text{ V} \dots 15 \text{ V}$		5.3		μC
Input capacitance	C_{ies}	$V_{CE} = 25 \text{ V}$, $V_{GE} = 0 \text{ V}$, $f = 1 \text{ MHz}$, $T_{vj} = 25 \text{ }^{\circ}\text{C}$		95.3		nF
Output capacitance	C_{oes}			4.41		
Reverse transfer capacitance	C_{res}			0.85		
Turn-on delay time	$t_{d(on)}$	$V_{CC} = 3600 \text{ V}$, $T_{vj} = 25 \text{ }^{\circ}\text{C}$		700		ns
		$I_C = 400 \text{ A}$, $T_{vj} = 125 \text{ }^{\circ}\text{C}$		630		
Rise time	t_r	$R_G = 5.6 \text{ } \Omega$, $T_{vj} = 25 \text{ }^{\circ}\text{C}$		250		ns
		$V_{GE} = \pm 15 \text{ V}$, $T_{vj} = 125 \text{ }^{\circ}\text{C}$		220		
Turn-off delay time	$t_{d(off)}$	$L_{\sigma} = 280 \text{ nH}$, inductive load, $T_{vj} = 25 \text{ }^{\circ}\text{C}$		1410		ns
		$T_{vj} = 125 \text{ }^{\circ}\text{C}$		1700		
Fall time	t_f	$V_{CC} = 3600 \text{ V}$, $T_{vj} = 25 \text{ }^{\circ}\text{C}$		650		ns
		$I_C = 400 \text{ A}$, $T_{vj} = 125 \text{ }^{\circ}\text{C}$		980		
Turn-on switching energy	E_{on}	$R_G = 5.6 \text{ } \Omega$, $T_{vj} = 25 \text{ }^{\circ}\text{C}$		2250		mJ
		$L_{\sigma} = 280 \text{ nH}$, inductive load, $T_{vj} = 125 \text{ }^{\circ}\text{C}$		2800		
Turn-off switching energy	E_{off}	$V_{CC} = 3600 \text{ V}$, $I_C = 400 \text{ A}$, $T_{vj} = 25 \text{ }^{\circ}\text{C}$		1340		mJ
		$V_{GE} = \pm 15 \text{ V}$, $R_G = 5.6 \text{ } \Omega$, $T_{vj} = 125 \text{ }^{\circ}\text{C}$		2120		
Short circuit current	I_{SC}	$t_{psc} \leq 10 \text{ } \mu\text{s}$, $V_{GE} = 15 \text{ V}$, $T_{vj} = 125 \text{ }^{\circ}\text{C}$, $V_{CC} = 4400 \text{ V}$, $V_{CEM \text{ CHIP}} \leq 6500 \text{ V}$		1800		A
Module stray inductance	$L_{\sigma \text{ CE}}$			20		nH
Resistance, terminal-chip	$R_{CC'+EE'}$	$T_C = 25 \text{ }^{\circ}\text{C}$		0.1		m Ω
		$T_C = 125 \text{ }^{\circ}\text{C}$		0.15		

³⁾ Characteristic values according to IEC 60747 – 9⁴⁾ Collector-emitter saturation voltage is given at chip level

Diode characteristic values ⁵⁾

Parameter	Symbol	Conditions	min	typ	max	Unit
Forward voltage ⁶⁾	V _F	I _F = 400 A	T _{vj} = 25 °C	3.2	3.8	V
			T _{vj} = 125 °C	3.4	4.0	
Reverse recovery current	I _{rr}	V _{CC} = 3600 V, I _F = 400 A, V _{GE} = ±15 V, R _G = 5.6 Ω L _σ = 280 nH inductive load	T _{vj} = 25 °C	510		A
	T _{vj} = 125 °C		680			
Recovered charge	Q _{rr}		T _{vj} = 25 °C	450		μC
			T _{vj} = 125 °C	770		
Reverse recovery time	t _{rr}		T _{vj} = 25 °C	1840		ns
			T _{vj} = 125 °C	2120		
Reverse recovery energy	E _{rec}		T _{vj} = 25 °C	670		mJ
			T _{vj} = 125 °C	1380		

⁵⁾ Characteristic values according to IEC 60747 – 2

⁶⁾ Forward voltage is given at chip level

Package properties ⁷⁾

Parameter	Symbol	Conditions	min	typ	max	Unit
IGBT thermal resistance junction to case	$R_{th(j-c)IGBT}$				0.016	K/W
Diode thermal resistance junction to case	$R_{th(j-c)DIODE}$				0.032	K/W
IGBT thermal resistance ²⁾ case to heatsink	$R_{th(c-s)IGBT}$	IGBT per switch, λ grease = $1\text{W/m} \times \text{K}$		0.012		K/W
Diode thermal resistance ⁷⁾ case to heatsink	$R_{th(c-s)DIODE}$	Diode per switch, λ grease = $1\text{W/m} \times \text{K}$		0.024		K/W
Partial discharge extinction voltage	V_e	$f = 50 \text{ Hz}$, $Q_{PD} \leq 10\text{pC}$ (acc. to IEC 61287)	5100			V
Comparative tracking index	CTI		≥ 600			


²⁾ For detailed mounting instructions refer to ABB Document No. 5SYA2039

Mechanical properties ⁷⁾


Parameter	Symbol	Conditions	min	typ	max	Unit
Dimensions	$L \times W \times H$	Typical , see outline drawing	$130 \times 140 \times 48$			mm
Clearance distance in air	d_a	according to IEC 60664-1 and EN 50124-1	Term. to base:	40		mm
			Term. to term:	26		
Surface creepage distance	d_s	according to IEC 60664-1 and EN 50124-1	Term. to base:	64		mm
			Term. to term:	56		
Mass	m			1150		g

⁷⁾ Package and mechanical properties according to IEC 60747 – 15

Electrical configuration



Outline drawing ²⁾



Note: all dimensions are shown in mm

²⁾ For detailed mounting instructions refer to ABB Document No. 5SYA2039

This is an electrostatic sensitive device, please observe the international standard IEC 60747-1, chap. IX.

This product has been designed and qualified for Industrial Level.




Fig. 1 Typical on-state characteristics, chip level




Fig. 2 Typical transfer characteristics, chip level




Fig. 3 Typical output characteristics, chip level




Fig. 4 Typical output characteristics, chip level




Fig. 5 Typical switching energies per pulse vs collector current




Fig. 6 Typical switching energies per pulse vs gate resistor




Fig. 7 Typical switching times vs collector current




Fig. 8 Typical switching times vs gate resistor




Fig. 9 Typical capacitances
vs collector-emitter voltage




Fig. 10 Typical gate charge characteristics




Fig. 11 Turn-off safe operating area (RBSOA)




Fig. 12 Typical reverse recovery characteristics vs forward current




Fig. 13 Typical reverse recovery characteristics vs di/dt




Fig. 14 Typical diode forward characteristics, chip level




Fig. 15 Safe operating area diode (SOA)




Fig. 16 Thermal impedance vs time

Analytical function for transient thermal impedance:

$$Z_{th(j-c)}(t) = \sum_{i=1}^n R_i (1 - e^{-t/\tau_i})$$

	i	1	2	3	4	5
IGBT	$R_i(K/kW)$	12.75	2.99			
	$\tau_i(ms)$	151	5.84			
DIODE	$R_i(K/kW)$	25.5	6.3			
	$\tau_i(ms)$	144	5.83			

For detailed information refer to:

- 5SYA 2042-02 Failure rates of HiPak modules due to cosmic rays
- 5SYA 2043-01 Load – cycle capability of HiPaks
- 5SZK 9120-00 Specification of environmental class for HiPak

ABB Switzerland Ltd, Semiconductors reserves the right to change specifications without notice.



ABB Switzerland Ltd
Semiconductors
Fabrikstrasse 3
CH-5600 Lenzburg, Switzerland

Telephone +41 (0)58 586 1419
Fax +41 (0)58 586 1306
Email abbsem@ch.abb.com
Internet www.abb.com/semiconductors