

查询B43858C1336M012供应商



捷多邦，专业PCB打样工厂

，24小时加急出货

## Aluminum electrolytic capacitors

### Single-ended capacitors

Series/Type: B43858

Date: December 2006

© EPCOS AG 2007. Reproduction, publication and dissemination of this publication, enclosures hereto and the information contained therein without EPCOS' prior express consent is prohibited.

**Single-ended capacitors****B43858****High ripple current – 105 °C****Long-life grade capacitors  
for electronic ballasts****Applications**

- Electronic ballasts
- Power supplies

**Features**

- High ripple current capability at high frequency
- Long useful life (5000 h/105 °C)
- Good electrical characteristics

**Construction**


- Radial leads
- Charge-discharge proof, polar
- Aluminum case with insulating sleeve
- Minus pole marking on the insulating sleeve
- Case with safety vent

**Delivery mode**

Terminal configurations and packing:

- Bulk
- Taped, Ammo pack
- Cut
- Kinked
- PAPR (protection against polarity reversal):  
crimped leads, J leads, bent leads

Refer to chapter "Single-ended capacitors – Taping, packing and lead configurations" for further details and ordering example.





B43858

High ripple current – 105 °C

**Specifications and characteristics in brief**


Rated voltage $V_R$	160 ... 450 V DC								
Surge voltage $V_S$	$1.1 \cdot V_R$								
Rated capacitance $C_R$	2.2 ... 330 $\mu\text{F}$								
Capacitance tolerance	$\pm 20\% \triangleq M$								
Dissipation factor $\tan \delta$ (20 °C, 120 Hz)	$V_R \leq 350$ V DC: $\tan \delta = 0.20$ $V_R \geq 400$ V DC: $\tan \delta = 0.24$								
Leakage current $I_{\text{leak}}$ (20 °C, 5 min)	$I_{\text{leak}} = 0.03 \mu\text{A} \cdot \left( \frac{C_R}{\mu\text{F}} \cdot \frac{V_R}{V} \right) + 15 \mu\text{A}$								
Self-inductance ESL	Diameter (mm)	$\leq 12.5$	16	18	20				
	ESL (nH)	20	26	34	38				
Useful life $105$ °C, $V_R$ , $I_{\text{AC},R}$ $40$ °C, $V_R$ , $1.6 \cdot I_{\text{AC},R}$	$> 5000$ h $> 400000$ h								
Requirements	$\Delta C/C$	$\leq \pm 50\%$ of initial value							
	$\tan \delta$	$\leq$ 3 times initial specified limit							
Voltage endurance test $105$ °C, $V_R$	$I_{\text{leak}}$	$\leq$ initial specified limit							
	$5000$ h								
Post test requirements	$\Delta C/C$	$\leq \pm 25\%$ of initial value							
	$\tan \delta$	$\leq$ 2 times initial specified limit							
Vibration resistance test	$I_{\text{leak}}$	$\leq$ initial specified limit							
	To IEC 60068-2-6, test Fc: Displacement amplitude 0.75 mm, frequency range 10 ... 2000 Hz, acceleration max. 20 g, duration $3 \times 2$ h. Capacitor rigidly clamped by the aluminum case.								
IEC climatic category	To IEC 60068-1: $V_R \leq 250$ V: 40/105/56 (-40 °C/+105 °C/56 days damp heat test) $V_R \geq 350$ V: 25/105/56 (-25 °C/+105 °C/56 days damp heat test)								
	IEC 60384-4								

**B43858****High ripple current – 105 °C**

### Dimensional drawings


#### With stand-off rubber seal

Diameters (mm): 10, 12.5, 16, 18



#### With flat rubber seal

Diameter (mm): 20



### Dimensions and weights

Dimensions (mm)				Approx. weight g
d +0.5	l	a ±0.5	b	
10	12.5 +1.0	5.0	0.60 ±0.05	1.6
10	16 +1.0	5.0	0.60 ±0.05	1.9
10	20 +2.0	5.0	0.60 ±0.05	2.6
12.5	20 +2.0	5.0	0.60 ±0.05	3.6
12.5	25 +2.0	5.0	0.60 ±0.05	4.5
16	20 +2.0	7.5	0.80 ±0.05	5.5
16	25 +2.0	7.5	0.80 ±0.05	7.5
16	31.5 +2.0	7.5	0.80 ±0.05	7.8
18	31.5 +2.0	7.5	0.80 ±0.1	11.0
18	35 +2.0	7.5	0.80 ±0.1	13.0
18	40 +2.0	7.5	0.80 ±0.1	16.0
20	35 +2.0	10.0	1.0 ±0.1	18.0
20	40 +2.0	10.0	1.0 ±0.1	20.0



B43858

High ripple current – 105 °C



## Overview of available types

$V_R$ (V DC)	160	200	250	350	400	450
Case dimensions $d \times l$ (mm)						
$C_R$ ( $\mu$ F)						
2.2				10 $\times$ 12.5	10 $\times$ 12.5	10 $\times$ 12.5
3.3				10 $\times$ 16	10 $\times$ 16	10 $\times$ 16
4.7				10 $\times$ 16	10 $\times$ 16	10 $\times$ 16
6.8				10 $\times$ 16	10 $\times$ 16	10 $\times$ 20
10		10 $\times$ 16	10 $\times$ 16	10 $\times$ 20	10 $\times$ 20	12.5 $\times$ 20
22	10 $\times$ 16	10 $\times$ 16	10 $\times$ 20	12.5 $\times$ 25	12.5 $\times$ 25	16 $\times$ 25
33	10 $\times$ 20	10 $\times$ 20	12.5 $\times$ 20	16 $\times$ 20	16 $\times$ 25	16 $\times$ 31.5
47	12.5 $\times$ 20	12.5 $\times$ 20	12.5 $\times$ 25	16 $\times$ 31.5	16 $\times$ 31.5	18 $\times$ 31.5
68	12.5 $\times$ 25	16 $\times$ 20	16 $\times$ 25	18 $\times$ 31.5	18 $\times$ 40	18 $\times$ 40
100	16 $\times$ 25	16 $\times$ 25	16 $\times$ 31.5	18 $\times$ 40	20 $\times$ 40	
220	18 $\times$ 31.5	18 $\times$ 35	18 $\times$ 40			
330	20 $\times$ 35					

Other voltage and capacitance ratings are available upon request.

## Technical data and ordering codes

$C_R$ 120 Hz 20 °C $\mu$ F	Case dimensions $d \times l$ mm	$ESR_{max}$ 120 Hz –25 °C $\Omega$	$ESR_{max}$ 120 Hz 20 °C $\Omega$	$Z_{max}$ 100 kHz 20 °C $\Omega$	$I_{AC,R}$ 100 kHz 105 °C mA	$I_{AC,max}$ 100 kHz 85 °C mA	Ordering code (composition see below)
$V_R = 160$ V DC							
22	10 $\times$ 16	528	15.07	5.00	420	714	B43858C1226M***
33	10 $\times$ 20	352	10.05	1.50	540	918	B43858C1336M***
47	12.5 $\times$ 20	247	7.05	1.05	650	1105	B43858C1476M***
68	12.5 $\times$ 25	171	4.88	0.81	900	1530	B43858C1686M***
100	16 $\times$ 25	116	3.32	0.68	1100	1870	B43858C1107M***
220	18 $\times$ 31.5	53	1.51	0.25	1320	2244	B43858C1227M***
330	20 $\times$ 35	35	1.00	0.20	1800	3060	B43858C1337M***

## Composition of ordering code

\*\*\* = Version

000 = for standard leads, bulk

001 = for kinked leads, bulk (for  $\varnothing \geq 10$  mm)

002 = for cut leads, bulk (for  $\varnothing \geq 10$  mm)

003 = for crimped leads, blister (for  $\varnothing \geq 16$  mm)

004 = for J leads, blister (from  $d \times l = 10 \times 12.5$  mm to  $16 \times 31.5$  mm)

008 = for taped leads, Ammo pack, lead spacing  $F = 5$  mm (from  $d \times l = 10 \times 12.5$  mm to  $12.5 \times 25$  mm)

009 = for taped leads, Ammo pack, lead spacing  $F = 7.5$  mm (from  $d \times l = 16 \times 20$  mm to  $18 \times 31.5$  mm)

**B43858****High ripple current – 105 °C****Technical data and ordering codes**

$C_R$ 120 Hz 20 °C $\mu F$	Case dimensions $d \times l$ mm	$ESR_{max}$ 120 Hz –25 °C $\Omega$	$ESR_{max}$ 120 Hz 20 °C $\Omega$	$Z_{max}$ 100 kHz 20 °C $\Omega$	$I_{AC,R}$ 100 kHz 105 °C mA	$I_{AC,max}$ 100 kHz 85 °C mA	Ordering code (composition see below)
-------------------------------------	--	---	--	---	---------------------------------------	--	---

 $V_R = 200$  V DC

10	10 × 16	1161	33.16	4.00	200	340	B43858C2106M***
22	10 × 16	528	15.07	1.50	470	799	B43858C2226M***
33	10 × 20	352	10.05	1.40	500	850	B43858C2336M***
47	12.5 × 20	247	7.05	1.05	780	1326	B43858C2476M***
68	16 × 20	171	4.88	0.75	850	1445	B43858C2686M***
100	16 × 25	116	3.32	0.68	1250	2125	B43858C2107M***
220	18 × 35	53	1.51	0.10	1390	2363	B43858C2227M***

 $V_R = 250$  V DC

10	10 × 16	1161	33.16	4.00	280	476	B43858H2106M***
22	10 × 20	528	15.07	1.50	510	867	B43858H2226M***
33	12.5 × 20	352	10.05	1.40	600	1020	B43858H2336M***
47	12.5 × 25	247	7.05	1.05	700	1190	B43858H2476M***
68	16 × 25	171	4.88	0.75	1150	1955	B43858H2686M***
100	16 × 31.5	116	3.32	0.62	1350	2295	B43858H2107M***
220	18 × 40	53	1.51	0.10	1460	2482	B43858H2227M***

 $V_R = 350$  V DC

2.2	10 × 12.5	6330	180.86	6.00	100	170	B43858C4225M***
3.3	10 × 16	4220	120.58	4.00	130	221	B43858C4335M***
4.7	10 × 16	2963	84.66	3.00	180	306	B43858C4475M***
6.8	10 × 16	2048	58.51	2.70	220	374	B43858C4685M***
10	10 × 20	1393	39.79	2.00	300	510	B43858C4106M***
22	12.5 × 25	633	18.09	1.50	560	952	B43858C4226M***
33	16 × 20	422	12.06	0.80	580	986	B43858C4336M***
47	16 × 31.5	296	8.47	0.65	1000	1700	B43858C4476M***
68	18 × 31.5	205	5.85	0.50	1200	2040	B43858C4686M***
100	18 × 40	139	3.98	0.40	1450	2465	B43858C4107M***

**Composition of ordering code**

\*\*\* = Version

- 000 = for standard leads, bulk
- 001 = for kinked leads, bulk (for  $\emptyset \geq 10$  mm)
- 002 = for cut leads, bulk (for  $\emptyset \geq 10$  mm)
- 003 = for crimped leads, blister (for  $\emptyset \geq 16$  mm)
- 004 = for J leads, blister (from  $d \times l = 10 \times 12.5$  mm to  $16 \times 31.5$  mm)
- 008 = for taped leads, Ammo pack, lead spacing  $F = 5$  mm (from  $d \times l = 10 \times 12.5$  mm to  $12.5 \times 25$  mm)
- 009 = for taped leads, Ammo pack, lead spacing  $F = 7.5$  mm (from  $d \times l = 16 \times 20$  mm to  $18 \times 31.5$  mm)
- 012 = for bent 90° leads, blister (for  $\emptyset 16$  and  $18$  mm)

**B43858****High ripple current – 105 °C****Technical data and ordering codes**

$C_R$ 120 Hz 20 °C $\mu F$	Case dimensions $d \times l$ mm	ESR <sub>max</sub> 120 Hz –25 °C $\Omega$	ESR <sub>max</sub> 120 Hz 20 °C $\Omega$	$Z_{max}$ 100 kHz 20 °C $\Omega$	$I_{AC,R}$ 100 kHz 105 °C mA	$I_{AC,max}$ 100 kHz 85 °C mA	Ordering code (composition see below)
-------------------------------------	--	--	---	---	---------------------------------------	--	---

 **$V_R = 400$  V DC**

2.2	10 $\times$ 12.5	6330	180.86	7.00	100	170	B43858C9225M***
3.3	10 $\times$ 16	4220	120.58	5.00	130	221	B43858C9335M***
4.7	10 $\times$ 16	2963	84.66	4.00	180	306	B43858C9475M***
6.8	10 $\times$ 16	2048	58.51	3.50	270	459	B43858C9685M***
10	10 $\times$ 20	1393	39.79	2.20	300	510	B43858C9106M***
22	12.5 $\times$ 25	633	18.09	1.70	560	952	B43858C9226M***
33	16 $\times$ 25	422	12.06	0.75	720	1224	B43858C9336M***
47	16 $\times$ 31.5	296	8.47	0.65	980	1666	B43858C9476M***
68	18 $\times$ 40	205	5.85	0.45	1300	2210	B43858C9686M***
100	20 $\times$ 40	139	3.98	0.35	1550	2635	B43858C9107M***

 **$V_R = 450$  V DC**

2.2	10 $\times$ 12.5	6330	180.86	8.50	100	170	B43858C5225M***
3.3	10 $\times$ 16	4220	120.58	8.00	130	221	B43858C5335M***
4.7	10 $\times$ 16	2963	84.66	7.00	180	306	B43858C5475M***
6.8	10 $\times$ 20	2048	58.51	6.00	270	459	B43858C5685M***
10	12.5 $\times$ 20	1393	39.79	4.00	300	510	B43858C5106M***
22	16 $\times$ 25	633	18.09	1.75	600	1020	B43858C5226M***
33	16 $\times$ 31.5	422	12.06	1.40	780	1326	B43858C5336M***
47	18 $\times$ 31.5	296	8.47	1.10	980	1666	B43858C5476M***
68	18 $\times$ 40	205	5.85	0.90	1350	2295	B43858C5686M***

**Composition of ordering code**

\*\*\* = Version


- 000 = for standard leads, bulk
- 001 = for kinked leads, bulk (for  $\emptyset \geq 10$  mm)
- 002 = for cut leads, bulk (for  $\emptyset \geq 10$  mm)
- 003 = for crimped leads, blister (for  $\emptyset \geq 16$  mm)

- 004 = for J leads, blister (from  $d \times l = 10 \times 12.5$  mm to  $16 \times 31.5$  mm)
- 008 = for taped leads, Ammo pack, lead spacing  $F = 5$  mm (from  $d \times l = 10 \times 12.5$  mm to  $12.5 \times 25$  mm)
- 009 = for taped leads, Ammo pack, lead spacing  $F = 7.5$  mm (from  $d \times l = 16 \times 20$  mm to  $18 \times 31.5$  mm)
- 012 = for bent 90° leads, blister (for  $\emptyset 16$  and  $18$  mm)



**B43858**
**High ripple current – 105 °C**

### Useful life

depending on ambient temperature  $T_A$  under ripple current operating conditions<sup>1)</sup>



### Frequency factor of permissible ripple current $I_{AC}$ versus frequency $f$



1) Refer to chapter "General technical information, 5.3 Calculation of useful life" for an explanation on how to interpret the useful life




## Taping, packing and lead configurations

### Taping

Single-ended capacitors are available taped in Ammo pack from diameter 5 to 18 mm as follows:  
 Lead spacing F = 2.5 mm ( $\varnothing$  d = 5 ... 6.3 mm)  
 Lead spacing F = 3.5 mm ( $\varnothing$  d = 8 mm)  
 Lead spacing F = 5.0 mm ( $\varnothing$  d = 5 ... 12.5 mm)  
 Lead spacing F = 7.5 mm ( $\varnothing$  d = 16 ... 18 mm).


### Lead spacing 2.5 mm ( $\varnothing$ d = 5 ... 6.3 mm)

Last 3 digits of ordering code: 007




### Dimensions in mm

$\varnothing$ d	F	H	W	W <sub>0</sub>	W <sub>1</sub>	W <sub>2</sub>	H <sub>0</sub>	P	P <sub>0</sub>	P <sub>1</sub>	I <sub>1</sub>	t	$\Delta h$	D <sub>0</sub>
5	2.5	18.5	18.0	5.5	9.0	1.5	16.0	12.7	12.7	5.1	1.0	0.7	1.0	4.0
6.3														
Tolerance	+0.8 -0.2	$\pm 0.75$	$\pm 0.5$	min.	$\pm 0.5$	max.	$\pm 0.5$	$\pm 1.0$	$\pm 0.2$	$\pm 0.5$	max.	$\pm 0.2$	max.	$\pm 0.2$

**B43858****High ripple current – 105 °C****Lead spacing 3.5 mm ( $\emptyset d = 8$  mm)**


Last 3 digits of ordering code: 006

**Dimensions in mm**


$\emptyset d$	F	H	W	$W_0$	$W_1$	$W_2$	P	$P_0$	$P_1$	$I_1$	t	$\Delta h$	$D_0$
8	3.5	18.5	18.0	12.5	9.0	1.5	12.7	12.7	4.6	1.0	0.7	1.0	4.0
Toler- ance	+0.8 -02	1.0	$\pm 0.5$	min.	$\pm 0.5$	max.	$\pm 1.0$	$\pm 0.2$	$\pm 0.5$	max.	$\pm 0.2$	max.	$\pm 0.2$


**Lead spacing 5.0 mm ( $\varnothing d = 5 \dots 8 \text{ mm}$ )**

Last 3 digits of ordering code: 008


**Lead spacing 5.0 mm ( $\varnothing d = 10 \dots 12.5 \text{ mm}$ )**


Last 3 digits of ordering code: 008


**Dimensions in mm**

$\varnothing d$	F	H	W	$W_0$	$W_1$	$W_2$	$H_0$	P	$P_0$	$P_1$	$I_1$	t	$\Delta h$	$D_0$
5	5.0	18.5	18.0	5.5	9.0	1.5	16.0	12.7	12.7	3.85	1.0	0.7	1.0	4.0
6.3														
8	5.0	20.0	18.0	12.5	9.0	1.5	16.0	12.7	12.7	3.85	1.0	0.7	1.0	4.0
10							—	12.7	12.7	3.85				
12.5							—	15.0	15.0	5.0				
Toler- ance	+0.8 -02	$\pm 0.75$	$\pm 0.5$	min.	$\pm 0.5$	max.	$\pm 0.5$	$\pm 1.0$	$\pm 0.2$	$\pm 0.5$	max.	$\pm 0.2$	max.	$\pm 0.2$

**B43858****High ripple current – 105 °C****Lead spacing 7.5 mm ( $\varnothing d = 16 \dots 18 \text{ mm}$ )**

Last 3 digits of ordering code: 009

**Dimensions in mm**

$\varnothing d$	F	H	W	$W_0$	$W_1$	$W_2$	P	$P_0$	$P_1$	$l_1$	t	$\Delta P$	$\Delta h$	$D_0$
16	7.5	18.5	18.0	12.5	9.0	1.5	30.0	15.0	3.75	1.0	0.7	0	0	4.0
18 <sup>a)</sup>														
Tolerance	$\pm 0.8$	$-0.5$ $+0.75$	$\pm 0.5$	min.	$\pm 0.5$	max.	$\pm 1.0$	$\pm 0.2$	$\pm 0.5$	max.	$\pm 0.2$	$\pm 1.0$	$\pm 1.0$	$\pm 0.2$

\*) Available only for case dimensions 18 × 20, 18 × 25 and 18 × 31.5 mm




**B43858**

**High ripple current – 105 °C**



## Packing units and box dimensions

### Ammo pack



Case size d × l mm	Dimensions (mm)			Packing units pcs.
	A <sub>max</sub>	B <sub>max</sub>	C <sub>max</sub>	
5 × 11	345	55	240	2000
6.3 × 11	345	55	290	2000
8 × 11.5	345	55	240	1000
10 × 12.5	345	55	280	750
10 × 16	345	60	200	500
10 × 20	345	60	200	500
12.5 × 20	345	65	280	500
12.5 × 25	345	65	280	500
12.5 × 25	345	65	280	500
12.5 × 30	345	65	275	500
16 × 20	315	65	275	300
16 × 25	315	65	275	300
16 × 31.5	315	65	275	300
18 × 20	315	65	275	250
18 × 25	315	65	275	250
18 × 31.5	315	65	275	250


**B43858**
**High ripple current – 105 °C**



### Kinked or cut leads

Single-ended capacitors are available with kinked or cut leads. Other lead configurations also available upon request.



### Kinked leads

Last 3 digits of ordering code: 001

#### With stand-off rubber seal



#### With flat rubber seal




Case size $d \times l$ (mm)	Dimensions (mm) $a \pm 0.5$
10 × 20	5.0
12.5 × 20	5.0
12.5 × 25	5.0
12.5 × 30	5.0
12.5 × 35	5.0
12.5 × 40	5.0
16 × 20	7.5
16 × 25	7.5
16 × 31.5	7.5
18 × 20	7.5
18 × 25	7.5
18 × 31.5	7.5
18 × 35	7.5
18 × 40	7.5
20 × 20	10.0
20 × 25	10.0
20 × 40	10.0
22 × 30	10.0
22 × 35	10.0
22 × 40	10.0

**B43858****High ripple current – 105 °C**

### Cut leads


Last 3 digits of ordering code: 002

#### With stand-off rubber seal



KAL1085-I

#### With flat rubber seal



KAL1086-R

Case size $d \times l$ (mm)	Dimensions (mm) $a \pm 0.5$
10 × 12.5	5.0
10 × 16	5.0
10 × 20	5.0
12.5 × 20	5.0
12.5 × 25	5.0
12.5 × 30	5.0
12.5 × 35	5.0
12.5 × 40	5.0
16 × 20	7.5
16 × 25	7.5
16 × 31.5	7.5
18 × 20	7.5
18 × 25	7.5
18 × 31.5	7.5
18 × 35	7.5
18 × 40	7.5
20 × 20	10.0
20 × 25	10.0
20 × 40	10.0


**B43858**
**High ripple current – 105 °C**

### PAPR leads (Protection Against Polarity Reversal)


These lead configurations ensure correct placement of the capacitor on the PCB with regard to polarity. PAPR leads are available for diameters from 10 mm up to 20 mm.

There are three configurations available: Crimped leads, J leads, bent 90° leads


#### Crimped leads

Last 3 digits of ordering code: 003




#### With stand-off rubber seal



#### With flat rubber seal



#### Suggestion for PCB hole diameter



Case size d × l (mm)	Dimensions (mm)					
	B ±0.2	C ±0.5	D ±0.1	E ±0.1	a ±0.5	Øb
16 × 20	1.5	3.0	1.3	0.3	7.5	0.8 ±0.05
16 × 25	1.5	3.0	1.3	0.3	7.5	0.8 ±0.05
16 × 31.5	1.5	3.0	1.3	0.3	7.5	0.8 ±0.05
18 × 20	1.5	3.0	1.3	0.3	7.5	0.8 ±0.1
18 × 25	1.5	3.0	1.3	0.3	7.5	0.8 ±0.1
18 × 31.5	1.5	3.0	1.3	0.3	7.5	0.8 ±0.1
18 × 35	1.5	3.0	1.3	0.3	7.5	0.8 ±0.1
18 × 40	1.5	3.0	1.3	0.3	7.5	0.8 ±0.1
20 × 20	1.5	3.0	1.6	0.3	10.0	1.0 ±0.1
20 × 25	1.5	3.0	1.6	0.3	10.0	1.0 ±0.1
20 × 40	1.5	3.0	1.6	0.3	10.0	1.0 ±0.1




B43858

High ripple current – 105 °C



### J leads


Last 3 digits of ordering code: 004




KAL1091-S-E

### Suggestion for PCB hole diameter

Suggestion for PCB hole diameter,  
wire  $\varnothing 0.6$  mm




Suggestion for PCB hole diameter,  
wire  $\varnothing 0.8$  mm



Case size $d \times l$ (mm)	Dimensions (mm)				
	$C \pm 0.5$	$E \pm 0.5$	$J \pm 0.2$	$a \pm 0.5$	$\varnothing b$
10 × 12.5	3.2	0.7	1.2	5.0	$0.6 \pm 0.05$
10 × 16	3.2	0.7	1.2	5.0	$0.6 \pm 0.05$
10 × 20	3.2	0.7	1.2	5.0	$0.6 \pm 0.05$
12.5 × 20	3.2	0.7	1.2	5.0	$0.6 \pm 0.05$
12.5 × 25	3.2	0.7	1.2	5.0	$0.6 \pm 0.05$
16 × 20	3.5	0.7	1.6	7.5	$0.8 \pm 0.05$
16 × 25	3.5	0.7	1.6	7.5	$0.8 \pm 0.05$
16 × 31.5	3.5	0.7	1.6	7.5	$0.8 \pm 0.05$
18 × 20	3.5	0.7	1.6	7.5	$0.8 \pm 0.1$
18 × 25	3.5	0.7	1.6	7.5	$0.8 \pm 0.1$
18 × 31.5	3.5	0.7	1.6	7.5	$0.8 \pm 0.1$
18 × 35	3.5	0.7	1.6	7.5	$0.8 \pm 0.1$

**B43858****High ripple current – 105 °C****Bent 90° leads for horizontal mounting pinning**

Last 3 digits of ordering code: 012



KAL1094-H-E

Case size $d \times l$ (mm)	Dimensions (mm)				
	$C \pm 0.5$	$E \pm 0.5$	$F \pm 0.5$	$a \pm 0.5$	$\emptyset b$
16 × 20	4.0	4.0	12.0	7.5	$0.8 \pm 0.05$
16 × 25	4.0	4.0	12.0	7.5	$0.8 \pm 0.05$
16 × 31.5	4.0	4.0	12.0	7.5	$0.8 \pm 0.05$
18 × 20	4.0	4.0	13.0	7.5	$0.8 \pm 0.1$
18 × 25	4.0	4.0	13.0	7.5	$0.8 \pm 0.1$
18 × 31.5	4.0	4.0	13.0	7.5	$0.8 \pm 0.1$
18 × 35	4.0	4.0	13.0	7.5	$0.8 \pm 0.1$
18 × 40	4.0	4.0	13.0	7.5	$0.8 \pm 0.1$

Bent leads for diameter 12.5 mm available upon request.



B43858

High ripple current – 105 °C

**Overview of packing units and code numbers for case sizes 5 × 11 ... 16 × 31.5**

					PAPR				
Case size d × l mm	Stand- ard, bulk pcs.	Taped, Ammo pack pcs.	Kinked leads, bulk pcs.	Cut leads, bulk pcs.	Crimped leads pcs.	J leads pcs.	Bent 90° leads, blister pcs.		
5 × 11	2000	2000	—	—	—	—			
6.3 × 11	2500	2000	—	—	—	—			
8 × 11.5	1000	1000	—	—	—	—			
10 × 12.5	1000	750	—	1000	—	675			
10 × 16	100	500	—	1000	—	675			
10 × 20	500	500	500	500	—	500			
12.5 × 20	350	500	350	350	—	300	<sup>1)</sup>		
12.5 × 25	250	500	500	500	—	225	<sup>1)</sup>		
12.5 × 30	200	500	175	175	—	180	<sup>1)</sup>		
12.5 × 35	175	-	175	175	—	150	<sup>1)</sup>		
12.5 × 40	175	-	175	175	—	150	<sup>1)</sup>		
16 × 20	250	300	200	200	200	200	120		
16 × 25	250	300	200	200	200	200	120		
16 × 31.5	200	300	250	250	344	344	120		
The last three digits of the complete ordering code state the lead configuration	000	Code	F (mm)	d (mm)	001	002	003	004	012
		006	3.5	8					
		007	2.5	5...6.3					
		008	5	5...12.5					
		009	7.5	16...18					

**B43858****High ripple current – 105 °C****Overview of packing units and code numbers for case sizes 18 × 20 ... 25 × 40**

Case size d × l	Stan- dard, bulk	Taped, Ammo pack		Kinked leads, bulk	Cut leads, bulk	PAPR			
		pcs.	pcs.			pcs.	pcs.	pcs.	
18 × 20	175	250		175	175	200	200	120	
18 × 25	150	250		150	150	200	200	120	
18 × 31.5	100	250		100	100	150	150	120	
18 × 35	100	—		100	100	150	150	150	
18 × 40	125	—		100	100	120	—	72	
20 × 20	125	—		125	125	200	—	—	
20 × 25	125	—		125	125	200	—	—	
20 × 30	100	—		100	100	120	—	—	
20 × 35	100	—		100	100	120	—	—	
20 × 40	100	—		100	100	120	—	—	
22 × 30	80	—		100	100	—	—	—	
22 × 35	80	—		100	100	—	—	—	
22 × 40	80	—		100	100	—	—	—	
25 × 40	40	—		100	—	—	—	—	
The last three digits of the complete ordering code state the lead configuration	000	Code	F (mm)	d (mm)	001	002	003	004	012
		007	2.5	4...6.3					
		008	5	6.3...12.5					
		009	7.5	16...18					



**B43858**

**High ripple current – 105 °C**



## **Cautions and warnings**

### **Personal safety**

The electrolytes used by EPCOS have not only been optimized with a view to the intended application, but also with regard to health and environmental compatibility. They do not contain any solvents that are detrimental to health, e.g. dimethyl formamide (DMF) or dimethyl acetamide (DMAC).

Furthermore, part of the high-voltage electrolytes used by EPCOS are self-extinguishing. They contain flame-retarding substances which will quickly extinguish any flame that may have been ignited.

As far as possible, EPCOS does not use any dangerous chemicals or compounds to produce operating electrolytes. However, in exceptional cases, such materials must be used in order to achieve specific physical and electrical properties because no safe substitute materials are currently known. However, the amount of dangerous materials used in our products has been limited to an absolute minimum. Nevertheless, the following rules should be observed when handling Al electrolytic capacitors:

- Any escaping electrolyte should not come into contact with eyes or skin.
- If electrolyte does come into contact with the skin, wash the affected parts immediately with running water. If the eyes are affected, rinse them for 10 minutes with plenty of water. If symptoms persist, seek medical treatment.
- Avoid breathing in electrolyte vapor or mists. Workplaces and other affected areas should be well ventilated. Clothing that has been contaminated by electrolyte must be changed and rinsed in water.

**B43858****High ripple current – 105 °C**

## Product safety

The table below summarize the safety instructions that must be observed without fail. A detailed description can be found in the relevant sections of chapter "General technical information".

Topic	Safety information	Reference Chapter "General technical information"
Polarity	Make sure that polar capacitors are connected with the right polarity.	1 "Basic construction of aluminum electrolytic capacitors"
Reverse voltage	Voltages polarity classes should be prevented by connecting a diode.	3.1.6 "Reverse voltage"
Upper category temperature	Do not exceed the upper category temperature.	7.2 "Maximum permissible operating temperature"
Maintenance	Make periodic inspections of the capacitors. Before the inspection, make sure that the power supply is turned off and carefully discharge the electricity of the capacitors. Do not apply any mechanical stress to the capacitor terminals.	10 "Maintenance"
Mounting position of screw terminal capacitors	Do not mount the capacitor with the terminals (safety vent) upside down.	11.1. "Mounting positions of capacitors with screw terminals"
Mounting of single-ended capacitors	The internal structure of single-ended capacitors might be damaged if excessive force is applied to the lead wires. Avoid any compressive, tensile or flexural stress. Do not move the capacitor after soldering to PC board. Do not pick up the PC board by the soldered capacitor. Do not insert the capacitor on the PC board with a hole space different to the lead space specified.	11.4 "Mounting considerations for single-ended capacitors"
Robustness of terminals	The following maximum tightening torques must not be exceeded when connecting screw terminals: M5: 2 Nm M6: 2.5 Nm	11.3 "Mounting torques"
Soldering	Do not exceed the specified time or temperature limits when soldering.	11.5 "Soldering"



B43858

High ripple current – 105 °C



Topic	Safety information	Reference Chapter "General technical information"
Soldering, cleaning agents	Do not allow halogenated hydrocarbons to come into contact with aluminum electrolytic capacitors.	11.6 "Cleaning agents"
Passive flammability	Avoid external energy, such as fire or electricity.	8.1 "Passive flammability"
Active flammability	Avoid overload of the capacitors.	8.2 "Active flammability"
		Reference Chapter "Capacitors with screw terminals"
Breakdown strength of insulating sleeves	Do not damage the insulating sleeve, especially when ring clips are used for mounting.	"Screw terminals - accessories"



## Important notes

The following applies to all products named in this publication:

1. Some parts of this publication contain **statements about the suitability of our products for certain areas of application**. These statements are based on our knowledge of typical requirements that are often placed on our products in the areas of application concerned. We nevertheless expressly point out that **such statements cannot be regarded as binding statements about the suitability of our products for a particular customer application**. As a rule, EPCOS is either unfamiliar with individual customer applications or less familiar with them than the customers themselves. For these reasons, it is always ultimately incumbent on the customer to check and decide whether an EPCOS product with the properties described in the product specification is suitable for use in a particular customer application.
2. We also point out that **in individual cases, a malfunction of passive electronic components or failure before the end of their usual service life cannot be completely ruled out in the current state of the art, even if they are operated as specified**. In customer applications requiring a very high level of operational safety and especially in customer applications in which the malfunction or failure of a passive electronic component could endanger human life or health (e.g. in accident prevention or life-saving systems), it must therefore be ensured by means of suitable design of the customer application or other action taken by the customer (e.g. installation of protective circuitry or redundancy) that no injury or damage is sustained by third parties in the event of malfunction or failure of a passive electronic component.
3. **The warnings, cautions and product-specific notes must be observed.**
4. In order to satisfy certain technical requirements, **some of the products described in this publication may contain substances subject to restrictions in certain jurisdictions (e.g. because they are classed as "hazardous")**. Useful information on this will be found in our Material Data Sheets on the Internet ([www.epcos.com/material](http://www.epcos.com/material)). Should you have any more detailed questions, please contact our sales offices.
5. We constantly strive to improve our products. Consequently, **the products described in this publication may change from time to time**. The same is true of the corresponding product specifications. Please check therefore to what extent product descriptions and specifications contained in this publication are still applicable before or when you place an order. We also **reserve the right to discontinue production and delivery of products**. Consequently, we cannot guarantee that all products named in this publication will always be available.
6. Unless otherwise agreed in individual contracts, **all orders are subject to the current version of the "General Terms of Delivery for Products and Services in the Electrical Industry" published by the German Electrical and Electronics Industry Association (ZVEI)**.
7. The trade names EPCOS, EPCOS-JONES, BAOKE, Alu-X, CeraDiode, CSSP, MLSC, PhaseCap, PhaseMod, SIFERRIT, SIFI, SIKOREL, SilverCap, SIMID, SIOV, SIP5D, SIP5K, UltraCap, WindCap are **trademarks registered or pending** in Europe and in other countries. Further information will be found on the Internet at [www.epcos.com/trademarks](http://www.epcos.com/trademarks).