

Temperature Measurement

B57560

Glass-Encapsulated Sensors

G 560

Applications

- Automotive electronics
- Industrial electronics
- Home appliances

Features


- Glass-encapsulated, heat-resistive and highly stable
- For temperature measurement up to 300 °C
- Fast response
- Leads: dumet wires (copper-clad FeNi)

Options

Leads: nickel-plated wires

Delivery mode

Bulk



Dimensions
in mm


Climatic category (IEC 60068-1)		55/300/56	
Max. power at 25 °C	P_{25}	50	mW
Resistance tolerance	$\Delta R_N/R_N$	$\pm 1\%, \pm 3\%, \pm 5\%$	
Rated temperature	T_N	25	°C
Dissipation factor (in air)	δ_{th}	approx. 1,3	mW/K
Thermal cooling time constant (in air)	τ_c	approx. 15	s
Heat capacity	C_{th}	approx. 20	mJ/K

R_{25}	No. of R/T characteristic	$B_{25/85}$	$B_{0/100}$	$B_{25/100}$	Ordering code
Ω		K	K	K	
2 k	8401	3420	$3390 \pm 1\%$	3436	B57560G0202+
5 k	8402	3480	$3450 \pm 1\%$	3497	B57560G0502+
10 k	8407	3480	$3450 \pm 1\%$	3497	B57560G0103+
20 k	8415	3992	$3970 \pm 1\%$	4006	B57560G0203+
30 k	8415	3992	$3970 \pm 1\%$	4006	B57560G0303+
50 k	8403	3992	$3970 \pm 1\%$	4006	B57560G0503+
100 k	8404	4066	$4036 \pm 1\%$	4085	B57560G0104+
230 k	8405	4240	$4537 \pm 1\%^{(1)}$	4264	B57560G0234+
1400 k	8406	4557	$5133 \pm 2\%^{(2)}$	4581	B57560G0145+

+ : F000 for $\Delta R_N/R_N = \pm 1\%$;
H000 for $\Delta R_N/R_N = \pm 3\%$;
J000 for $\Delta R_N/R_N = \pm 5\%$;

F002 for $\Delta R_N/R_N = \pm 1\%$ for nickel-plated wires
H002 for $\Delta R_N/R_N = \pm 3\%$ for nickel-plated wires
J002 for $\Delta R_N/R_N = \pm 5\%$ for nickel-plated wires

1) $B_{100/200}$
2) $B_{200/300}$



**Temperature Measurement****B57560****Glass-Encapsulated Sensors****G 560****Reliability data**

Test	Standard	Test conditions	$\Delta R_{25}/R_{25}$ (typical)	Remarks
Storage in dry heat	IEC 60068-2-2	Storage at upper category temperature T: 300 °C t: 1000 h	< 3 %	No visible damage
Storage in damp heat, steady state	IEC 60068-2-3	Temperature of air: 85 °C Relative humidity of air: 85 % Duration: 56 days	< 2 %	No visible damage
Rapid temperature cycling	IEC 60068-2-14	Lower test temperature: – 55 °C Upper test temperature: 200 °C Number of cycles: 1000	< 2 %	No visible damage

Diese Broschüre ersetzt die vorige Ausgabe.

Fragen über Technik, Preise und Liefermöglichkeiten richten Sie bitte an den Ihnen nächstgelegenen oder an unsere Vertriebsgesellschaften im Ausland. Bauelemente können aufgrund technischer Erfordernisse nicht auf Lager gehalten werden. Auskünfte darüber bitten wir unter Angabe des betreffenden Typs ebenfalls über die zuständige Vertriebsgesellschaft zu holen.

Published by EPCOS AG

Corporate Communications, P.O. Box 80 17 09, 81617 Munich, GERMANY

☎ ++49 89 636 09, FAX (0 89) 636-2 26 89

© EPCOS AG 2002. Reproduction, publication and dissemination of this brochure and the information contained herein without EPCOS' prior express consent is prohibited.

Purchase orders are subject to the General Conditions for the Supply of Products and Services of the EPCOS Group, which are recommended by the ZVEI (German Electrical and Electronic Manufacturers' Association), unless otherwise stated.

This brochure replaces the previous edition.

For questions on technology, prices and delivery please contact the Sales Offices of EPCOS AG or the nearest sales representative.

Due to technical requirements components may contain dangerous substances. For information on the handling of these components please also contact one of our Sales Offices.