


US 5A ... US 5M



Surface mount diode

Ultrafast silicon rectifier diodes

US 5A ... US 5M

Forward Current: 5 A

Reverse Voltage: 50 to 1000 V

Features

- Max. solder temperature: 260 °C
- Plastic material has UL classification 94V-0

Mechanical Data


- Plastic case: SMC / DO-214AB
- Weight approx.: 0,21 g
- Terminals: plated terminals solderable per MIL-STD-750
- Mounting position: any
- Standard packaging: 3000 pieces per reel

- 1) Max. temperature of the terminals $T_T = 100\text{ °C}$
- 2) $I_F = 3\text{ A}$, $T_J = 25\text{ °C}$
- 3) $T_A = 25\text{ °C}$
- 4) Mounted on P.C. board with 50 mm² copper pads at each terminal

Type	Polarity color band	Repetitive peak reverse voltage V_{RRM} V	Surge peak reverse voltage V_{RSM} V	Maximum forward voltage $T_J = 25\text{ °C}$ $I_F = 5\text{ A}$ $V_F^{2)}$ V	Maximum reverse recovery time $I_F = 0,5\text{ A}$ $I_R = 1\text{ A}$ $I_{RR} = 0,25\text{ A}$ t_{rr} ns
US 5A	-	50	50	1	75
US 5B	-	100	100	1	75
US 5D	-	200	200	1	75
US 5G	-	400	400	1,3	75
US 5J	-	600	600	1,7	100
US 5K	-	800	800	1,7	100
US 5M	-	1000	1000	1,7	100

Absolute Maximum Ratings		$T_A = 25\text{ °C}$, unless otherwise specified	
Symbol	Conditions	Values	Units
I_{FAV}	Max. averaged fwd. current, R-load, $T_T = 100\text{ °C}^1)$	5	A
I_{FRM}	Repetitive peak forward current $f > 15\text{ Hz}^1)$	15	A
I_{FSM}	Peak fwd. surge current 50 Hz half sinus-wave ³⁾	150	A
I^2t	Rating for fusing, $t < 10\text{ ms}^3)$	110	A ² s
R_{thA}	Max. thermal resistance junction to ambient ⁴⁾	50	K/W
R_{thT}	Max. thermal resistance junction to terminals	10	K/W
T_J	Operating junction temperature	- 50 ... + 150	°C
T_s	Storage temperature	- 50 ... + 150	°C

Characteristics		$T_A = 25\text{ °C}$, unless otherwise specified	
Symbol	Conditions	Values	Units
I_R	Maximum leakage current, $T_J = 25\text{ °C}$; $V_R = V_{RRM}$	<10	µA
	$T_J = 100\text{ °C}$; $V_R = V_{RRM}$	<300	µA
C_J	Typical junction capacitance (at MHz and applied reverse voltage of V)	-	pF
Q_{rr}	Reverse recovery charge ($U_R = V$; $I_F = A$; $dI_F/dt = A/ms$)	-	µC
E_{RSM}	Non repetitive peak reverse avalanche energy ($I_R = mA$; $T_J = \text{°C}$; inductive load switched off)	-	mJ



case: SMC / DO-214AB

US 5A ... US 5M




Fig. 1 Forward characteristics (typical values)




Fig. 2 Rated forward current vs. temp. of the terminals⁴⁾