



UNISONIC TECHNOLOGIES CO., LTD
UP1855
PNP SILICON TRANSISTOR
HIGH CURRENT TRANSISTOR
■ FEATURES

- * High current switching
- * Low $V_{CE(SAT)}$
- * High h_{FE}



SOT-223

*Pb-free plating product number: UP1855L

■ ORDERING INFORMATION

Order Number		Package	Pin Assignment			Packing
Normal	Lead Free Plating		1	2	3	
UP1855-x-AA3-R	UP1855L-x-AA3-R	SOT-223	B	C	E	Tape Reel

UP1855L-x-AA3-R



- (1)Packing Type
- (2)Package Type
- (3)Rank
- (4)Lead Plating

- (1) R: Tape Reel
- (2) AA3: SOT-223
- (3) refer to Classification of h_{FE2}
- (4) L: Lead Free Plating, Blank: Pb/Sn



UP1855

PNP SILICON TRANSISTOR

■ ABSOLUTE MAXIMUM RATINGS (Ta = 25°C)

PARAMETER	SYMBOL	RATINGS	UNIT
Collector -Base Voltage	V _{CBO}	-180	V
Collector -Emitter Voltage	V _{CEO}	-140	V
Emitter -Base Voltage	V _{EBO}	-6	V
Collector Current (Pulse)	I _{CM}	-10	A
Collector Current (DC)	I _C	-4	A
Power Dissipation	P _D	1	W
Junction Temperature	T _J	+150	°C
Storage Temperature	T _{STG}	-40 ~ +150	°C

Note Absolute maximum ratings are those values beyond which the device could be permanently damaged.

Absolute maximum ratings are stress ratings only and functional device operation is not implied.

■ ELECTRICAL CHARACTERISTICS (Ta = 25°C, unless otherwise specified)







PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Collector-Base Breakdown Voltage	BV _{CBO}	I _C = -100μA	-180	-210		V
Collector-Emitter Breakdown Voltage	BV _{CEO}	I _C = -10mA	-140	-170		V
Emitter-Base Breakdown Voltage	BV _{EBO}	I _E = -100μA	-6	-8		V
Collector Cut-off Current	I _{CBO}	V _{CB} = -150V V _{CB} = -150V, Ta = 100°C			-50 -1	nA μA
Emitter Cut-off Current	I _{EBO}	V _{EB} = -6V			-10	nA
Collector-Emitter Saturation Voltage	V _{CE(SAT)}	I _C = -100mA, I _B = -5mA I _C = -500mA, I _B = -50mA I _C = -1A, I _B = -100mA I _C = -3A, I _B = -300mA		-30 -70 -110 -275	-60 -120 -150 -370	mV
Base-Emitter Saturation Voltage	V _{BE(SAT)}	I _C = -3A, I _B = -300mA		-970	-1110	mV
Base-Emitter Turn-On Voltage	V _{BE(ON)}	I _C = -3A, V _{CE} = -5V		-830	-950	mV
DC Current Gain	h _{FE1}	I _C = -10mA, V _{CE} = -5V	100	200		
	h _{FE2}	I _C = -1A, V _{CE} = -5V	100		300	
	h _{FE3}	I _C = -3A, V _{CE} = -5V	75	140		
	h _{FE4}	I _C = -10A, V _{CE} = -5V		10		
Transition Frequency	f _T	I _C = -100mA, V _{CE} = -10V, f = 50MHz		110		MHz
Output Capacitance	C _{ob}	V _{CB} = -20V, f = 1MHz		40		pF
Switching Times	t _{ON}	I _C = -1A, V _{CC} = -50V		68		ns
	t _{OFF}	I _{B1} = -100mA, I _{B2} = 100mA		1030		ns

Note: Pulse test: t_p ≤ 300μs, Duty cycle ≤ 2%

■ CLASSIFICATION OF h_{FE2}

RANK	A	B
RANGE	100 ~ 200	180 ~ 300

■ TYPICAL CHARACTERISTICS



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.