



# U0402FC3.3C thru U0402FC36C

## UNBUMPED FLIP CHIP ARRAY

### APPLICATIONS

- ✓ Cellular Phones
- ✓ MCM Boards
- ✓ Wireless Communication Circuits
- ✓ IR LEDs
- ✓ SMART & PCMCIA Cards

### IEC COMPATIBILITY (EN61000-4)

- ✓ 61000-4-2 (ESD): Air - 15kV, Contact - 8kV
- ✓ 61000-4-4 (EFT): 40A - 5/50ns

### FEATURES


- ✓ ESD Protection > 25 kilovolts
- ✓ Available in Multiple Voltage Types Ranging From 3.3V to 36V
- ✓ 250 Watts Peak Pulse Power per Line (tp = 8/20µs)
- ✓ Bidirectional Configuration & Monolithic Structure
- ✓ Protects 1 Line
- ✓ RoHS Compliant

### MECHANICAL CHARACTERISTICS

- ✓ Standard EIA Chip Size: 0402
- ✓ Weight 0.73 milligrams (Approximate)
- ✓ Solder Reflow Temperature:
  - Tin-Lead - Sn/Pb: 240-245°C
  - Lead-Free: 260-270°C
- ✓ Flammability Rating UL 94V-0
- ✓ 8mm Plastic & Paper Tape and Reel Per EIA Standard 481
- ✓ Device Marking On Reel



### PIN CONFIGURATION



# U0402FC3.3C thru U0402FC36C

## DEVICE CHARACTERISTICS

### MAXIMUM RATINGS @ 25°C Unless Otherwise Specified

PARAMETER	SYMBOL	VALUE	UNITS
Peak Pulse Power ( $t_p = 8/20\mu s$ ) - See Figure 1	$P_{PP}$	250	Watts
Operating Temperature	$T_J$	-55°C to 150°C	°C
Storage Temperature	$T_{STG}$	-55°C to 150°C	°C


### ELECTRICAL CHARACTERISTICS PER LINE @ 25°C Unless Otherwise Specified

PART NUMBER (See Note 1)	RATED STAND-OFF VOLTAGE  $V_{WM}$ VOLTS	MINIMUM BREAKDOWN VOLTAGE	MAXIMUM CLAMPING VOLTAGE (See Fig. 2)	MAXIMUM CLAMPING VOLTAGE (See Fig. 2)	MAXIMUM LEAKAGE CURRENT (See Note 2)	TYPICAL CAPACITANCE  @0V, 1 MHz C pF
		@ 1mA $V_{(BR)}$ VOLTS	@ $I_p = 1A$ $V_C$ VOLTS	@ 8/20 $\mu s$ $V_C @ I_{PP}$	@ $V_{WM}$ $I_D$ $\mu A$	
U0402FC3.3C	3.3	4.0	7.0	12.5V @ 20A	75*	150
U0402FC05C	5.0	6.0	9.8	14.7V @ 17A	10**	100
U0402FC08C	8.0	8.5	13.4	19.2V @ 13A	10***	75
U0402FC12C	12.0	13.3	19.0	29.7V @ 9.0A	1	50
U0402FC15C	15.0	16.7	24.0	35.7V @ 7.0A	1	40
U0402FC24C	24.0	26.7	43.0	55.0V @ 5.0A	1	30
U0402FC36C	36.0	40.0	64.0	84.0V @ 3.0A	1	25


**Note 1:** All devices are bidirectional. Electrical characteristics apply in both directions.

**Note 2:** \*Maximum leakage current < 5 $\mu A$  @ 2.8V. \*\*Maximum leakage current < 500nA @ 3.3V. \*\*\*Maximum leakage current < 200nA @ 5V.




**FIGURE 1  
PEAK PULSE POWER VS PULSE TIME**



**FIGURE 2  
PULSE WAVE FORM**



GRAPHS





**APPLICATION INFORMATION**

PRINTED CIRCUIT BOARD RECOMMENDATIONS	
PARAMETER	VALUE
Pad Size on PCB	0.275mm
Pad Shape	Round
Pad Definition	Non-Solder Mask Defined Pads
Solder Mask Opening	0.325mm Round
Solder Stencil Thickness	0.150mm
Solder Stencil Aperture Opening (laser cut, 5% tapered walls)	0.330mm Round
Solder Paste Type	No Clean
Pad Protective Finish	OSP(Entek Cu Plus 106A)
Tolerance - Edge To Corner Ball	±50µm
Solder Ball Side Coplanarity	±20µm
Maximum Dwell Time Above Liquidous (183°C)	60 Seconds
Soldering Maximum Temperature	270°C

REQUIREMENTS
<p><b>Temperature:</b>  <math>T_P</math> for Lead-Free (SnAgCu): 260-265°C  <math>T_P</math> for Tin-Lead: 240-245°C            Preheat time and temperature depends on solder paste and flux activation temperature, component size, weight, surface area &amp; plating.</p>

**RECOMMENDED NON-SOLDER MASK DEFINED PAD ILLUSTRATION**



# U0402FC3.3C thru U0402FC36C

## PACKAGE OUTLINE & DIMENSIONS

PACKAGE OUTLINE		U0402	
<b>PACKAGE DIMENSIONS</b>			
DIM	MILLIMETERS	INCHES	
A	0.46 NOM	0.018 NOM	
B	0.86 NOM	0.034 NOM	
C	0.99 ± 0.0254	0.039 ± 0.001	
D	0.10 NOM	0.004 NOM	
E	0.35 NOM	0.014 NOM	
F	0.483 ± 0.0254	0.019 ± 0.001	
I	0.406 NOM	0.016 NOM	
<b>NOTES:</b> 1. Controlling dimensions in inches. 2. Decimal tolerances for mounting pad and outline: .xxx ± 0.05mm (± 0.002"). 3. Maximum chip size: 1.02 (0.040") by 0.51 (0.020").			
MOUNTING PAD		PAD DIMENSIONS	
DIM	MILLIMETERS	INCHES	
A	0.23	0.009	
B	0.48	0.019	
C	0.69	0.027	
D	0.46	0.018	
E	0.99	0.039	
F	0.20	0.008	
G	0.20	0.008	
H	0.66	0.026	
I	0.13	0.005	
<b>NOTE:</b> 1. Top view of tape. Metal contacts are face down in tape package.			
TAPE & REEL ORIENTATION			
<b>TAPE &amp; REEL ORDERING NOMENCLATURE</b> 1. Surface mount product is taped and reeled in accordance with EIA 481. 2. 8mm Plastic Tape: 7 Inch Reels - 5,000 pieces per reel. Ordering Suffix: -T75-1 (i.e., U0402FC05C-T75-1). 3. 8mm Paper Tape: 7 Inch Reels - 10,000 pieces per reel. Ordering Suffix: -T710-2 (i.e., U0402FC05C-T710-2).		<b>NOTE:</b> 1. Preferred: Using 0.1mm (0.004") stencil.  <b>Outline &amp; Dimensions: Rev 3 - 11/02, 0620</b>	

**COPYRIGHT © ProTek Devices 2005**

SPECIFICATIONS: ProTek reserves the right to change the electrical and or mechanical characteristics described herein without notice (except JEDEC).

DESIGN CHANGES: ProTek reserves the right to discontinue product lines without notice, and that the final judgement concerning selection and specifications is the buyer's and that in furnishing engineering and technical assistance, ProTek assumes no responsibility with respect to the selection or specifications of such products.

**ProTek Devices**

2929 South Fair Lane, Tempe, AZ 85282

Tel: 602-431-8101 Fax: 602-431-2288

E-Mail: [sales@protekdevices.com](mailto:sales@protekdevices.com)

Web Site: [www.protekdevices.com](http://www.protekdevices.com)