





For SILICA FIBER

TOHL40, TOHL50, TOHL60, TOHL100 TOHL101, TOTX50 + TORX28A

Series name (type)	Configuration	Input/output interface	Operating temperature (°C) (1)	Data rate (b/s)	Transmission distance (m)	Applicable fiber optic connector	Power supply
★★ TOHL40 (TOTX40/TORX40)		1 Vp-p 75Ω	-20 to 60	60 (Hz) to 6M (Hz)	2k (GI 50/125)	TOCP18A	+12V
TOHL50 (TOTX50/TORX50)		TTL	-20 to 70	DC to 20M (NRZ)	4k (GI 50/125)		+5V
TOTX50 + TORX28A (TOTX50/TORX28A)			0 to 50	1M to 20M (NRZ) Star Network Use		TOCP28A	(T) (2) +5V (R) (3) ±5V +200V
TOHL60 (TOTX60/TORX60)		TTL / ECL	-20 to 70	0.2M to 64M (NRZ)	2k (GI 50/125)	FO1 type (FC type)	TTL +5V ECL +5V -5.2V
★ TOHL100 (TOED100/TORX100)		(R) TTL	-40 to 85	DC to 20M (NRZ)			TOCP19 (SMA)
★ TOHL101 (TOED101/TORX101)							

Notes: (1) Only module
(2) Connector part, full-lock type
(3) Connector part, half-lock type

*: New products
**: Under development