

353-0802

## SOLID FATIGUE STEP

## KEY FEATURES

- ① Extremely comfortable to stand on and provides excellent levels of fatigue-relief.
- ② Made from an extremely durable rubber.
- ③ Can withstand high temperature environments, including spillage of hot metal or molten glass.
- ④ Interlocking tiles allow unusual shaped areas to be fitted with ease.
- ⑤ Isolated tiles can be replaced without the need to re-mat the entire area.



## SUITABLE APPLICATIONS

- ◆ Wet/Oily and Dry environments.
- ◆ Ideal for INDUSTRIAL use, and its ability to withstand high temperatures makes it suitable for WELDING BAY areas or other applications where spillage of hot materials may occur.
- ◆ Very effective anti-fatigue properties, therefore ideal for areas where employees stand for prolonged periods.

FATIGUE PREVENTION	WEAR TOLERANCE	SLIP RESISTANCE
Excellent	Excellent	Good

## PRODUCT DATA

<b>Material:</b>	SBR/NBR Rubber
<b>Appearance:</b>	Solid textured surface with high grip
<b>Chemical Resistance:</b>	Thickness: 16 mm nominal
<b>UV Resistance:</b>	Resistant to water, acid, degreasing agents and antifreeze.
<b>Operating Temperature:</b>	Resistant to UV
<b>Flame Retardancy:</b>	-20°C to + 160°C
	Conforms to DOC FF2/70 US Department of Commerce for surface Flammability. When forced to burn, Carbon Monoxide, Oxides of Nitrogen and Sulphur are emitted.

## INSTALLATION &amp; CLEANING

<b>Installation:</b>	Loose lay interlocking tiles
<b>Cleaning:</b>	Pressure wash or steam clean using, if required, a mild detergent.

## SIZES &amp; OPTIONS

<b>Sizes:</b>	0.9 m x 0.9 m tiles (each mat has 3 female and 1 male side)
<b>Options:</b>	Bevelled edges either in yellow or black, corner units and connectors (Installation guide available)
<b>Colours:</b>	Black
<b>Country of Origin:</b>	USA