


Advanced Power MOSFET

SSW/I4N80A

FEATURES

- Avalanche Rugged Technology
- Rugged Gate Oxide Technology
- Lower Input Capacitance
- Improved Gate Charge
- Extended Safe Operating Area
- Lower Leakage Current : 25 μ A (Max.) @ $V_{DS} = 800V$
- Low $R_{DS(ON)}$: 3.400 Ω (Typ.)

$BV_{DSS} = 800 V$
 $R_{DS(on)} = 4.0 \Omega$
 $I_D = 4 A$



Absolute Maximum Ratings

Symbol	Characteristic	Value	Units
V_{DSS}	Drain-to-Source Voltage	800	V
I_D	Continuous Drain Current ($T_C=25^\circ C$)	4	A
	Continuous Drain Current ($T_C=100^\circ C$)	2.5	
I_{DM}	Drain Current-Pulsed ①	16	A
V_{GS}	Gate-to-Source Voltage	• 80	V
E_{AS}	Single Pulsed Avalanche Energy ②	256	mJ
I_{AR}	Avalanche Current ③	4	A
E_{AR}	Repetitive Avalanche Energy ③	12	mJ
dv/dt	Peak Diode Recovery dv/dt ③	2.0	V/ns
P_D	Total Power Dissipation ($T_A=25^\circ C$) *	3.1	W
	Total Power Dissipation ($T_C=25^\circ C$)	120	W
	Linear Derating Factor	0.96	W/ $^\circ C$
T_J, T_{STG}	Operating Junction and Storage Temperature Range	-55 to +150	$^\circ C$
	Maximum Lead Temp. for Soldering Purposes, 1/8 " from case for 5-seconds	300	

Thermal Resistance

Symbol	Characteristic	Typ.	Max.	Units
$R_{\theta JC}$	Junction-to-Case	--	1.04	$^\circ C/W$
$R_{\theta JA}$	Junction-to-Ambient *	--	40	
$R_{\theta JA}$	Junction-to-Ambient	--	62.5	

* When mounted on the minimum pad size recommended (PCB Mount).

SAMSUNG
ELECTRONICS

SSW/I4N80A

N-CHANNEL
POWER MOSFET

Electrical Characteristics ($T_C=25^\circ\text{C}$ unless otherwise specified)

Symbol	Characteristic	Min.	Typ.	Max.	Units	Test Condition
BV_{DSS}	Drain-Source Breakdown Voltage	800	--	--	V	$V_{\text{GS}}=0\text{V}, I_D=250\mu\text{A}$
$\Delta \text{BV}/\Delta T_J$	Breakdown Voltage Temp. Coeff.	--	0.98	--	$\text{V}/^\circ\text{C}$	$I_D=250\mu\text{A}$ See Fig 7
$V_{\text{GS}(\text{th})}$	Gate Threshold Voltage	2.0	--	3.5	V	$V_{\text{DS}}=5\text{V}, I_D=250\mu\text{A}$
I_{GSS}	Gate-Source Leakage , Forward	--	--	100	nA	$V_{\text{GS}}=30\text{V}$
	Gate-Source Leakage , Reverse	--	--	-100		$V_{\text{GS}}=-30\text{V}$
I_{DSS}	Drain-to-Source Leakage Current	--	--	25	μA	$V_{\text{DS}}=800\text{V}$
		--	--	250		$V_{\text{DS}}=640\text{V}, T_C=125^\circ\text{C}$
$R_{\text{DS}(\text{on})}$	Static Drain-Source On-State Resistance	--	--	4.0	Ω	$V_{\text{GS}}=10\text{V}, I_D=0.85\text{A}$ ④*
g_{fs}	Forward Transconductance	--	2.92	--	S	$V_{\text{DS}}=50\text{V}, I_D=0.85\text{A}$ ④
C_{iss}	Input Capacitance	--	700	910	pF	$V_{\text{GS}}=0\text{V}, V_{\text{DS}}=25\text{V}, f=1\text{MHz}$ See Fig 5
C_{oss}	Output Capacitance	--	65	75		
C_{rss}	Reverse Transfer Capacitance	--	25	30		
$t_{\text{d}(\text{on})}$	Turn-On Delay Time	--	18	45	ns	$V_{\text{DD}}=400\text{V}, I_D=2\text{A}, R_G=16\Omega$ See Fig 13 ④ ⑤
t_r	Rise Time	--	29	70		
$t_{\text{d}(\text{off})}$	Turn-Off Delay Time	--	50	110		
t_f	Fall Time	--	28	65		
Q_g	Total Gate Charge	--	32	42	nC	$V_{\text{DS}}=640\text{V}, V_{\text{GS}}=10\text{V}, I_D=2\text{A}$ See Fig 6 & Fig 12 ④ ⑤
Q_{gs}	Gate-Source Charge	--	6.2	--		
Q_{gd}	Gate-Drain("Miller") Charge	--	13.9	--		

Source-Drain Diode Ratings and Characteristics

Symbol	Characteristic	Min.	Typ.	Max.	Units	Test Condition
I_s	Continuous Source Current	--	--	4	A	Integral reverse pn-diode in the MOSFET
I_{SM}	Pulsed-Source Current ①	--	--	16	A	
V_{SD}	Diode Forward Voltage ④	--	--	1.4	V	$T_J=25^\circ\text{C}, I_s=4\text{A}, V_{\text{GS}}=0\text{V}$
t_{rr}	Reverse Recovery Time	--	380	--	ns	$T_J=25^\circ\text{C}, I_F=4\text{A}$
Q_{rr}	Reverse Recovery Charge	--	2.89	--	μC	$dI_F/dt=100\text{A}/\mu\text{s}$ ④

Notes :

- Repetitive Rating : Pulse Width Limited by Maximum Junction Temperature
- $L=30\text{mH}, I_{AS}=4\text{A}, V_{DD}=50\text{V}, R_g=27\Omega$, Starting $T_J=25^\circ\text{C}$
- $I_{SD}\leq 4\text{A}, di/dt\leq 110\text{A}/\mu\text{s}, V_{DD}\leq \text{BV}_{DSS}$, Starting $T_J=25^\circ\text{C}$
- Pulse Test : Pulse Width = $250\mu\text{s}$, Duty Cycle $\leq 2\%$
- Essentially Independent of Operating Temperature

N-CHANNEL
POWER MOSFET

SSW/I4N80A

Fig 1. Output Characteristics




Fig 2. Transfer Characteristics




Fig 3. On-Resistance vs. Drain Current




Fig 4. Source-Drain Diode Forward Voltage




Fig 5. Capacitance vs. Drain-Source Voltage










Fig 6. Gate Charge vs. Gate-Source Voltage



SSW/I4N80A

N-CHANNEL
POWER MOSFET



N-CHANNEL
POWER MOSFET

SSW/I4N80A

Fig 12. Gate Charge Test Circuit & Waveform




Fig 13. Resistive Switching Test Circuit & Waveforms





Fig 14. Unclamped Inductive Switching Test Circuit & Waveforms



SSW/I4N80A

N-CHANNEL
POWER MOSFET

Fig 15. Peak Diode Recovery dv/dt Test Circuit & Waveforms

