




SS22L - SS215L

2.0 AMPS. Surface Mount Schottky Barrier Rectifiers

Sub SMA

Features

- For surface mounted application
- Low-Profile Package
- Ideal for automated pick & place
- Low power loss, high efficiency
- High current capability, low VF
- High surge current capability
- Plastic material used carriers Underwriters Laboratory Classification 94V-0
- Epitaxial construction
- High temperature soldering: 260°C / 10 seconds at terminals



Mechanical Data

- Cases: Sub SMA plastic case
- Terminal : Pure tin plated, lead free.
- Polarity: Color band denotes cathode end
- Packaging: 12mm tape per EIA STD RS-481
- Weight approx. 15mg

Dimensions in inches and (millimeters)

Maximum Ratings and Electrical Characteristics

Rating at 25°C ambient temperature unless otherwise specified.

Single phase, half wave, 60 Hz, resistive or inductive load.

For capacitive load, de-rate current by 20%

Type Number	Symbol	SS 22L	SS 23L	SS 24L	SS 25L	SS 26L	SS 29L	SS 210L	SS 215L	Units
Maximum Recurrent Peak Reverse Voltage	V _{RRM}	20	30	40	50	60	90	100	150	V
Maximum RMS Voltage	V _{RMS}	14	21	28	35	42	63	70	105	V
Maximum DC Blocking Voltage	V _{DC}	20	30	40	50	60	90	100	150	V
Marking Code (Note 4)		22LYM	23LYM	24LYM	25LYM	26LYM	29LYM	20LYM	2ALYM	
Maximum Average Forward Rectified Current at T _L (See Fig. 1)	I _(AV)	2.0								A
Peak Forward Surge Current, 8.3 ms Single Half Sine-wave Superimposed on Rated Load (JEDEC method)	I _{FSM}	50								A
Maximum Instantaneous Forward Voltage (Note 1) @ 2.0A	V _F	0.5			0.70		0.85		0.95	V
Maximum DC Reverse Current @ T _A =25°C at Rated DC Blocking Voltage @ T _A =125 °C	I _R	0.4					0.1			mA
		15			10		5		mA	
Typical Junction Capacitance (Note 3)	C _j	130								pF
Typical Thermal Resistance (Note 2)	R _{θJL}	17								°C/W
	R _{θJA}	75								
Operating Temperature Range	T _J	-65 to +125			-65 to +150					°C
Storage Temperature Range	T _{STG}	-65 to +150								°C

Notes:

- Pulse Test with PW=300 usec, 1% Duty Cycle
- Measured on P.C.Board with 0.27" x 0.27" (7.0mm x 7.0mm) Copper Pad Areas.
- Measured at 1 MHz and Applied Reverse Voltage of 4.0V D.C.
- 22LYM: 2=2A, 2=20V, L=Low Profile, Y=Year Code, M=Month Code.

RATINGS AND CHARACTERISTIC CURVES (SS22L THRU SS215L)

FIG.1- MAXIMUM FORWARD CURRENT DERATING CURVE




FIG.2- MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




FIG.3- TYPICAL FORWARD CHARACTERISTICS




FIG.4- TYPICAL REVERSE CHARACTERISTICS




FIG.5- TYPICAL JUNCTION CAPACITANCE




FIG.6- TYPICAL TRANSIENT THERMAL CHARACTERISTICS

