

FATIGUE STEP BLACK

KEY FEATURES



- ① Extremely comfortable to stand on and provides excellent levels of fatigue-relief.
- ② Open holes allow efficient drainage.
- ③ Surface design helps to prevent slips.
- ④ Interlocking tiles allow unusual shaped areas to be fitted with ease.
- ⑤ Can withstand high temperature environments including the spillage of molten glass.

SUITABLE APPLICATIONS

- ◆ Wet/Oily and Dry environments.
- ◆ Ideal for **INDUSTRIAL** use, and its ability to withstand high temperatures makes it suitable for **WELDING BAY** areas or wet applications where good drainage is essential to prevent slipping.
- ◆ Very effective **anti-fatigue** and **slip prevention** properties, therefore ideal for areas where **employees stand for prolonged periods.**

FATIGUE PREVENTION	WEAR TOLERANCE	SLIP RESISTANCE
Excellent	Excellent	Good

PRODUCT DATA

Material:	SBR/NBR Rubber
Appearance:	Smooth with 22 mm holes
Chemical Resistance:	Thickness: 16 mm nominal
UV Resistance:	Resistant to water, acid, degreasing agents and antifreeze.
Operating Temperature:	Resistant to UV
Flame Retardancy:	-20°C to + 160°C
	Conforms to DOC FF2/70 US Department of Commerce for surface Flammability. When forced to burn, Carbon Monoxide, Oxides of Nitrogen and Sulphur are emitted.

INSTALLATION & CLEANING

Installation:	Loose lay interlocking tiles
Cleaning:	Pressure wash or steam clean using, if required, a mild detergent.

SIZES & OPTIONS

0.9 m x 0.9 m tiles (each mat has 3 female and 1 male side)

Bevelled edges in yellow or black, corner units and connectors
(Installation guide available)

Black

USA

Sizes:

Options: PDF
维库一下

Colours: sc.com

Country of Origin: