




Features

- Powers ringing SLICs
- Overcurrent protection
- Surface mount design
- Superior transient response
- Non-isolated outputs
- Ultraquiet outputs
- 10 REN capability
- Compact design
- Simplifies assembly & test
- Fast time-to-market
- Remote inhibit
- Eliminates ALEL caps
- Patent 6,195,273

SPT5504C SLIC Power Module

Input Specifications

Voltage	4.75 VDC Min. 5 VDC Nom. 5.25 VDC Max.
Current	
No Load	120 mA Nom. 150 mA Max.
IBAT1 = 100 mA	1920 mA Nom. 1980 mA Max.
IBAT2 = 100 mA	750 mA Nom. 780 mA Max.
Disabled	20 mA Max.
Remote Enable	
Low = Enable	0.4 VDC Max. (open = enable)
High = Disable	4.0 VDC Min. (source ≤ 1 mA)

Output Specifications

Power	7 W
VBAT1	
Voltage	-74 V Min. -72 V Nom. -70 V Max.
Current	0 to 100 mA 10 REN (2 s on, 4 s off) 120 mA Min. (trip < 150 ms)
Ripple Voltage	15 mV Nom. 40 mV Max. (IBAT1 = 50 mA)
Temperature Coefficient (T -25 °C)	-25 mV/°C Nom. -40 mV/°C Max.
VBAT2	
Voltage (Two 50 mA Outputs)	-25 V Min. -24 V Nom. -23 V Max.
Current	0 to 100 mA
Ripple Voltage	5 mA Nom. 20 mA Max. (IBAT2 = 50 mA)
Temperature Coefficient (T -25 °C)	1.2 mV/°C Nom. 4 mV/°C Max.
VBAT2 Load Regulation (IBAT2 = 0 to 50 mA)	0.5 mV/mA Nom. 1 mV/mA Max.
VBAT2 Setpoint Accuracy	2 % Nom. 4 % Max.
Cross Regulation (IBAT1 = 0 to 100 mA)	0.1 mV/mA Nom. 0.2 mV/mA Max.

General Information

The SPT5504C is a member of Bourns Switch Power SLIC Power module family. The output voltages provide low-noise operation for very quiet off-hook conditions and on-hook transmissions. The SPT5504C is capable of 7 W total output power, with up to 100 mA available from each output rail.

The SPT5504C's easy to use surface

mount design and compact footprint minimize the board space dedicated to power (less than 1.4 in²). Its robust design ensures reliable power and eliminates the need for Aluminum Electrolytic capacitors. By integrating the entire power solution, the OEM customer saves time and money in engineering, debugging, purchasing hard-to-source components, test and inventory.

Output Decoupling

Although not specifically required for proper/specified operation of the SPT5504C, external decoupling capacitors may be employed to reduce noise and interaction with adjacent circuits. Output decoupling can be achieved by placing 0.1 µF ceramic caps at the load. Note that larger cap values can substantially increase the start-up currents drawn from the 5 V source.

Input Decoupling


Local input decoupling is recommended to reduce the apparent source impedance to the SPT5504C.

C2 0.1 µF, X7R ceramic
C1 100 µF, 10 V, low ESR tantalum (AVX TPS series or Kemet T495 series).

Fault Protection

- F1 may be used in distributed systems to isolate single-board failures.
- F1 should be ≥ 2.5 A, $i^2t \geq 0.2 \text{ A}^2 \text{ sec}$, $R \leq 25 \text{ m}\Omega$.

Product Dimensions



DIMENSIONS = MILLIMETERS
(INCHES)

TOLERANCES = (.xx) = ± .25
(.01)
(.xxx) = ± .13
(.005)

General Specifications


MTBF	2,100 kHrs Nom. Bellcore TR332 (40 °C)
Operating Temperature	40 to +85 °C



SPT5504C SLIC Power Module

BOURNS®

Product Schematic



PIN DESCRIPTIONS:

5 V _{in}	4.75-5.25 VDC input, <3 A
V _{BAT1}	-72 V, 100 mA output
V _{BAT2}	-24 V, 2 x 50 mA outputs
GND	Common input and output returns
Inhibit	Logic level remote inhibit (>4.0 V, source 1 mA). Enabled when open or <0.4 V.
NC	No connection



Reliable Electronic Solutions

Asia-Pacific: TEL +886- (0)2 25624117 • FAX +886- (0)2 25624116

Europe: TEL +41-41 768 5555 • FAX +41-41 768 5510

The Americas: TEL +1-951 781-5500 • FAX +1-951 781-5700

www.bourns.com