


Solved by **Sipex** **SP1084**
5A Low Dropout Linear Regulator

Features

- Low Dropout Voltage: 1.3V Typically at 5A
- Current Limiting and Thermal Protection
- Output Current: 5A
- Current Limit: 6.5A
- Operating Junction Temperature Range: 0 to 125°C
- Line Regulation: 0.015% (Typical)
- Load Regulation: 0.2% (Typical)
- Available in RoHS Compliant, Lead Free Packaging



Applications

- High Efficiency Linear Regulators
- Battery Chargers
- Post Regulation for Switching Supply
- Microprocessor Supply
- Desktop PCs, RISC and Embedded Processors Supply

General Description

The SP1084 is a series of low dropout positive voltage regulators with a maximum dropout of 1.5V at 5A of load current.

The series features on-chip thermal limiting which provides protection against any combination of overload and ambient temperatures that would create excessive junction temperatures. It also includes a trimmed band-gap reference and a current limiting circuit.

The SP1084 is available in 1.5V, 1.8V, 2.5V, 2.85V, 3.3V and 5.0V versions. The fixed versions integrate the adjustment resistors. It is also available in an adjustable version which can set the output voltage with two external resistors.

The SP1084 series is available in standard packages of TO-263-3, TO-220 and TO-252.




Figure 1. Package Types of SP1084



Pin Configuration




Figure 2. Pin Configuration of SP1084 (Top View)

Functional Block Diagram




Figure 3. Functional Block Diagram of SP1084

Absolute Maximum Ratings (Note 1)

| Parameter | Symbol | Min | Max | Unit |
|---------------------------------------|-------------------|-----|------|--------------------|
| Operating Junction Temperature Range | T_J | | 150 | $^{\circ}\text{C}$ |
| Storage Temperature Range | T_S | -65 | 150 | $^{\circ}\text{C}$ |
| Lead Temperature (Soldering, 10 sec.) | T_{LEAD} | | 300 | $^{\circ}\text{C}$ |
| ESD (Human Body Model) | ESD | | 2000 | V |

Note 1: Stresses greater than those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under "Recommended Operating Conditions" is not implied. Exposure to "Absolute Maximum Ratings" for extended periods may affect device reliability.

Recommended Operating Conditions

| Parameter | Symbol | Min | Max | Unit |
|--------------------------------------|-----------------|-----|-----|--------------------|
| Input Voltage | V_{IN} | | 12 | V |
| Operating Junction Temperature Range | T_J | 0 | 125 | $^{\circ}\text{C}$ |

Electrical Characteristics

Typicals and limits appearing in normal type apply for $T_J = 25^{\circ}\text{C}$. Limits appearing in **Boldface** type apply over the entire operating junction temperature range.

| Parameter | Symbol | Conditions | Min | Typ | Max | Unit |
|-------------------|------------------|---|-----------------------|-----------------------|-----------------------|------|
| Reference Voltage | V_{REF} | SP1084-ADJ, $I_{OUT} = 10\text{mA}$, $V_{IN} - V_{OUT} = 3\text{V}$, $10\text{mA} \leq I_{OUT} \leq 5\text{A}$, $1.5\text{V} \leq V_{IN} - V_{OUT} \leq 5\text{V}$ | 1.238 1.225 | 1.250 1.250 | 1.262 1.270 | V |
| Output Voltage | V_{OUT} | SP1084-1.5, $I_{OUT} = 0\text{mA}$, $V_{IN} = 4.5\text{V}$, $10\text{mA} \leq I_{OUT} \leq 5\text{A}$, $3.1\text{V} \leq V_{IN} \leq 6\text{V}$ | 1.485 1.47 | 1.5 1.5 | 1.515 1.53 | V |
| | | SP1084-1.8, $I_{OUT} = 0\text{mA}$, $V_{IN} = 4.8\text{V}$, $10\text{mA} \leq I_{OUT} \leq 5\text{A}$, $3.4\text{V} \leq V_{IN} \leq 6\text{V}$ | 1.782 1.764 | 1.8 1.8 | 1.818 1.836 | V |
| | | SP1084-2.5, $I_{OUT} = 0\text{mA}$, $V_{IN} = 5.5\text{V}$, $10\text{mA} \leq I_{OUT} \leq 5\text{A}$, $4.1\text{V} \leq V_{IN} \leq 7\text{V}$ | 2.475 2.45 | 2.5 2.5 | 2.525 2.55 | V |
| | | SP1084-2.85, $I_{OUT} = 0\text{mA}$, $V_{IN} = 6\text{V}$, $10\text{mA} \leq I_{OUT} \leq 5\text{A}$, $4.5\text{V} \leq V_{IN} \leq 8\text{V}$ | 2.822 2.793 | 2.85 2.85 | 2.879 2.907 | V |
| | | SP1084-3.3, $I_{OUT} = 0\text{mA}$, $V_{IN} = 6.3\text{V}$, $10\text{mA} \leq I_{OUT} \leq 5\text{A}$, $4.9\text{V} \leq V_{IN} \leq 8\text{V}$ | 3.267 3.234 | 3.3 3.3 | 3.333 3.366 | V |
| | | SP1084-5.0, $I_{OUT} = 0\text{mA}$, $V_{IN} = 8\text{V}$, $10\text{mA} \leq I_{OUT} \leq 5\text{A}$, $6.6\text{V} \leq V_{IN} \leq 10\text{V}$ | 4.95 4.9 | 5 5 | 5.05 5.1 | V |
| Line Regulation | ΔV_{OUT} | SP1084-ADJ, $I_{OUT} = 10\text{mA}$, $2.85\text{V} \leq V_{IN} \leq 10\text{V}$ | | 0.015 0.035 | 0.2 0.2 | % |
| | | SP1084-1.5, $I_{OUT} = 10\text{mA}$, $3.1\text{V} \leq V_{IN} \leq 10\text{V}$ | | 0.5 1 | 6 6 | mV |
| | | SP1084-1.8, $I_{OUT} = 10\text{mA}$, $3.4\text{V} \leq V_{IN} \leq 10\text{V}$ | | 0.5 1 | 6 6 | mV |
| | | SP1084-2.5, $I_{OUT} = 10\text{mA}$, $4.1\text{V} \leq V_{IN} \leq 10\text{V}$ | | 0.5 1 | 6 6 | mV |
| | | SP1084-2.85, $I_{OUT} = 10\text{mA}$, $4.5\text{V} \leq V_{IN} \leq 10\text{V}$ | | 0.5 1 | 6 6 | mV |
| | | SP1084-3.3, $I_{OUT} = 10\text{mA}$, $4.9\text{V} \leq V_{IN} \leq 10\text{V}$ | | 0.5 1 | 6 6 | mV |
| | | SP1084-5.0, $I_{OUT} = 10\text{mA}$, $6.6\text{V} \leq V_{IN} \leq 10\text{V}$ | | 0.5 1 | 10 10 | mV |

Electrical Characteristics (Continued)

Typicals and limits appearing in normal type apply for $T_j = 25^\circ\text{C}$. Limits appearing in **Boldface** type apply over the entire operating junction temperature range.

| Parameter | Symbol | Conditions | Min | Typ | Max | Unit |
|--------------------------------------|-------------------------|--|-----------|-------------------|-------------------|---------------------------|
| Load Regulation | ΔV_{OUT} | SP1084-ADJ, $0\text{mA} \leq I_{\text{OUT}} \leq 5\text{A}$, $V_{\text{IN}} - V_{\text{OUT}} = 3\text{V}$ | | 0.1 0.2 | 0.3 0.4 | % |
| | | SP1084-1.5, $0\text{mA} \leq I_{\text{OUT}} \leq 5\text{A}$, $V_{\text{IN}} - V_{\text{OUT}} = 3\text{V}$ | | 3 7 | 15 20 | mV |
| | | SP1084-1.8, $0\text{mA} \leq I_{\text{OUT}} \leq 5\text{A}$, $V_{\text{IN}} - V_{\text{OUT}} = 3\text{V}$ | | 3 7 | 15 20 | mV |
| | | SP1084-2.5, $0\text{mA} \leq I_{\text{OUT}} \leq 5\text{A}$, $V_{\text{IN}} - V_{\text{OUT}} = 3\text{V}$ | | 3 7 | 15 20 | mV |
| | | SP1084-2.85, $0\text{mA} \leq I_{\text{OUT}} \leq 5\text{A}$, $V_{\text{IN}} - V_{\text{OUT}} = 3\text{V}$ | | 3 7 | 15 20 | mV |
| | | SP1084-3.3, $0\text{mA} \leq I_{\text{OUT}} \leq 5\text{A}$, $V_{\text{IN}} - V_{\text{OUT}} = 3\text{V}$ | | 3 7 | 15 20 | mV |
| | | SP1084-5.0, $0\text{mA} \leq I_{\text{OUT}} \leq 5\text{A}$, $V_{\text{IN}} - V_{\text{OUT}} = 3\text{V}$ | | 5 10 | 20 35 | mV |
| Dropout Voltage | | $I_{\text{O}} = 5\text{A}$, $\Delta V_{\text{REF}} - \Delta V_{\text{OUT}} = 1\%$ | | 1.3 | 1.5 | V |
| Current Limit | I_{LIMIT} | $V_{\text{IN}} - V_{\text{OUT}} = 3\text{V}$, | 5.5 | 6.5 | | A |
| Minimum Load Current | | $V_{\text{IN}} = 10\text{V}$ (SP1084-ADJ) | | 3 | 10 | mA |
| Quiescent Current | | $V_{\text{IN}} = 10\text{V}$ (SP1084) | | 5 | 10 | mA |
| Ripple Rejection | | $f_{\text{RIPPLE}} = 120\text{Hz}$, $C_{\text{OUT}} = 25\mu\text{F}$ Tantalum, $I_{\text{OUT}} = 5\text{A}$, $V_{\text{IN}} - V_{\text{OUT}} = 3\text{V}$ | 60 | 72 | | dB |
| Adjust Pin Current | | $V_{\text{IN}} = 4.25\text{V}$, $I_{\text{OUT}} = 10\text{mA}$ | | 55 | 120 | μA |
| Adjust Pin Current Change | | $10\text{mA} \leq I_{\text{OUT}} \leq 5\text{A}$, $1.5\text{V} \leq (V_{\text{IN}} - V_{\text{OUT}}) \leq 4.5\text{V}$ | | 0.2 | 5 | μA |
| Temperature Stability | | $I_{\text{OUT}} = 10\text{mA}$, $V_{\text{IN}} - V_{\text{OUT}} = 1.5$ | | 0.5 | | % |
| Long Term Stability | | $T_{\text{A}} = 125^\circ\text{C}$, 1000Hrs | | 0.5 | | % |
| RMS Noise (% of V_{OUT}) | | $10\text{Hz} \leq f \leq 10\text{kHz}$ | | 0.003 | | % |
| Thermal Resistance Junction -to-Case | θ_{JC} | TO-263 TO-220 TO-252 | | 3 3 4 | | $^\circ\text{C}/\text{W}$ |

Typical Performance Characteristics




Figure 4. Dropout Voltage vs. Output Current




Figure 5. Output Voltage vs. Temperature




Figure 6. Line Regulation vs. Temperature




Figure 7. Adjust Pin Current vs. Output Current

Typical Performance Characteristics (Continued)




Figure 8. Dropout Voltage vs. Temperature




Figure 9. Short Circuit Current vs. Dropout Voltage




Figure 10. Load Transient Response




Figure 11. Line Transient Response

APPLICATION INFORMATION





Figure 12. Typical Applications of SP1084

Mechanical Dimensions

TO-263-3


Unit: mm(inch)



Mechanical Dimensions (Continued)

TO-220


Unit: mm(inch)




Mechanical Dimensions (Continued)

TO-252

Unit: mm(inch)



ORDERING INFORMATION



| Part Number | Voltage Range | Temperature Range | Package | Pin Count | Pack Qty |
|--------------------|---------------|-------------------|---------|-----------|----------|
| SP1084V2-L/TR | Adj | 0°C to +125°C | TO-252 | 2 | 2,500/TR |
| SP1084V2-L-1-5/TR | 1.5V | 0°C to +125°C | TO-252 | 2 | 2,500/TR |
| SP1084V2-L-1-8/TR | 1.8V | 0°C to +125°C | TO-252 | 2 | 2,500/TR |
| SP1084V2-L-2-5/TR | 2.5V | 0°C to +125°C | TO-252 | 2 | 2,500/TR |
| SP1084V2-L-2-85/TR | 2.85V | 0°C to +125°C | TO-252 | 2 | 2,500/TR |
| SP1084V2-L-3-3/TR | 3.3V | 0°C to +125°C | TO-252 | 2 | 2,500/TR |
| SP1084V2-L-5-0/TR | 5V | 0°C to +125°C | TO-252 | 2 | 2,500/TR |
| SP1084V1-L/TR | Adj | 0°C to +125°C | TO-263 | 3 | 800/TR |
| SP1084V1-L-1-5/TR | 1.5V | 0°C to +125°C | TO-263 | 3 | 800/TR |
| SP1084V1-L-1-8/TR | 1.8V | 0°C to +125°C | TO-263 | 3 | 800/TR |
| SP1084V1-L-2-5/TR | 2.5V | 0°C to +125°C | TO-263 | 3 | 800/TR |
| SP1084V1-L-2-85/TR | 2.85V | 0°C to +125°C | TO-263 | 3 | 800/TR |
| SP1084V1-L-3-3/TR | 3.3V | 0°C to +125°C | TO-263 | 3 | 800/TR |
| SP1084V1-L-5-0/TR | 5V | 0°C to +125°C | TO-263 | 3 | 800/TR |
| SP1084V-L | Adj | 0°C to +125°C | TO-220 | 3 | 50/TUBE |
| SP1084V-L-1-5 | 1.5V | 0°C to +125°C | TO-220 | 3 | 50/TUBE |
| SP1084V-L-1-8 | 1.8V | 0°C to +125°C | TO-220 | 3 | 50/TUBE |
| SP1084V-L-2-5 | 2.5V | 0°C to +125°C | TO-220 | 3 | 50/TUBE |
| SP1084V-L-2-85 | 2.85V | 0°C to +125°C | TO-220 | 3 | 50/TUBE |
| SP1084V-L-3-3 | 3.3V | 0°C to +125°C | TO-220 | 3 | 50/TUBE |
| SP1084V-L-5-0 | 5V | 0°C to +125°C | TO-220 | 3 | 50/TUBE |



Sipex Corporation

Headquarters and
Sales Office
233 South Hillview Drive
Milpitas, CA 95035
TEL: (408) 934-7500
FAX: (408) 935-7600

Sipex Corporation reserves the right to make changes to any products described herein. Sipex does not assume any liability arising out of the application or use of any product or circuit described herein; neither does it convey